MAY, 1940

McGraw-Hill Publishing Company, Inc.

Price 35c. per copy

In This Issue
SEA PLANE FLYING HITS NEW HIGH

AVIATION

The Oldest American Aeronautical Magazine

Published monthly; price 25c a copy. Subscription rates—United States, Canada, Mexico and Central American Countries $3.00 a year. All other countries, $5.00 a year or 25 shillings. Entered as second class matter September 3, 1938, at the Post Office, Albany, N. Y. under the Act of March 3, 1879. Volume 30, Number 5

NATIONAL AIR CARNIVAL

BIRMINGHAM, June 1st and 2nd

FUELING FACILITIES at the Airport where your ship can be refueled and lubricated with Texaco Aviation Products

(Left) GLIMPSE OF THE CROWD of more than 200 000 wide-eyed spectators at the National Air Carnival. This year's event will take place June 1st and 2nd, at Birmingham, Ala.

ADMINISTRATION BUILDING with hangar at the right. Here also are the headquarters and hangars of the 106th Observation Squadron

BIGGER better, more exciting than ever, the 1940 National Air Carnival at Birmingham, Alabama, June 1st and 2nd, bids you a gracious welcome

So popular was this event last year that more than 200,000 people witnessed this great spring spectacle

Here you can thrill to the sight and sound of the country's top-flight airmen stunting in the clouds or skimming around the pylons in feats of daring and hair-trigger precision in handling

Here, at the Municipal Airport, in true Southern fashion, you may have your ship cared for, and fueled and lubricated with *Texaco Aviation Gasoline* and *New Texaco Airplane Oil*. Using Texaco, you'll realize why—

More scheduled airline mileage, within the U. S. and to other countries, is flown with Texaco than with any other brand.

Texaco Aviation Products are available at all important airports, or through more than 2300 Texaco warehousing points.

The Texas Company, *Aviation Division*, 135 East 42nd Street, New York, N. Y.

Texaco Dealers invite you to tune in The Texaco Star Theatre — a full hour of all-star entertainment — Every Wednesday Night — Columbia Network — 9:00 E.D.T. 8:00 E.S.T. 8:00 C.D.T. 7:00 C.S.T. 6:00 M.S.T. 5:00 P.S.T.

TEXACO

TEXACO AVIATION PRODUCTS

DOUGLAS

NEW DOUGLAS WINGS FOR THE ROYAL DUTCH AIR LINES

K-L-M

"FIRST AROUND THE WORLD"

Now the World Over

Over its far-flung routes K.L.M. (Royal Dutch Air Lines) has built its reputation for dependable service with Douglas DC-2 and DC-3 equipment. Now K.L.M. augments its West Indies service with new Douglas DC-5 transports. Thus will travellers in Netherlands and British West Indies, Colombia and Venezuela enjoy the safety and comfort of the Douglas tricycle gear and be delighted with the airviews made possible by DC-5 high wing and circular fuselage construction. And K.L.M. profits by the operation and maintenance economies built into these latest Douglas transports. Douglas Aircraft Co., Inc., Santa Monica, Calif.

New Warner Super Scarab..

165 HIGH-STEPPING HORSES *that* STAY YOUNG

← 165 HP . . . 2100 RPM . . . 332 LBS. . . . 37¼" overall diameter . . . these are CAA approved specifications of the new Warner Super Scarab (at left). To keep this engine young and vigorous, Warner engineers specify tough, strong Nickel alloy steels which resist wear and withstand fatigue. Nickel alloy steels assure uniformly improved mechanical properties and long service life.

NICKEL STEELS

STANDARD IN SCARAB

SAE	
3115	Cam ring
3120	Rocker arm socket
3130	Crankshaft coupling pin
3130–3135	Prop hub retaining nut
3135	Rocker arm socket nut
3140	Crankshaft
3240	Cyl. head shrink ring
3250	Valve washer retainer
X4340	Crankshaft
4615	Cam idler drive shaft
4615	Generator drive shaft
4615	Pump idler drive shaft
4615	Crankshaft gear
2330	Con rod cap
2340	Con rod link
2340	Con rod master
3250	Roller sleeve

More sport when sport planes have more power. This 4-place Harlow is stepping out with a 165 HP Super Scarab built with reliable Nickel alloy steels.

Owners of private planes and airplane operators save money when stressed motor parts are made from strong, long-wearing alloys containing Nickel. Your inquiries are invited regarding these time-proved materials.

THE INTERNATIONAL NICKEL COMPANY, INC. 67 WALL STREET NEW YORK, N. Y.

BOEING DELIVERS

The First 4-Engine Altitude-Conditioned Transports

DELIVERY of the first BOEING 307 Stratoliners, heirs to the supremacy of the Flying Fortresses and the 314 Clippers, signalizes another outstanding BOEING achievement in aviation history. Not only does this event introduce a new era in over-land air transport progress, but it marks the climax of BOEING'S 4-engine program. This long-range program began with the construction of the Flying Fortresses, then came the 74-passenger Model 314 Atlantic type Clippers, and now the Stratoliners, designed to capitalize on the advantages of "upper level" flying.

BOEING is delivering five of the Stratoliners to TWA for transcontinental service, and three, known as "Strato-Clippers" to Pan American Airways. Six more Model 314 Clippers are now under construction for Pan American. Meanwhile, on a steady production line basis, BOEING has been delivering 4-engine Flying Fortresses for the past several months at the rate of one every four working days. Additional orders for still more advanced airplanes of the Flying Fortress type have just been received from the U. S. Army Air Corps.

Boeing has always built tomorrow's airplanes today!

BOEING AIRCRAFT COMPANY
SEATTLE, WASHINGTON

BOEING

STEARMAN
AIRCRAFT DIVISION
WICHITA KANSAS

The Drawing Board's The Place To Cure "FLUTTERING FLIPPERS"

IF THE HORIZONTAL members of your tail group wave a fluttery goodbye to the Mrs as you take off—if 'neutral' on the control column is anyplace between your knees and your map pockets—put it down as a case of Fluttering Flippers."



. . . And the Slickest Medicine is the Right Fafnir Bearings!

The tracing above shows how the chief engineer of a well-known aircraft plant licked "Fluttering Flippers" in his current production job * * You'll notice that he hasn't trusted anyone to put in "something just as good" . . . he's lettered "Fafnir" in the right place, right on the sketch! For countless problems that come up when friction threatens to creep into the engine or control system of an airplane, the solution's as simple as that In the Fafnir Aircraft line, you'll find the right bearing, already engineered to a maximum capacity/weight ratio, already provided with the right seals and shields and lubricant for the job * * No matter which Fafnir you choose, you can be sure it possesses the in-built quality that you and all other aircraft manufacturers have recognized for the past ten years Write for the Engineering Manual. The Fafnir Bearing Company, Aircraft Division, New Britain, Connecticut.

FAFNIR *Ball Bearings* { *For Aircraft Engines and Controls*

THE BALANCED LINE — MOST COMPLETE IN AMERICA . . .

THE *Lockheed* LOG

THE Lodestar

A PAYLOAD STAR *and a Pilot's Airplane, Too!*

The new Lodestar receives STAR billing with operators who use this 14-passenger Lockheed on regular schedules Yet in the day-in day-out routine of steady operation it is delivering the airline job for which it was designed, carrying large payloads at speeds that lower ton-mile and seat-mile costs

Naturally, operators value this kind of profitable performance But that isn't all! Pilots who fly these great transports at cruising speeds well over 200 m.p.h., with full loads, say, "It's a pilot's airplane" New responsiveness, ease of control and stability . . . These are inherent Lockheed qualities that make the Lodestar a favorite not only with operators who own them, but with the men who fly them!

Lockheed Aircraft Corporation, Burbank, California
Representatives Throughout The World

LOOK TO *Lockheed* FOR LEADERSHIP

Lockheed
RESEARCH

Lockheed
LUXURY

One of LOCKHEED'S new SEWING MACHINES

Yes, that's what it is. But it doesn't sew fabric. It "sews" Alclad aluminum alloy by a continuous row of spot welds, automatically spaced and so perfectly overlapped that scientific stress analyses prove this smooth union superior to riveted seams for many purposes.

It's just one step in the fabrication of a Lockheed, but it's the result of months of collaboration between Federal Machine and Welding Co. experts, electrical designers and Lockheed's Engineering Dept.

Advanced airplanes demand these advanced manufacturing methods. A forward step, such as this, may cut the weight 2 3% and increase the strength of a number of the airplane parts The sum total of all these small advantages makes the difference between just ordinary airplanes and Lockheeds.

Add up these improvements and you'll understand why airline operators the world over say—

Model for Model

LOCKHEEDS carry *greater* pay loads at *higher* speeds .... at *lower* costs!

CONTINENTAL goes LODESTAR, too!

Here's why ➡

Coronado spent torturous months on the "Trail of the Conquistadores" but today travelers of Denver, Colorado Springs, Pueblo, Santa Fe, Albuquerque and El Paso cover those same miles in luxurious minutes via Continental Air Line Lockheeds

Proof of operator and passenger enthusiasm lies in the fact that three new fourteen passenger Lodestars have been placed in service on Continental's "Sun Trail" route.

Here's a Lodestar floor plan. *Passengers* like it because it gives them 747 cu. ft. of cabin luxury--53 cu. ft. for each individual. (Compare that spaciousness per passenger to other transports.) *Stewardesses* like it because newly designed equipment, compactly fitted in 60 cu ft. of roominess, makes her duties easier *Pilots* like it because it handles as easily as a small airplane *Operators* like it because all these new comforts are combined with Lockheed s famous standards of high performance and profitable operation.



LOCKHEED AIRCRAFT CORPORATION • BURBANK, CALIFORNIA, U.S.A.

The SPERRY "FLYING LABORATORY"

The Birdmen's Perch

One thing we're strong for is giving credit where credit is due. Pennsylvania-Central Airlines has just begun its 14th year of operation. The Anniversary is noteworthy, for throughout that span, there has been *no fatality to passenger or crew member*. So, in our official capacity as Editor of the Birdmen's Perch, we hereby doff our helmet and bow very low to this unique record. And, as Manager of Gulf's Aviation Department, we want to say that we're downright proud that they've used our products for six years of that time—and since 1938 used them exclusively!

MAJOR AL WILLIAMS, alias "Tattered Wing-Tips," Mgr. Gulf Aviation Products, Gulf Bldg., Pittsburgh, Pa.

DOWN MEMORY LANE

Some of you veteran Perch fans may remember that back in December, 1937, a correspondent asked what happened when a bird tangles with a propeller. Whereupon half our readers promptly tangled with the other half in an argument that lasted till we called it off for lack of evidence in September, 1938. New evidence recently appeared in a *Newsweek* magazine paragraph reproduced below. Looks like both the "goodbye-bird" and the "goodbye-motor" factions were right.



MORE-THAN-MEETS-THE-EYE DEPT.

Ever notice how two fighters can look absolutely evenly matched until the bell rings? Then one will absorb punishment like a sponge while the other folds almost under one punch.



Oils are like that, too. They look alike, but there's no end of difference in their stamina. *The reason?* Just like with fighters, it's the way they're trained down or refined.

That's why we recommend Gulfpride Oil as *the* oil that can take it! For Gulfpride is refined not only by conventional methods but also by the Gulf-invented Alchlor process that works out up to 20% more surplus waste and sludge. And when you refine a 100% Pennsylvania that thoroughly, you've got a lubricant that can lick friction to a standstill!

FIGURE-SHARKS ONLY

A pilot with a fifteen passenger plane offered to take a high school class of 30—15 boys and 15 girls—for a ride. When they reached the airport, it was discovered that time would not permit more than one flight, hence half the class were out of luck. Hearing the teacher and principal decide to line the class up and count out every ninth pupil till only 15 remained, the star mathematician immediately figured out what places the boys should preempt so that every girl would be left on the ground. Can you do it?

We've got the right answer handy, so send in yours to Professor Wing Tips to be checked.

THIS MONTH'S WHOPPER

Dear Major:

Here is a story that I suppose you will have to publish as a whopper though it is as true as most of the stories we read in the papers about planes.

As we all know, airplanes need a good high-test and high octane gasoline like G A G (Adv.) But what most people don't know is that motorcycles do also. But maybe I better get into my story.

Last Sunday—a bright, sunshiny day—I was breezing along on my puddle jumper when to my disgust, dismay, etc., I had the experience that always befalls gents who take—not their best girl—but their mother-in-law out for a spin. You guessed it, I ran out of gas on a lonely road.

Well, sir, there was nothing for me to do but push popcycle and battle axe to the nearest service of gas, the local airport. When I got there, I found the only fuel on sale was Gulf Aviation. So, not without crossing my fingers against getting put out of even the dog house, I filled her up.

Then I wheeled her over to the runway. Old Frozen Face climbed on back, and I stepped on the starter.

Major, before I even knew what was coming off, we were off! Raced down the runway, took to the air, and headed for the moon. To give the old girl credit she never peeped. Just hung on and let me do the thinking.



Having read some time ago that the first planes were controlled by shifting the pilot's weight, I leaned to the right and cut the switch. Believe it or not, we came out of that right into with exactly enough speed to glide five miles back to the airport. You see, those tilted floorboards got too much pressure under them and tilted poppet, mad and me to under a fifty foot run.

Now here's the trouble, Major, also the blessing. I don't have a sole license, so the C.A.A. won't let me develop my new G A G flyingcycle without some dual instruction. And every cent I had saved went for railroad fare for my mother in law who left next day to live with my brother in California.

All contributions gratefully received—larger ones in proportion.

Paul F. Metzger

AVIATION

Established 1916

THE OLDEST AMERICAN AERONAUTICAL MAGAZINE

MAY 1940

Vol. 39, No. 5

McGRAW-HILL PUBLISHING COMPANY INC.
James H. McGraw Founder and Honorary Chairman

Editorial and Executive Offices
330 West 42nd Street New York N. Y

Publication Offices
99-129 North Broadway Albany N Y

Chicago 520 North Michigan Ave. — San Francisco, 68 Post Street
Los Angeles, 6121 Quitos Ave — Allwych London W C 2
Washington — Philadelphia — Cleveland — Detroit — St. Louis — Boston — Atlanta, Ga

JAMES H McGRAW JR, President — HOWARD EHRLICH, Executive V ce President
MASON BRITTON, Vice Chairman — G B PUTNAM, Treasurer
D C McGRAW, Secretary — J E BLACKBURN JR, Director of Circulation

Published monthly price 35c a copy Subscription rates—United States, Canada and Latin America, payable $3.00 a year All other countries $3 00 a year or 30 shillings Entered as second class matter September 3 1936 at the Post Office Albany N Y U S A under the act of March 3 1879. Printed in U S A Cable address — McGrawhill New York — Member of A B C. Copyright 1940 by McGraw Hill Publishing Company Inc 330 West 42nd Street, New York N Y The following publications are combined with AVIATION AERONAUTICAL ENGINEERING AIRCRAFT JOURNAL and THE AVIATION NEWS All rights to above names are reserved by the McGraw Hill Publishing Co

CONTENTS

REGULAR EDITION

AVIATION IS INDEXED IN READERS GUIDE TO PERIODICAL LITERATURE AND IN INDUSTRIAL ARTS INDEX

Flashes

Picked Up Along Editorial Airways

BACK TO THE DARK AGES?

» WITH NO MORE WARNING than was sounded in Europe's most recent "blitzkrieg," the White House issued an order last month that shocked the industry throughout its length and breadth, brought strong protests from aviation people to Washington, and made New Deal Congressmen join forces with their Republican opponents in violent objection. On the face of it, the order was simply a part of Reorganization Plan IV and recommended changing C.A.A. to C.A.B. (Civil Aeronautics Board) and abolition of the Safety Board. But the part that hurt most was the assignment of budgetary, personnel, and other controlling elements of the Board to the Secretary of Commerce. Opponents of the plan remembered the dark days of the old Bureau of Air Commerce and felt that the new set up would destroy the independence of the Authority which was the basic objective in its creation and which was written into the Civil Aeronautics Act at the insistence of the President himself.

Just why the President has reversed his stand on the independence of the C.A.A. no one seems to have discovered,—least of all Senator Pat McCarran, father of the Act, who was summoned frequently to the White House during the framing of the bill to be properly impressed with the desirability of independence for the new federal body. The Senator from Nevada has registered strong objections and has introduced a resolution against the adoption of the order.

It is too early to make a complete appraisal of this move which came as a surprise even to those members of the Authority nearest to the White House. If it may be interpreted simply as the result of the recommendations of the Brownlow Committee, it is unfortunate that aviation should be made a guinea pig for academic experimentation in government reorganization, particularly when the experiment may impair the operation of a successful existing agency. From the standpoint of the Administration it would appear to be exceedingly unwise to take any steps at this time which would have the appearance of tampering with the safety functions of the Authority. Such action in the light of the brilliant airline safety record, might easily start a storm of public protest that would make the air mail contract cancellation ruckus look like small potatoes in comparison.

In the brief period of its existence the Civil Aeronautics Authority, the Administrator, and the Safety Board have done a conscientious job. They have made a sincere effort to cooperate with the industry in the solution of its many problems. And they have burned plenty of midnight oil in the process. It may be possible to effect the proposed reorganization without serious impairment of the personnel and functions of the Authority. But whether or not this can be done depends directly upon the degree to which the Board can be kept free of the politics usually associated with the Department of Commerce. No matter what happens, no stones should be left unturned to oppose a return to the chaos and demoralization of the

Research Leaders: Dr. Joseph S. Ames, retired chairman; Dr. Vannevar Bush, present chairman; and Dr. George W. Lewis, Director of Research, have been important contributors to the twenty-five years of N.A.C.A. progress.

Flashes

old Bureau of Air Commerce of the middle thirties

» TWENTY-FIFTH BIRTHDAYS are rare in an industry as young as aviation, yet the past month marked a quarter-century point for the National Advisory Committee for Aeronautics. Since its establishment by President Wilson in 1915, the N A C A has grown from a bare idea to a government research institution which merits an important place among its counterparts in the other great nations of the world. The going hasn't always been easy. There have been times when purse-strings were controlled by those to whom basic research was a mystery and the N A C A meant nothing more than the name of a brand of cowling. There has been misunderstanding and attacks from those incapable of appreciating the necessity of long range research planning. But the N A C A has always come through. The present European war has provided a new appreciation of the need for fundamental scientific information in aeronautics. It has revealed to those heretofore uninterested, the vast research facilities of the totalitarian nations where such necessities are created without waiting for popular approval.

In a few months the new Ames Laboratories at Sunnyvale, Calif. will be in operation, supplementing the present facilities at Langley Field, Va. Later a new engine laboratory will be added. A new program to coordinate the work of the N A C A with that of industrial and educational laboratories is also underway.

Surely the N A C A has much of which to be proud on its twenty-fifth birthday. And the nation has an added sense of security in the knowledge that the quality of our research is second to none in the world.

» WE HAVE EATEN DINNERS GALORE and listened to speeches long and short in celebration of the air lines' first year of safety. Air line executives have grown weary under the burden of awards, testimonials and certificates commemorating this important accomplishment. Maybe it has been carried a little too far. The safety record is magnificent beyond question. It has been an important part of the great progress of air transportation in the past year. But let's not forget the other parts,—the phenomenal increase in traffic and the three million dollar profit. Then, if there ever should be another accident, it will not be quite so hard for the public and ourselves to take.

» IN THE COURSE OF A RECENT TRIP through the famous Henry E. Huntington library at Pasadena California we learned that one of the world's greatest collections of rare aviation books, prints and portraits has been assembled there and is available to qualified readers and researchers. Nucleus of the aeronautical library is the Maggs collection which includes books from 1650 through 1920, and covers especially the nineteenth century. Over 1500 items from the Maggs collection, plus 200 since added, are available.

» NEW FEATURES beginning in this issue include a monthly column of advice to private pilots by Jerry Lederer, of Aero Insurance Underwriters, whose news letters are already well known around the airports, and a new column presenting the private pilots' side of the picture by a well-known member of this group who prefers to remain anonymous. A monthly financial feature by Selig Altschul, including Barron's aviation index published by special permission, also begins in this issue.

IT PAYS TO FLY

"Maguire has been flying high without a pressure cabin"

Side Slips

By ROBERT OSBORN

» ACCORDING to the *New York Herald Tribune* the Safety Board of the Civil Aeronautics Authority has reported that pilots with less than 200 hours of flying time were responsible for 47% of the non-air-line accidents investigated. They recommended that the public should be careful in its selection of pilots for flying and suggested asking for the pilot's certificate when in doubt.

This is certainly good advice but we do hope the C.A.A. doesn't start requiring a pilot to display his license and photograph in the airplane, as is now generally required of a taxicab driver. Every such photograph we've seen so far has made the taxi driver look like Public Enemy Number One, and we're sure a similar requirement for an airplane pilot would have the same effect,—limiting passenger traffic to individuals wearing very thick glasses.

» THE PAPERS are making a big fuss over the fact that an eighty pound midget, living in Boston, has just obtained a pilot's license. Shucks, it has been well known for twenty years in

the aircraft industry that midgets must have been used for pilot, crew, and passengers in obtaining the advertised performance of almost all airplanes.

» IN the late-lamented Russo-Finnish War we're glad that the first practical test of dropping soldiers by parachute didn't work out so well. Reports stated that the soldiers were easily picked off by the ground troops they were supposed to surround. We've never relished the idea of a parachute jump all by itself, without having to duck and try to assemble a machine gun at the same time. Even if they got around to dropping us inside of a concrete pill-box or a whippet tank, we wouldn't like it.

» THE ARMY'S ANNOUNCEMENT of the new big bomber being built by the Douglas Company is certainly interesting,—seventy tons, two hundred and ten foot span, cruising range of more than six thousand miles, and more than fifty per cent bigger than the Dornier DO-X.

» WE'RE wondering if the structural engineers of the Army and Douglas took into account the fact that any airplane that size should be designed to withstand earthquake shocks as well as air and landing loads?

» SPEAKING of that 210 foot span,—we're betting it isn't listed on the Douglas drawings as exactly 210 feet. We've never yet found an aeronautical draftsman who could resist putting down exact dimensions, no matter how impractical they might be. So we have a hunch that the dimension on the drawings is 210.4625 feet or some similar figure.

» THE NAVY is now considering the construction of a dirigible aircraft carrier for use in coastal patrol. This dirigible is to have long range, possibly three times the speed of surface craft and, according to newspaper description, would never be used itself for direct attack on an enemy base. It would carry aircraft which would either be launched for making the attack on an enemy coastline or for the patrolling of our own coast line.

This all sounds practical enough except for one thing,—the matter of piping the Admiral, and his flying barge, aboard with the dirigible's officer and his side boys standing at attention around a large opening in the bottom of the dirigible. We've seen too many officers knocked flat by their own swords while standing still on dry ground. Of course they might wear parachutes and inflatable vests, in case of errors, but we doubt that the extra equipment would go very well, sartorially, with cocked hats and gold braid.

» WITH the great influx of foreign and domestic orders, the difficulty of obtaining materials, the turnover in experienced employees, and the necessity for financing plant expansions and machinery purchases, we are sure that all airplane manufacturing executives have plenty of headaches these days. Accordingly we'd like to pass along a helpful bit of poetical philosophy composed by Ed Noonan.

"When in trouble,
When in doubt,
Run in circles,
Holler and shout."

» WITH a hot political campaign just getting under way we're surprised that the recent sun spots which disrupted all telegraph and radio service, including the radio activities of the airlines, haven't been blamed on either political party by the other.

TAKE TO THE WATER

By Carl Norcross
Assistant Editor

Operators are missing a bet if they fail to follow crowds to the waterfronts, where substantial profits may be had from a seaplane base.

PAUL REVERE'S old slogan of, 'One if by land, and two if by sea,' might well apply to the operator's share of profits from a fixed flying base. As flying on floats becomes more popular every year, operators who are moving their bases to the water fronts are reaping a very practical harvest. Seaplane operation is striking a responsive chord with the American public, which seems ready and willing to pay cash for the fun of flying on the water.

The coming summer should be the best in history for seaplane operators. In the past year under the direction of CAA's Major A. B. McMullen, the joint CAA-NYA seaplane base program has added some 300 floats at strategic spots throughout the country and there will be more soon. This gives a seaplane pilot something that he has always needed—an easy way to get himself and his passengers ashore, and a way to refuel at specially designed docks where wings will not be damaged against high pilings or other obstructions. In short, the more seaplane bases, the more places there are to visit.

Seaplane operation offers the fixed base operator many advantages. The smart business man goes where the crowds are. No one needs to be told where the crowds are all summer long—when flying business is best. There is hardly a lake or river in America that is not lined with summer resorts. Along many of our coastal areas, especially along the East Coast with its hundreds of miles of inland waterways, people by the thousands swarm in from the large cities. And they all have money in their pockets.

An experienced seaplane operator who has had bases in half-a-dozen kinds of places, with both wheels and floats, summed up his recommendations this way.

"The ideal place for a fixed base operator," he said, "is one where there is a crowd of people. There must be a stable population from whom we'll get students and charter hops, as well as sight-seeing. Then there must be a transient population that will keep giving us a steady source of new customers. I also want my base located so that I'll get as much free advertising as possible—so that the crowds will see us taking off and landing many times a day. When you add these things all together, a seaplane base at a summer resort is the best bet."

Operators who are forced off busy airports by the airlines should consider moving to a water base. Here is a God-given airport which often stretches for miles. Perhaps the CAA

A summer scene in Port Chester, N. Y., where Long Island Sound offers miles of waterfront for seaplane pilots

Refueling Capt. Bob Fogg's CAA Fairchild at Jacksonville. CAA-designed floats have a lift hatch which gives easy access to drums used for flotation purposes.

One advantage of seaplane operation is that simple piers and floats are sufficient.

Every lake and river where crowds gather is a potential source of seaplane business.

has already provided the landing float. For a few hundred dollars a ramp can be built and an ingenious operator can construct a small marine railway and a Boston dolly for hauling his ship from the water. Many seaplanes are left in the water all summer and no hangar is needed.

The country has any number of seaplane operators who bless the day they left a hot dusty airport for the cooling breezes of a lake or river. Out in Seattle there are the Washington Aircraft and Transport organization, and Kurtzer Flying Service, who have good sized hangars on Lake Union and over fifteen seaplanes between them. Kurtzer has twenty CAA college students in addition to his regular work. Other Washington float operators are the Olympia Air Transport at Olympia, and Hubert & Dillon of Tacoma. In Portland, Ore. Art Whitaker, who is a Cub distributor, has been pushing seaplane flying for some time.

Several operators have found the lake regions of Michigan, Wisconsin and Minnesota are ideal places for summer operations. At Milwaukee the Lange Aviation Corporation has its base right in the city. Customers can practically step from their offices or homes right on to the base. Lange has Cubs, Luscombes and Fairchilds of his own, and many pilots in that area come to him in the spring to have wheels removed and floats put on their ships.

In Michigan, Irving Woodhams who operates out of the Kalamazoo airport also has a summer base at nearby Austin Lake where he has a ready-made crowd waiting for him. He operates several ships, including a Cessna, on floats. If his customers get tired of fishing at home, he can hop them up to the lakes in the wilds of northern Michigan in a few hours.

Charles L. Davis of Detroit, operating Seaplane Sales, Inc., does instruction work and hopping with three Cubs. Business is good, he tells us. Michigan has over 40 seaplane bases, due in a large measure to the active work of State Director Floyd Evans.

In Davenport, Iowa, Allied Aircraft Sales has a base on the Mississippi river. The operator there has a dock, a marine railway and a hangar recently constructed. On Medina Lake, some 20 miles out of San Antonio, Texas, a new seaplane base has been

(*Turn to page 94*)

Dewey Eldred's Taylorcraft on Ede floats over Miami.

Glenn Clark has his seaplane base right in the heart of Charleston, W. Va., and pilots who rent his planes have only a few minutes' walk from their homes or offices. Every flight his ships make is an advertisement for his business.

Right. Typical of the new interest in seaplane flying in the New York City area are these three bases at Ridgefield Park, N. J. These three operators have more than 200 active students. Many cities have similar water areas that could be used. (Aerial photo by Al Mummert)

Hunters and fishermen will rent your seaplanes if you give them a chance.



A Boston dolly being used for one of Bob Love's Stinsons at Boston. CAA will provide complete plans for dollies like this one, as well as designs for floats and ramps.

Top to bottom. 1. A two-wheeled beaching gear used with a Stinson at Seattle. 2. W. P. Ingersoll's marine railway at Crane Lake, Minnesota. 3. Passenger car used for towing at Fox Paw Seaplane Base, Fox Lake, Illinois. 4. An Aeronca on a small 4-wheel handling dolly, Inter City Airline, Boston.

DON'T GIVE UP THE SHIP!

To the 10,000 Civilian Pilot Training Students, we say, "Keep flying this summer".

Photo by Greenhoff

Cross-country flying with your friends will bring you new pleasures and aviation experiences this summer.

LIFE begins at 40 . . . hours! The real fun of flying is about to commence for the 10,000 new Civilian Pilot Training students. With the long, summer days just ahead, you are about to collect profitable flying dividends on your training investment.

There has been plenty of fun in the first 35 or 40 hours. We don't need to tell you that. You still get a kick out of recalling those first eight hours of instruction, and the deep thrill of your first solo. You'll *never* forget that! There was real satisfaction in the rest of your training, too, when step by step you mastered smooth take-offs and landings, precision turns and when you finally flew with the easy coordination that made you part of the airplane.

That was all fun—sure. But it was nothing compared with the enjoyment you will get out of being on your own. Up to now you've been like a circus horse, running 'round and 'round the ring, going through your paces under the eye of your instructor. That training had to come first, of course. Now you are soon to be on your own and you can do a little galloping across distant pastures. *You'll* be the boss.

Many of you live in the same area where you've been getting your instruction. You will want to buy flying time from your own instructor. If you have a summer job, you can still find plenty of time to fly during the long evenings and on weekends.

About half of you are at college away from home and if you fly this summer you will need to locate a new operator who rents airplanes. It is to you especially that we say, "Don't get rusty".

After you go home in June you will probably go out to the airport near where you live and perhaps things won't seem quite the same. There may be some strange faces, and you may not know the airport manager or the operators.

But don't let these things stop you from flying. At all airports, strangers quickly become friends. In your love of flying you have a bond that will soon make you one of the crowd. A few flights will make you feel at home on the field.

If the make of airplanes used near your home is different from the kind in which you learned, a few trips around the field with the operator will make you familiar with any differences. Most operators will not charge you dual time for these brief check trips. You may have learned to fly in a tandem ship, for example, and if the ones you will fly in this summer are side-by side planes, a short time in the air will make you feel at home. CPT instruction is basically sound and you can master differences in various light planes without any trouble.

Of course if you want to fly a larger ship in the class heavier than the light plane, you will need perhaps five hours of dual time. You will enjoy every minute of it. Flying different kinds of ships is always interesting and is something you should look forward to.

Summer flying, you will find, is a lot more pleasant than winter flying. The weather will be warm and balmy. Fields will be grass covered, and there will be no frozen ruts such as you bounced across last winter, or ponds of water and mud such as you encountered during the spring. The landscape is going to be much more interesting, too.

If you have been an aviation fan for several years, as is probably the case, you have spent plenty of time at airports watching other pilots climb into a cockpit and go zooming off across the field. Above all men around an airport, the pilot is most admired. This summer the crowds lining the field will be watching you as the center of attention.

One of the big thrills this summer

(*Turn to page 107*)

The country is filled with pleasant places for you to visit on your summer flights.

Photo by Greenhoff



STREAMLINED AIRCRAFT PRODUCTION

By
Don I. Carroll
Vice-President and plant manager, Vultee Aircraft, Inc

As told to
Chas. F. McReynolds
Pacific Coast Editor, Aviation.

MORE PLANES and more profit per square foot of floor space has been the aim of the Vultee Aircraft Company in the construction of its new factory. A special set of circumstances, combined with remarkable teamwork on the part of all the men who have worked to make this possible, has enabled us to realize the dream of all production men—the ideal factory for a given production problem—or at least as nearly ideal as anything planned and built by human beings may ever be expected to prove itself. For we have been able to design simultaneously a whole series of Vultee airplanes, the factory in which to build them, and the equipment with which to do the work. For some months now we have applied every facility at our command to the proper solution of this three-fold problem. The aircraft themselves—the Vultee basic and advanced trainers, basic combats, and pursuits—were planned to take advantage of every known production tool. At the same time the factory was laid out to provide for an expansion program which has increased our total floor space from 150,000 sq. ft. to more than 335,000 sq. ft. Those square feet of floor space were so planned as to eliminate every possible obstruction to smooth production. We sought to streamline the production line through eliminating lost motion or idle time of parts in process. And we tried to equip the factory with the latest and best machinery that we could build or buy. More than $650,000 has gone into the purchase of new machinery and equipment with which to build the millions of dollars worth of planes already on order.

Every phase of factory planning, every type of production problem, was considered from every possible angle during our planning period. As a result we believe that parts flowing through our plant are moving from 25 to 50 per cent less distance from raw stock to finished plane than in the average aircraft plant. But we have worked to eliminate other production losses also. Aware that a study has shown 70 to 85 per cent of all manufacturing time to be consumed in set-up, loading, and transporting operations, and only 15 to 30 per cent in actual cutting or forming, we have taken some drastic steps to reduce time spent in operations other than actual work. And then we have gone on and found ways to reduce work time by as much as 90 per cent, in some cases.

We have also taken great care so to plan and equip our plant that the need for specially trained personnel is kept at a minimum, and all personnel is given opportunity to reach full efficiency through having proper tools, adequate working space, full accessibility to work, etc. Further, we have streamlined the tooling process so that the skilled worker does not lose time from his work obtaining tools for his next work set-up. Instead we have a system of tool planning boards and tool runners. The operator posts on his planning board the list of tools to be needed for his next set-up. A tool runner services him by studying the board, drawing the needed tools, and placing them on his work bench ready for immediate use. The same tool runner returns the tools from the previous set-up at the time of the change-over.

But to give you a picture of what we have done, let me describe the plant layout, and take the reader through a quick tour of the various departments. The engineering department and executive offices are located at the front of the plant and partially separated from the main factory building by an alleyway which gives access to the stock rooms. Raw stock is stored all across the front of the main building, into which it is fed from the alleyway just mentioned. Great care



Don Carroll, left, discusses production with Vultee President Richard Millar.

Above. Final assembly hangar showing completed ships outside

Below. Fuselage production jig permits many men to weld and assemble steel tubing



has been taken to develop improved methods of handling and storing our raw materials. For example, sheet alloy is kept in racks mounted on casters, making any grade or gauge sheet material as readily available as a card in a filing cabinet. The store keeper simply pulls out the rack and removes the required number of sheets of metal. An overhead handling system is installed in the stock rooms for moving heavy or cumbersome materials.

An aisle separates the stock rooms from the metal fittings, machine shop and sheet metal fabricating departments, and in order to keep the movement of materials to an absolute minimum each fabricating department is located just opposite the section of the stock rooms which feeds it material. Steel stock is located at the left end of the stock rooms and feeds directly out to the metal fittings department.

Bar stock, tube stock, etc. is located approximately in the center of the stock rooms and is fed out to the machine shop just across the aisle. Sheet stock is stored to the right and fed out to the sheet metal department, located on the right side of the factory. When parts from the fabricating departments are completed and ready to go on to the next operation they pass through inspection and so as to obviate the necessity of back tracking to a centralized inspection department, separate inspection units are located directly in the path of the production flow. The sheet metal inspection unit is located at the far end of the sheet metal department, and one located at the end of metal fittings takes care of parts from this department and from the machine shop.

We have planned the plant in such a way as to eliminate insofar as possible the storage of formed parts and sub-assemblies. As each part or assembly is completed, it moves on to take its position in the assembly line. Parts taken from the three fabricating departments, after passing through heat treat, anodizing, sand blast, etc., begin to flow together in assembly operations.

Adjacent to and just beyond sheet metal, and the machine shop, is located the bench assembly department, from which parts flow on through the paint shop and into the wing, center section, or empennage assembly lines. The fuselage sub-assemblies begin to take shape to the left of bench assembly and as soon as the fuselage is removed from its master jig it takes its place at the beginning of the assembly line. At the present time two assembly lines are set up along the left side of the factory, one for the Vanguard pursuit and the other for the Valiant basic trainer type. The assembly line fuselage jigs are mounted on casters and move towards final assembly on a track. This keeps the production line flexible, and in the event we wish to move one airplane ahead of another or pull it out of the line for any reason, it can be done instantly.

The wing, center section, and empennage assembly lines located beyond the paint shop flow across the factory and into the final assembly line. Production is carefully scheduled so that these assemblies meet the line at just the right time. The power plant assembly line is located under the balcony on the left side of the factory. Fastened to the uprights which support the balcony is a track upon which steel plates, corresponding to the airplane firewall are mounted on rollers. In production an engine is bolted to one of these plates and all fittings up to the firewall are assembled on the engine as it moves down the track.

An overhead handling system moves the completed engine installations from the engine assembly line over to the airplane production lines. The airplanes on the basic trainer and pursuit production lines face each other, and the overhead handling system for the power plants brings the required engines down the center of the two lines, where they are swung into position and readily mounted on the airplane to which they are assigned. The final assembly and service hangar runs across the rear of the factory and has a clear 35 foot ceiling. Separate from the main factory building are the storage, shipping, maintenance, and drop hammer departments. In the drop hammer building are concentrated the foundry, wood and plaster pattern shops, and the hammer shop itself. Hammers vary in size from a small one accommodating dies as small as 50 lbs. in weight to a huge hammer using dies weighing up to 12,000 lbs. By separating the drop hammer shops from the factory proper the noise and jar of this work is kept away from the main production lines.

Next to the drop hammer shop is the Vultee wind tunnel, one of the first independent wind tunnels to be erected by any aircraft company on the West Coast. And at the far front corner of the main building, beyond the raw stock receiving rooms, is the experimental department. Here we have provided laboratory equipment for every form of testing up to and including stressing a full scale wing to complete destruction.

But to return to the production line itself, we have installed many interesting pieces of equipment. Not the least of such installations is our own completely equipped machine shop with batteries of Cleveland, Milwaukee, Van Norman, and other well known lathes, milling machines, screw machines, etc. Of great interest are the items of equipment which we have designed ourselves, or have had built to our specifications. Before sheet metal can be fed from raw stock to the sheet metal forming department it must be cut to pattern. For this work we have developed a radial router set-up with a rotary work table. We have increased production of this router as much as two hundred and fifty per cent through use of the rotary table, or "merry-go-round" with four set-up positions. This arrangement permits loading one position while the operator is routing and while still another workman is unloading a profiled stack of material. Thus an endless number of fully set-up work tables is fed past the router operator and he can concentrate all of his attention upon the operation of his machine. Provision is made for locking the turntable solidly in place while the router is working.

Not fifteen feet away from the routers are the power brakes and our new three column hydraulic press with motorized rotary platform and automatic cycle operation. This loading platform has three positions, one for loading, one for pressing, and one for unloading. Two operators are required, one to load and one to unload. Actual pressing operation is fully automatic and the element of hazard for the operator is entirely eliminated. The pressing head travels approximately two and a half times faster than any hydraulic press previously used for aircraft work. As the head rises after the pressing operation the rotary table automatically swings around to bring the next set of loaded dies into position for pressing.

Another unique machine, which represents an adaptation of wood working procedure, is the new Vultee high-speed milling machine developed

(*Turn to page 98*)

Vultee engineers designed and built this high speed mill, which runs in 10 000 R.P.M. A job that used to require 30 hours is done in two hours on this mill using specially designed cutters.

One man using this Erco automatic riveter can turn out twice as much work as he could formerly do with older methods.

Vultee factory is filled with latest type of machine tools which help in speed up production. Much of the $650 000 which was spent on new production equipment was invested in new types of lathes, mills, screw machines and other such equipment purchased from Cincinnati, Milwaukee, Van Norman, Cleveland and other machine tool manufacturers.



The trend to increased use of machines by aircraft plants is typified in this Vultee shop where brakes, shears, punches and other sheetmetal machinery is used.

Router work is speeded up as much as 250 per cent by this rotary router table which permits setup and unloading without interrupting the router operator

For a Ripe Old Age—

FOLLOW THE FLYING RULES

Private flying under a controlled program is 1,100 per cent safer than it was throughout the entire country last year.

By Tom Hardin
Chairman, Air Safety Board
Civil Aeronautics Authority

"THESE are not accidents. They are suicides!"—This blunt remark was made by a friend of mine after he had finished reading some recent airplane accident reports. The grim charge was not fair to the pilots because none took his own life or his passenger's life intentionally. But when one reads the cold, unadorned facts of an accident report he realizes that in most fatal accidents the pilot's complete disregard of flying rules is as deliberate as though he intended to destroy himself and his airplane.

The pilot failed to control his flying—to confine it within the limits of his training, experience and the dictates of good judgment.

Private flying cannot progress until the safety record is better. Thousands of potential pilots are kept away from flying because they are afraid of accidents. To a non-pilot, flying is somewhat mysterious, and what is unknown is often a little frightening. Given this feeling to begin with, it may take only one accident seen or heard about to drive the embryo pilot away from flying for a long time.

The great toll of private flying accidents is not necessary. A high-accident rate in any kind of flying can be improved, as the airlines have demonstrated conclusively. By a joint industry-government program, the airline record has improved year by year until the domestic airlines have now flown for more than a year without a single fatal accident in the entire United States. During the twelve months ending March 26 1940, the domestic airlines flew over 87,000,000 miles without a fatality. Yet during 1939 private flying had 189 fatal accidents in 182,000,000 miles—a fatality for every 963,000 miles flown. Discouraging as this figure is, it is an improvement over 1938 when there was a fatality for every 752,088 miles of private flying.

Improvement in private flying can be made. A high accident rate is no more inevitable in private flying than in airline flying. The CAA Civilian Pilot Training program furnishes the proof. More than 100,000 hours, or approximately 7,000,000 miles were flown in this program before the first fatality occurred. Up to April 1, CPT students flew about 122,000,00 miles per fatality, which is more than 1,100 per cent better than the entire private flying record for last year. The records of some of our best commercial flying schools and charter operators furnish additional proof that private flying can be safe.

Controlled vs. Uncontrolled Flying

Fatal accidents usually come from uncontrolled flying. The pilot either lacked individual control or discipline, or his instructor's influence did not reach out to restrain or direct the pilot. A few examples of uncontrolled flying are emphasized in recent accident reports.

During the six months ending March 1, the Air Safety Board reported fourteen fatal accidents caused by pilots starting or continuing flight into known adverse weather conditions without the equipment or training necessary for instrument flying. During the same period there were 45 fatal accidents reported that were caused by the pilot engaging in some sort of unnecessary maneuver close to the ground, or other brand of airmanship that might be classified as show-off or reckless flying.

In a recent six months period 14 fatal accidents occurred because pilots flew into known adverse weather.

Regularly we investigate accidents in which pilots met with disaster because they forgot to fill the gasoline tank or attempted to stretch their supply over too great a distance. During the last six months an average of one fatal accident a month has been attributed to this type of negligence.

A certain number of young men foolishly believe they are natural-born pilots and that they can fly without instruction. There are about half a dozen recent cases in which individuals with little or no recorded flying time brought death to themselves during their first, self-initiated attempt to fly without an instructor in the plane. In one instance, such a pilot had the audacity to attempt to test a new type of airplane. These incidents do not include the numerous cases in which meagerly trained pilots attempted to overstep their ability and brought injury not only to themselves but also to their unsuspecting passengers.



Forty-five pilots were killed in six months doing show-off flying.

Other accidents exhibiting the same general lack of judgment occurred as the result of pilots diving their planes until the wings cracked under the strain, or because they attempted to fly in some other manner inconsistent with the design characteristics of their equipment, existing conditions or pilot qualifications.

Whether or not these accidents involved show-off or reckless flying inspired by over-exuberance, or were just cases of negligence, carelessness or poor judgment, they all occurred due to lack of control. Pilots failed to discipline themselves and to exercise good judgment.

In *controlled* flying, on the other hand, as is exemplified by the teaching at our better flying schools and in the Civilian Pilot Training program, the instruction is so excellent that the student knows how to fly properly and he has a deeply ingrained sense of self-discipline. Teaching follows a pre-determined pattern in which nothing is overlooked or forgotten. Students are so prepared for emergencies that when one occurs they automatically do the right thing.

The most important step toward the eradication of suicidal flying and development of controlled flying in its stead is the early indoctrination of air discipline in the mind of the student flyer. This is a job for the instructor. Every instructor should be the idol of his students. He should guard his qualifications, character, and conduct with professional pride. They should be unimpeachable. The instruction and philosophy that he can impart to the student during early training days usually form the student's guiding light throughout the rest of his flying career. The instructor recertification program as recommended by the Air Safety Board and started last year should do much toward assuring us that all instructors will be more capable in handling this great responsibility.

One pilot a month is killed because he forgets to fill his gas tank.

The splendid safety record of the airlines has been mentioned. Airline operations are conducted by large organizations in which controlled flying is relatively easy to obtain as compared with improving private flying which is scattered over 2,500 airports and pasture fields throughout the country. Control in this latter type of flying is an individual matter, as the pilot is usually on his own.



Pilots who try to learn flying without an instructor usually become an "accident statistic".

But much can be done to cure a reckless pilot of his fool-hardy ways by group censorship. The cool reception of such an individual by fellow pilots will discourage his show-off tendencies and the creation of a public opinion that will deprecate the acts of the show-off will cut at the very basis for his conduct.

Other means of controlling the situation might be through local ordinances or state laws enforced by local authority, severe airport rules restricting operations of show-off pilots, and agreements between aircraft owners not to rent equipment to such pilots. Aeronautical organizations such as local N.A.A. chapters, flying clubs and aviation committees of local service clubs can greatly assist in promoting one or more of the foregoing safety control measures. These suggestions are not made with a view to increasing federal regulations, but rather as a means of providing practical enforcement of safety measures now covered by federal rules. Reference is made particularly to the restraint of pilots by local laws when pilots attempt to fly into known adverse weather conditions or desire to operate craft improperly serviced or maintained. We *may* need more federal regulations, but violations of existing regulations are clearly indicated in about 50 per cent of all fatal aircraft accidents.



Diving a plane until the wings crack off is a sure form of suicide.

Strict enforcement of regulations is not possible without individual and group cooperation from the aviation fraternity itself. An unreported violator cannot be prosecuted, neither can a dead one. It is not practical from an economic standpoint—nor desirable if it were possible—to place a federal police force on every one of nearly 2,500 airports throughout the country. Consequently, if we are going to have enforcement of safety regulations, it will have to come from the flying industry and each person within the industry, possibly assisted by local civil authorities.

Improving the safety record in private flying depends upon three factors: providing better basic training, controlling the reckless, show-off flyer, and in doing everything possible to provide a spin-proof and stall-safe airplane. This last development introduces a problem we have to solve with the assistance of aircraft designers and manufacturers. Past records indicate that if every airplane flying today could be made spin-proof and stall-proof the number of fatal accidents would be cut in half, if not more than half.

(*Turn to page 110*)



Fuselage is begun in jigs on left and is then moved on monorails until landing gears are installed at rear of this shop. Assembly line then moves forward as shown at right.

All metal stabilizers are assembled part by part on the two jigs shown here. Rivet holes are predrilled

How Luscombe Builds Metal Planes

By Charles E. Burgess

Production Manager
Luscombe Airplane Corporation



BUILDING light airplanes of metal construction brings many production problems which are not met in the factory where typical light planes are manufactured. Beginning with the Phantom, Luscombe engineers have had experience over several years with metal construction methods. The Phantom, however, was a hand-made airplane whereas the Luscombes rolling out of our factory doors today are produced as efficiently as possible and with a minimum of hand work. In our 24,000 square feet of floor space, new production methods now permit us to turn out four metal ships per day.

The present Luscombe has a full monocoque fuselage of 17ST Alclad skins, 032 and 040 thick, riveted to oval-shaped Dural bulkhead stampings. Wing spars are I-beam Dural extrusions, wing rib cap strips are T shape Dural extrusions. Wings are fabric covered. Tail surfaces and control areas are of channel section Dural covered with Alclad.

In order to produce an airplane of these more expensive materials, to sell in the low price class, it has been necessary to reduce the work done outside the factory as much as possible as well as keep detailed hand labor to a minimum within the plant. Progress towards this end has been most noticeable within the last year. Various jigs have been developed to enable the rapid assembly of detailed parts. For the most part these jigs are simple and are of wood or steel. Formerly all fuselage covering skins were drilled by hand after being fitted to the bulkheads in the fuselage jigs. This job, using predrilled skins as at present, has resulted in cutting production time almost in half.

The entire procedure of production is based upon the fast assembly of prebuilt parts to the airplane as it goes through the line on an overhead conveyor. Stamped bulkheads, obtained from Teicher Manufacturing Corporation, are predrilled in template forms in the sheet metal division, painted with P27 primer, and placed on a huge supply rack at the head of the assembly line. Small aluminum forgings, reinforcements, and fittings are riveted to the bulkheads to which wing struts and landing gear are attached. This riveting is done with Chicago Pneumatic jaw riveters prior to arrangement of these bulkheads in the fuselage jigs. Firewalls are of stainless steel shotwelded by the Edward G. Budd Company. Three suspension points are built into the firewall for the engine mount and a vee shaped welded steel tube structure joins the top suspension point to the superstructure at either side. The superstructure is of 17ST Alclad sheet with an oval Pyralin window built into the center of it. Deep extruded channel sections of Dural joining the wing butts, are riveted to the lower front and rear of the superstructure. Longitudinal L shaped extrusions on top on either side of the skylight provide further reinforcement for the superstructure.

The above mentioned parts, in addition to many others, are made up in quantities and stacked in the subassembly division of the plant. Large sheets of Alclad come into the Luscombe plant flat. These are cut on a Niagara shear in the required sizes. They are then assigned to their respective jigs where the are drilled. After this procedure they are curved to the desired degree on a rolling machine and stacked at the head of the fuselage assembly line. Once bulkheads and firewall are set up in the fuselage jigs, two of which are now in use, the predrilled skins are clipped to the bulkheads by Cleco spring fasteners. Rivets are inserted, covered by masking tape, and the main structure is then riveted together by four men in 3 hours and 40 minutes. The fuselage is then attached to an overhead conveyor and routed to the next production stage where the seat bottom is riveted in place and the landing gear legs are placed into position.

This landing gear is a unique arrangement and employs only a single oleo unit located within the fuselage at the center. The external landing gear leg is bolted into the sleeve of the lower part of the internal leg. The main landing gear leg is therefore two individual parts bolted together, the upper part of which will usually withstand the most severe damage to an airplane. This construction requires only that the lower leg be replaced in most cases involving landing gear damage. The landing gear is a heat-

(*Turn to page 102*)

Ships moving forward on assembly line after undercarriage has been added. Stabilizers, fins, engine mounts, engines, wind shields, panel boards and many other cabin fittings are added here before final assembly starts.

After stabilizer is assembled to fuselage, the vertical fin is made secure. Note convenient hand hole at right.



Mechanic on left is using a heat dolly to buck rivets on stabilizer, which is removed from jig for final riveting.

Wood jigs make wing assembly an easy matter. First jig has a right-hand wing, second has a left-hand wing.



Above, Corrugations in ailerons are made in this press brake replacing hand method.

Right: Until brake was installed, slower hand method was used to form aileron corrugations.

Ailerons are assembled on jigs like this. Temporary tacknees hold sheets in frame during riveting.

A detailed description of the Boeing Model 307, "Stratoliner" the first pressurized cabin ship to be delivered to the airlines.

By R. J. Minshall
Vice-President—Engineering
Boeing Aircraft Company



Into the SUB-STRATOSPHERE

TO say that the aviation industry is making a marked advance this year with the introduction of the four-engine Stratoliner type transport is not the whole story. It should also be stated in another way. The aviation industry has advanced *to* the Stratoliner. The whole background of knowledge and progress through the years—not only on the part of the airplane manufacturer but also the equipment and materials manufacturers, the air lines and allied industries—has made possible this new type transport. From results obtained, we sincerely believe that the Stratoliners and subsequent airplanes of the same general type will have a lasting place in the future of air transportation. The principles involved are sound.

When the idea of such a transport was conceived several years ago, it was based on several factors. It seemed apparent that the air transport industry would soon be ready for larger planes than the types then in operation. It seemed clear also that the larger planes would have certain advantages in addition to greater carrying capacity. The larger ship, by virtue of its size, would be more comfortable and more attractive to passengers because of additional conveniences offered. Along with this came the consideration of four engines. The Boeing Company was convinced of the desirability of four engines for such an airplane because of the outstanding success of its four-engine Army Flying Fortresses, and because of the demonstrated advantages of four-engine Flying Boats in transoceanic operation. The ability of an airplane to continue flight if one or even two of its power plants should fail appeared definitely attractive.

Then came the consideration of cabin supercharging—something entirely new. Sooner or later air transportation was going to get away from the conventional altitude limitations, and get away from the discomforts which admittedly were present when, for one reason or another, it was found desirable to climb above a certain conventional level. Should the projected Model 307 four-engine transport be the first to attack this problem? There was considerable discussion of the point. There was no doubt that it would be possible and practicable, but there would also be a good deal of expense involved, because it was a new field. The advantages of the supercharged cabin were so attractive that it was decided at the outset to make this a feature of the 307, and thereafter the name Boeing Stratoliner was created.

It was decided to use only a moderate degree of supercharging, because this simplified the process and at the same time brought within comfortable reach altitudes as high as would normally be desired for the first few years at least—up to 20,000 feet. In the range between 14,000 and 20,000 feet operators could over-ride most surface weather conditions, would have a wide margin of altitude over high terrain, and at the same time would gain higher speeds, smoother air, and steadier winds.

To gain this end required supercharging of approximately 2½ pounds per square inch (differential between outside and inside atmospheric pressure). The structure was designed to withstand supercharging of 6 pounds per square inch.

In developing the supercharging system and its equipment, and, for that matter, the mechanics of the whole airplane, simplicity and reliability were made the guiding principles. Thus the supercharging and pressure-regulating apparatus was made entirely automatic, with a system of control valves, check valves, safety valves, etc., all operating automatically, purely by action of the pressures involved. This leaves the operator merely the task of turning the apparatus on or off, and watching the few simple instruments that record the operation. It is possible, however, to control the equipment manually so as to continue operation in case of any malfunctioning of parts of the system. As an additional precaution, the system has been installed completely in duplicate. Either one of the two sets of apparatus can do the entire supercharging work.

The principle of practical simplicity likewise was carried out in the design of the supercharged cabin itself. It was made completely circular in cross-section from nose to tail, so that all atmospheric pressure loads are evenly distributed. This design has the additional advantage of providing excellent streamlining, and also provides a maximum cabin volume which is highly desirable for passenger accommodations.

The fuselage is a semi monocoque structure, consisting of 24ST Alclad covering stiffened by 24 ST extruded bulb angle longitudinal stiffeners and 24ST formed "J" section circumferential stiffeners. The circular fuselage skin is uninterrupted at the juncture of the wings. Skin thickness varies from .020 to .040, depending on loca-



The tail gear of the Stratoliner is of the single strut oleo-pneumatic type and is retractable into the fuselage. Tail wheel is full swiveling and provided with a caster lock controlled from the cockpit. Retraction is accomplished by means of a screw mechanism and electric motor.

A Boeing 307-B above the clouds. The ship is powered with four 1100 H.P. Wright Cyclones. Interiors designed for TWA have nine single reclining chairs on left side of cabin, and on right of aisle are four compartments seating six each in daytime which make up into four berths each at night. Interesting design features are wing tip slots and slotted flaps. Wing span is 107 feet, substantially the same as a B-17.

Inside the control room of the TWA version of the 307. The pilot is on the left, co-pilot on right, and flight engineer in the foreground. In the Pan American cockpit of this model, arrangements have been made for an additional seat behind the pilot to be filled by the radio officer

tion. Longitudinal stiffeners are spaced nine degrees apart around the periphery of the fuselage, and run continuous through the circumferential frames, which are notched. Circumferential stiffeners are spaced approximately 16 inches apart along the body centerline.

Loads from the wings, empennage and tail gear are distributed to the semi-monocoque body structure by trussed bulkheads. The main wing spar bulkheads are made up of hat section channels and square tube truss members. Part of the longitudinal stiffeners run continuous through the bulkhead hat section channels, while others are bolted to angle fittings. The passenger cabin floor is supported by a system of fore and aft and spanwise beams. The fore and aft beams are built-up "I" sections made from 24ST extruded tee and 24ST Alclad sheet stiffeners with 24 ST extruded rail and bulb angle stiffeners. The spanwise beams are 24ST extruded "I" and "Z" sections and are rigidly attached to the circumferential stiffeners at the sides of the body and to the fore and aft beams.

Demarking the rearmost end of the supercharged cabin is a hemispherical pressure bulkhead, consisting of a dome-shaped web of 24ST Alclad sheet with radial "J" section stiffeners. A removable circular hatch is installed in one side of this bulkhead to provide access to the tail section of the body. This bulkhead also contains a pressure relief valve which is set to discharge any pressure in the cabin in excess of 2.65 lbs. per square inch. This safety valve has a capacity to handle the full overload output of both cabin superchargers, to prevent excessive pressures in case of the remote possibility that all other controls should fail. The normal function of the automatic controls, of course, is to prevent pressures in excess of 2½ lbs.

The maximum diameter of the fuselage is 11½ feet. The floor level is located approximately one-third of the diameter from the bottom of the fuselage at its largest section. Cargo compartments and accessory compartment below the floor (all of which are accessible from within the airplane as well as through outside hatches in the bottom) are maintained under full cabin pressure. Cargo compartments have a combined capacity of 412 cubic feet, or 6590 pounds. An auxiliary entrance to the control cabin is provided through the bottom of the body forward of the front cargo hold, by way of a trap door in the cabin floor, and operating personnel may thus enter the control cabin without passing through the main passenger cabin.

Skin seams in the fuselage are sealed effectively by means of a tape impregnated with sealing compound, inserted between the laps prior to riveting. The seams include two rows of rivets diagonally spaced approximately ½ inches apart. All doors and hatches are sealed against leakage simply by soft rubber gaskets which press together when under the influence of cabin pressure. There are seventeen main passenger compartment windows each measuring 16 inches high and 12 inches wide. Like the rest of the cabin wall, they are designed to withstand 6 lbs. per square inch internal pressure. The windows are made of Plexiglas or Lucite (transparent plastics), curved to conform with body contour, and are sealed in rubber channels. Control cabin windshield and sliding side windows are ¾-inch safety glass. The sliding windows are mounted in steel frames which are seated against a rubber seal to prevent leakage of air or water. Fittings where control cables pass through the supercharged cabin shell are designed with a special gland, the result of a long process of experimentation, which allows them to slide freely with but a nominal amount of air leakage.

The Company was able to utilize features of their other large planes, and, with this background of knowledge, add to them the particular requirements of the new transport. The Stratoliner's wings, for example, are substantially the same as the wings of the B-17 type Flying Fortress. They are all-metal, tapered wings with a span of 107 feet 3 inches, and a symmetrical airfoil section. The root sec-

(Turn to page 116)

Large cabin volume is illustrated here. Semi-monocoque type of construction can be seen, and the extensive system of cross beams on which plywood flooring rests. Below is rear cargo compartment, with a volume of 200 cubic feet and load capacity of 3200 pounds. Ship's maximum cargo is 6580 pounds





Comparison of the cross-section of the Boeing Stratoliner with that of a typical streamlined train.

Interior of inboard engine nacelle prior to equipment installation. Semi-monocoque structure is similar to that used in Boeing 314 Pan American Clippers.

AVIATION
May, 1940
48

BENDIX RADIO

BENDIX AIR RADIO NEWS

MAY 1940 — Published by BENDIX RADIO CORPORATION, Baltimore, Md — Cable Address BENRAD

BENDIX RADIO EQUIPMENT ON THE NEW PAN AMERICAN GRACE DC-3'S

Help Maintoin 100% Plane-To-Graund Communicotian Over Long South Americon Route

New Airliners Flying Panagro Route From Cristobol To Santiago and Buenas Aires

The Famous Panagra Route is one of the most important articles of the South American Air Transport system. Flying over jungles, deserts and mountains, Panagra Airliners require Radio equipment of almost reliability to maintain communication with their ground stations. The installation of Bendix Equipment is playing an important part in maintaining the high record of safety and reliability the line has established over this difficult route.

New Pan American Grace DC-3 Airliner, with the passengers disembarking at Cristobal, Canal Zone. These giant airliners offer safe, modern, luxury service connecting Buenos Aires on the East Coast, Santiago on the West and Cristobal, Canal Zone, 4½ days from Buenos Aires to New York. They serve 21 cities and 7 countries, covering the west coast and mid-central section of South America.

Panagra Field at Lima, Peru. This field is an important link in the Panagra Line and is one of the five points served in Peru. The operations control office is located at Lima and it also has one of the 42 radio stations established by the Line to provide weather service and to maintain constant communication with the Airliners at any point in the Route.

The Bendix TA-2 Transmitter provides an output of 180 watts on any of 8 channels, each of which can be selected automatically from the operating position. This famous Bendix Transmitter has proved its reliability in practically every country of the world in airline, military, naval and other type services, and is representative of the high engineering refinement and dependability of Bendix Radio Equipment.

BENDIX—STANDARD FOR THE AVIATION INDUSTRY

AVIATION FINANCIAL TRENDS

By Selig Altschul

THE most sensational market performing group in recent months has not been the "war babies," but their counterpart, a peace time "specialty." Although the aircraft manufacturing group rallied the market at the outbreak of European hostilities last September, it remained for the air transport stocks to record the best gains to date. This performance is clearly portrayed by the accompanying chart showing the action of the general market as contrasted with that of the two aviation groups.

Stimulated by an outstanding safety record and continuing to attract an increasing percentage of the travelling public, the air lines commenced to realize the earning power they were known to possess. Investors, quick to appraise the changing tide in the fortunes of the industry, rapidly bid up the prices of air line equities. Present market prices evaluate the entire domestic air transport industry at approximately $130,000,000. By way of comparison, at the time of the passage of the CAA in June, 1938 it would have been theoretically possible to purchase the equity of the entire industry for less than $35,000,000.

The growth characteristics of the industry may well justify this almost four-fold increase in market values in less than two years. Cool perspective however, may check any wild hysteria for air transport equities. Total assets of the industry as of December 31, 1939, aggregated about $47,000,000. Gross operating revenues reported for the year 1939 totaled about $52,000,000 with net earnings less than $3,200,000. Admittedly, 1940 earnings may easily double 1939 results, but may not continue at a rate to generate spiraling higher market prices from present levels.

Available reports for the early months of this year augur well for a new high in earnings for 1940. Estimates place the industry at the break-even point for the first quarter of this year. During 1939, the industry did not start showing a profit until April and it was not until June that it offset its losses of previous months.

Of the major companies, American and Eastern thus far are showing the greatest improvement over 1939.

Estimates for the full year 1940 by all companies are extremely optimistic.

American estimates that it will fly almost 315,000,000 revenue passenger miles in 1940, compared with 207,360,215 in 1939, an increase of 51.9%. This should place American's passenger revenues over the $16,000,000 mark, as compared with $10,712,958 for 1939. This, of course, assumes that no material reduction will be made in passenger fares.

United Air Lines also estimates an increase of 52% in revenue passenger miles for 1940 over 1939. On this basis, revenue income should be increased to about $11,500,000 as contrasted to $7,621,801 for 1939. The

(Turn to page 120)

		Barron's Aircraft Average	Barron's Transport Average	Barron's 50 Stock Average
Sept	1, 1939	36 t0	14 38	78
	8,	40 25	t6 41	86
	t5	42 65	t7 12	90
	22	42 80	t7 12	91
	29	41 12	t6 91	90
Oct	6	41 50	t7 09	90
	t3	42 22	17 78	9t
	20	45 03	t8 69	9t
	27,	46 38	t9 47	92
Nov	3	48 65	t9 53	93
	t0	45 32	19 22	87
	t7	45 12	20 03	89
	24	43 35	19 t2	89
Dec.	t	41 42	18 T2	86
	8	42 30	19 62	89
	t5	43 68	21 34	87
	22	43 75	21 94	87
	29	44 t5	23 06	87
Jan.	5, t940	43 98	22 8t	90
	t2,	4t 52	2t 72	87
	t9	42 80	21 9t	85
	26	44 38	24 25	86
Feb	2	44 65	23 78	85
	9	46 08	24 47	87
	16	45 03	23 78	87
	23	44 52	24 09	87
Mar	t,	44 00	23 94	86
	8	46 t5	25 91	87
	t5	43 75	26 8t	87
	21	44 50	29 38	86
	29	45 50	30 81	87
Apr.	5,	46 95	34 00	88



Curtiss-Wright's New

BASIC COMBAT FIGHTER

THE Curtiss-Wright C-W 23 is a new high-speed, heavily-armed basic combat plane which is being made in the St. Louis Airplane Division. It is a two-seater designed to have a wide variety of uses

While designed primarily as a combat ship, it may also be used for tactical training missions, attack gunnery, aerial photography, light bombing, photographic gunnery, radio communications, long range observation and reconnaissance, and for instrument flight assignments

The ship is an all-metal, low-wing monoplane with fully retractable landing gear Top speed is over 325 m p h and the airplane can climb over 3,000 feet per minute Design permits armament of six .30 and 50 caliber Colt-Browning machine guns located in the wings, rear cockpit and fuselage The rear cockpit is equipped with controls and swiveling seat so that both pilotage and flexible gunnery operations may be performed from that position

The "Tell-Tale" system, a visual signal device developed by Curtiss-Wright for directing the pilot's attention to improper operating conditions as well as identifying the specific items at fault, is installed in the front cockpit This indicator panel contains seven sets of warning lights for "Fuel Pressure Low", "Oil Pressure Low", "Tank Selector Off", "Mixture Lean", "Low Prop R.P.M.", "Flaps Down" and "Landing Gear Not Locked", and a test button identifying burned out lamps

The two cockpits arranged in tandem are fully enclosed, have sliding transparent panels on each side, and are equipped with cockpit and instrument lights. Both cockpits contain pilot controls for the elevator, aileron, rudder, elevator and rudder trim tabs, foot brakes, engine and propeller unit, fuel tank selector valve and wobble pump The front cockpit contains, in addition, a hand parking brake control, hydraulic hand pump, engine primer and starter control and electrical control panel. The windshield of acrylic plastic is in one piece Latches on the two outward swinging doors are "rotary" type.

The fuselage is of semi-monocoque construction with a covering of skin of aluminum alloy sheet A baggage compartment is provided.

The engine mount with a steel tube engine mounting rug having welded lugs containing rubber cushions, is mounted to the fuselage by four fittings of the "quick detachable" ball and socket type

The airplane may be powered with a 9-cylinder Wright Cyclone engine or a 9-cylinder Pratt & Whitney Wasp, and is equipped with an automatic constant speed propeller controlled from either cockpit

Aluminum sheet used for cowling is reinforced with channel and hat section stiffeners, and consists of three parts each covering approximately 120 degrees of the engine periphery The cowl design is unique in that the two upper parts are fitted tightly to the fuselage at the rear of the cowling thus the cooling air enters the front of the engine compartments evenly around the periphery of the engine, but is exhausted at the bottom only

Left and right main fuel tanks, each of 50 gallons capacity are integral in that they are liquid tight compartments in the center section structure. A fuel gauge selector switch is incorporated in the pilot's selector dial The carburetor fuel pressure outlet is connected to the "Tell-Tale" panel fuel pressure warning signal so that a light will indicate low fuel pressure The oil tank has a service capacity of 9 45 gallons, and an overload capacity of 12 75 gallons with ample provision for expansion, and is mounted in front of the fire wall

The electrical system is a 12-volt single conductor, grounded system except where two conductor circuits are necessary to avoid compass magnetic interference The starter installation consists of an electric hand inertia type starter controlled from the front cockpit with a cranking attachment extending through the engine cowl for hand cranking Instruments in the front and rear cockpit are lighted by individual rim lights; cockpit lights illuminate control equipment. The plane is electrically shielded and bonded for radio

The wing, of multi cellular riveted construction, is made up of outer panels bolted to a center section, the latter being integral with the fuselage Wing tips are removable. External riveting of the forward 30% of the chord of both upper and lower surfaces is of the flush type, the remainder of the heads being of the brazier type The airfoil contour is maintained by aluminum alloy formed sheet metal ribs; the bottom structural member of the center line is a strong aluminum alloy inverted 'T' section, intended to serve as an emergency landing skid in the event of a landing with retracted wheels

Split trailing edge flaps extend from one aileron inner edge to the other The flaps are actuated by a hydraulic cylinder which is controlled by a valve in the cockpit, their position being shown by an electrical indicator so that partial flap deflections for take-off can be obtained by manipulation of the control valve.

The aileron, of all metal aluminum alloy construction, consists of a channel spar, channel ribs and sheet metal covering A continuous type hinge is riveted to the front of the spar The hinge pin is hardened steel wire; the control horn, of aluminum alloy, is riveted to the spar near the inner edge of the aileron The ailerons are dynamically and statically balanced.

The landing gear, actuated hydraulically by means of a power system or emergency hand pump is automatically locked in the down position.

Ailerons and elevators are operated by the conventional stick The aileron operating cables are so fastened to a quadrant mounted on the torque tube connecting the two sticks that the severance of one cable, within or without the cockpit, will decommission but one aileron, thereby permitting continued control of the airplane For elevator operation, a short push-pull tube is fastened to the lower end of the rear stick The rudder is actuated by cables fastened to the pedal support links. Ball bearings are used at all major points in the control system

The stabilizer, of all metal construction, is cantilevered from and is integral with the fuselage. Stabilizer tips and fin tip are removable Fin construction is similar to that of the stabilizer, being of aluminum alloy, cantilevered from and integral with the fuselage The rudder construction is similar to that of the elevator but there is only one shear web at

(Turn to page 110)



Maintenance Note Book

Fairchild Trainer for 1940

WITH the attitude of the Air Corps apparently drifting towards the low wing primary trainer it is important when a new model of this type of ship has been accepted. The Fairchild M-62 has been designated by the Army as the PT-19 and at present is in quantity production at the Fairchild plant in Hagerstown.

Built to have a strength factor of 10 the new trainer has the ATC #724. Aerodynamically the wing has been designed so that the wing tip should remain unstalled even after the wing root has passed the stalling point. Ease of servicing has also been a prominent feature of the design and in addition to the regular inspection holes large inspection panels have been placed at important points on the ship and can be easily removed.

The fuselage is of welded 4130 chrome molybdenum steel tubular structure. Wood fairing and fabric covering are employed except that the top of the fuselage aft of the cockpit is metal covered. Army type seats are adjustable vertically 7½ inches and are designed to accommodate seat pack parachutes. Rudder pedals are adjustable in three positions, and a parking lock is supplied to lock the rudder bar in neutral position and the stick in forward center position.

The wing construction consists of a center section and two outer panels with conventional two-spar construction, both spars being at 90° to the plane of symmetry. Ribs are Warren truss type with spruce cap strings and bracing, and end ribs, landing gear ribs and those at the fuselage attachment are chrome molybdenum. Split flaps, manually controlled, extend from fuselage to outer wing panel. Ailerons are statically and aerodynamically balanced fabric-covered aluminum alloy structures and are differentially controlled.

The plywood-covered wing was chosen for its structural characteristics of lightness and large torsional rigidity. The improved type of plywood used for the wing cover is of the phenolic glue bonded type which has been developed from plywood used previously in aircraft construction. Phenolic resin gives a glue line which is stronger than wood in shear; is insoluble in warm or cold water, in dilute alkalis, acids and such organic solvents as alcohol, benzine and ether. Dry or humid conditions do not affect it; it is repellent to living organisms, and it is not attacked by mold or fungi. When properly set by heat, phenolic resin glue is a hard inert solid which does not deteriorate with time or exposure. The plywood cover is pre-

(Turn to page 126)





The fuselage of the Fairchild Trainer is of welded steel tube construction. The structure just aft of the front cockpit is the crash bulkhead which supports the ship in case it noses over. The complete unit including oil tank, engine and accessories is detachable at the fire wall.

The steerable tailwheel is controlled through the arm at the top that extends rearward in the drawing. The section that is removed is the inspection plate.

FLIGHT TEST

of the Curtiss-Wright Transport

IT TOOK less than ten seconds for the 19-ton Curtiss-Wright Transport to leave the ground once the blocks were pulled to start its maiden flight. This is but one of the many pertinent results that came out of the ships first test flight. It isn't every day of the year that its possible to look into the report of such a flight test and the following paragraphs taken from the Curtiss-Wright report are aimed at giving a summarized picture of what went on while the transport was put through its paces.

Eddie Allen has been in charge of the flight testing being assisted by Dean Smith and Willis Wells of Curtiss-Wright's St. Louis plant.

"The new airliner, technically known as the CW-20 was loaded to 27,000 pounds gross weight at a C. G. of 24% of the M. A. C. for the first flight. The wind was 20 M. P. H. and the airport (St. Louis) pressure altitude was 310 feet. Most of the tests were conduced at 4,000 feet.

"Power used in take off was 1150 h.hp. per engine which corresponds to a take-off loadmg of 11.75 lbs. per hp. This is a higher loading than it will maintain when maximum take-off gross weight and power are later used.

"The flaps were set for take-off at 15° or about one quarter of their full travel. This angle was decided upon as a result of simulated takeoff tests and seemed to be a comfortable compromise. During the flight the flaps were raised and lowered several times and operated perfectly. Longitudinal trim was practically unaltered when flaps were moved, and the airplane seemed quite as readily controllable with flaps in any position. At one time with the airplane flying at low speed and power the flaps were retracted at full retraction rate with practically no loss of attitude. The landing gear and tail wheel were raised a short time after take-off and lowered just before landing. The retracting mechanism, safety latches, and position indicators seemed to act promptly and positively.

"Preliminary tests were made of air control effectiveness and stability. The use of power controls made handling easier, despite the fact that surface tab balances were set in their least effective positions to avoid any possibility of overbalance. The power controls were used during most of the test.

"Tests were made with various rpm and b.m.e.p. readings. Changes in throttle setting seemed to have but a minor effect on longitudinal trim even when flaps were used. With an outside air temperature of 50° F. at no time during the flight and including the take-off period did any cylinder head exceed 380° F. Without cowling changes it now seems perfectly feasible to hold the maximum temperature for cruising to a constant value of 400° F. under any air conditions.

"While the airplane was only maneuvered gently and not flown at high speed, there were no skin wrinkles in evidence and no tendency of any part to vibrate or flutter was noted. No difficulties of any kind were experienced with power plant operation, brake operation, instrument vibration, hydraulic system, electrical system or other units where difficulty is frequently experienced on the first flight."

The new Curtiss-Wright Substratosphere transport is one of the largest airliners to have been built having a wing span of 108 feet and being 75 feet long and being 19 feet 2 inches in height. Her two 1700 H. P. Wright Double Row Cyclone engines equipped with two three-bladed 15-foot Curtiss Electric controllable pitch, full-feathering propellers, provide her with a cruising range of 210 M. P. H. and a maximum speed of 243 M. P. H.

Lenape "Brave"

95-hp. engine for light planes

Flying Equipment



By Everett Rudloff
Lenape Aircraft Motors, Inc.

ANTICIPATING a growing need for a moderately powerful training engine and for a more flexible power unit for the heavier sport planes that will be light in weight, the Lenape Aircraft Motors, Inc., of Matawan, N. J., is about to start production on a five-cylinder radial 95 hp engine which has been contemplated for some time and has been A T C'd more than a year (number 212).

Revving at 2 200 for its rated horsepower, the new engine called the Lenape "Brave" weighs 192 lb., dry weight. Notable features in the design include double ignition impulse coupling on one magneto, solid steel cylinders with screwed on heads, full pressure oil feed, double springed Thompson siderome valves, renewable valve seats and a number of other features which will be more fully described in succeeding paragraphs.

The fundamental advantage of a properly designed radial engine is thorough cooling without elaborate cylinder baffles and this feature enables the Lenape five-cylinder engine to show remarkable performance in hard, long climbs, under full throttle conditions. All cylinders are equally cooled and therefore run at the same operating temperature. This cooling efficiency in the Lenape is in a large measure the result of designs both of the solid thin wall steel barrels and the cast aluminum, screwed on head. The cooling fins are so arranged that the air is guided to areas, which on some engines, cause much trouble from over-heating. For example, the rear spark plug bosses on the Lenape actually run at a temperature of 370 deg. F. The accessories on the rear of the engine are adequately cooled because of this efficient air flow. With this power plant blast, tubes are not needed to cool the magnetos.

The cylinder design follows the trend of large military engines with its screwed-on cylinder head construction. The barrels are accurately machined from specially heat-treated 4130-X steel supplied by the Bethlehem Steel Company. The approximate weight of each forging is 28 lb. The barrel and its fins are machined in one piece, which then weighs 5½ lb. A specially designed Gisholt automatic lathe completes this machining in one operation. An unusually hard interior wearing surface of 270 to 300 Brinell is maintained at all times, meaning long operating life. The barrel extends approximately 2 in. inside of the crankcase and thus the piston does not protrude beyond the end of the cylinder on the inside of the crankcase at the inner end. This feature makes ample provision for the side thrust from the power stroke and whip of the piston during the full length of the stroke.

Four heavy stepped studs fasten the enclosed oil-tight rocker boxes, housing the rocker arm mechanism, to the top of the cylinder. These studs have their lower portion ⅞ in. in diameter, threaded with coarse U. S. standard

(Turn to page 104)



Front view of Lenape "Brave"



Inspecting one of the nearly completed engines is E. H. White (left) general manager and J. L. Boland (right) chief engineer of Lenape Aircraft Motors. Boland has been a long time in aviation making his first flight in 1909 and during the last war was chief engineer of one of the Aeromarine Plant Divisions. White came to Lenape from the Glenn Martin Company where he worked on power plants for Navy boats. Prior to that he was with the Bureau of Air Commerce.

Shown in Flight is a Vultee Vanguard Pursuit

MEN, METHODS AND MACHINES...

In Vultee's recently expanded factory a straight line production system coordinated by experienced craftsmen establishes a new high in aircraft manufacturing efficiency. Here men, methods and machines combine to produce the famous Vultee V-12 Attack-Bombers, Valiant Basic and Advanced Trainers and Vanguard Pursuits in large quantities.

VULTEE AIRCRAFT, INC.

VULTEE FIELD, CALIFORNIA, U.S.A. CABLE ADDRESS "VULTEE"

"VULTEE VANGUARD 61" PURSUIT PLANE

Is Equipped with

"NORMA-HOFFMANN" PRECISION BEARINGS

Tests upon this newest development of Vultee Aircraft, Inc (Downey, Calif.) are basis of the belief that it is one of the fastest if not the fastest, military aircraft in the world. As such, maneuverability at high speeds necessitates not only extreme sensitiveness and quick response in the controls, but the utmost of dependability as well.

Significant, therefore, of the confidence of Vultee engineers is the fact that **NORMA-HOFFMANN PRECISION BEARINGS** are employed in the control mechanism of the "Vanguard 61"—as they are also at like points in the new Vultee 'Valiant BT-54 Trainer.

In the "Vanguard" and "Valiant," as well as in other Vultee models, **NORMA-HOFFMANN PRECISION BEARINGS** are used not only in the controls but also in the instrument equipment and elsewhere.

"Where the bearings must not fail"—on land, at sea, and in the air—practically every representative builder of aircraft, engines, instruments and aircraft equipment—including the U. S. Government—employs **NORMA-HOFFMANN PRECISION BEARINGS** as an added assurance of safety, friction-free operation, long service, and low maintenance cost.



There is a Norma-Hoffmann Precision Bearing for virtually every aircraft application — 108 distinct series and over 3000 catalogued sizes. Write for the Catalog. Let our engineers work with you.

NORMA-HOFFMANN BEARINGS CORPORATION, STAMFORD, CONN., U.S.A.

BUYER'S LOG BOOK

What's New in Accessories, Materials, Supplies and Equipment

Presenting performance, installation and service features intended to meet the most stringent requirements, the Adel 4-way hydraulic selector valve represents a marked advance in the design of valve equipment specifically suited to use with aircraft hydraulic systems. Manufactured by the Adel Precision Products Corp. of Burbank, Calif., the paramount aim in this design has been to obtain utmost simplicity, with compactness and light weight, together with a high rate of flow and unusually low pressure drop. Operating handle loads as low as 15 in-lb are obtained while operating under 1,000 lb. per sq. in. pressure. This means that valves may be operated with an applied force of less than 4 lb. on a 4-in. handle. Design pressure of 4250 lb. per sq. in. is used on all sizes with provision for 3,000 lb. per sq. in. operating pressure in special units. All operating parts are readily accessible and may be removed from valve bodies without breaking line connections. Weight of the Adel valve is only 12 oz. and dimensions are 3 x 2.25 x 1 in. Models are available for capacities in excess of 15 G.P.M. and fitted for either straight or pipe threads.—AVIATION, *May, 1940*

Adel 4 way hydraulic selector valve

Such demands as absolute reliability and ease of operation of all manner of aircraft controls have made the use of anti-friction bearings for all controls, retractable gears, flaps, gun mounts, bomb doors, bomb release mechanisms, etc., practically universal. SKF Industries, Inc., Philadelphia, Pa., have specialized on development of bearings to meet such requirements and now offer a complete line of ball and roller bearings specifically designed to meet aircraft control problems.—AVIATION, *May, 1940*

SKF control bearings.

As electrical systems on aircraft have grown more extensive the provision of compact and reliable switches has been required. Micro Switches, manufactured by the Micro Switch Corp. of Freeport, Ill., have been specially developed for aircraft needs and are now being used widely both in this country and abroad for signaling position of retractable landing gears, automatic control of landing gear operation, wing flaps, propeller pitch control, use on bomb releases, etc.—AVIATION, *May, 1940*



Micro Switch.

Keeping pace with the rapidly increasing demand for stainless steel, the Republic Steel Corporation, Massillon, Ohio, has recently greatly expanded its manufacturing facilities. Stainless steel is now available to the trade in a wide range of sheet and strip sizes and gages. Increasing application of stainless steel to aircraft design and manufacture is being experienced.—AVIATION, *May 1940*

Cutting stainless steel into strips.

Since many aircraft parts must be protected against corrosion, especially in seaplane service, the aviation industry will doubtless find considerable use for the new Albany Rust Preventative "PW" which is manufactured by the Albany Grease Co., New York, N. Y. This product is said to penetrate loose rust, dries quickly, is easily removed, is water repellent, heat resistant, will not soil and is non-abrasive.—AVIATION, *May 1940*

Applicable to many operations in machine shops or tool rooms, and on miscellaneous bench work, a pneumatically operated vise has demonstrated its ability to increase some types of production up to 50 per cent. Available in a range of five sizes, the tool is offered by the Larkin Air Vise Company of Portland, Conn.—AVIATION, *May, 1940*

To aid welding inspectors' and operators to check fillet welds accurately and rapidly, a low priced fillet weld gage has been developed by the General Electric Co., Schenectady, N. Y. The gage can be used on fillets of the following sizes: $\frac{5}{16}$ in., $\frac{3}{8}$ in., $\frac{1}{2}$ in., $\frac{5}{8}$ in., $\frac{7}{8}$ in., and 1 in.—AVIATION, *May, 1940*

Musselman Doenut Tire

To fill the need for some means of adjusting the sensitivity of Turn Indicators under actual operating conditions the A-1 Turn Indicator Sensitivity Control has been developed by Aircraft Instrument Service, Inc., Detroit, Mich. This instrument provides the pilot or operator with a means for correcting for any change in sensitivity of the Turn Indicator due to variation in suction from venturi or vacuum pumps and may also be used as a shut-off valve to protect the Turn Indicator during acrobatic flying. The device is already in service on a number of leading airlines. Total weight is 3½ ounces. The control can be installed in a few minutes and requires but 1⅛ in. of instrument panel space.—AVIATION, *May, 1940*

Introduction of two new types of lightweight air-operated riveting hammers for use in aircraft manufacture has been made by Ingersoll Rand Company, New York, N. Y. Each is available with pistol grip, offset, or push button handles. One type is a long stroke, slow-hitting machine for aluminum, dural, or soft iron rivets. The other is a short-stroke fast hitting riveter for general fabrication work.—AVIATION, *May, 1940*

Complete elimination of damage to tire valves caused by creeping of the tire on the wheel rim is achieved in the Doenut tires and wheels offered by Musselman Products Co., Cleveland, Ohio. The Musselman Doenut tire is equipped with a valve stem which projects out through the side of the tire near the edge of the rim but not contacting it. Three tire sizes are available, 10 x 2.75 in., 12 x 3.30 in., and 16 x 4.40 in.—AVIATION, *May, 1940*

Cleco 41 rivet squeezer

Better and faster riveting is made possible, especially in cramped quarters, by a pneumatic squeeze riveter introduced by The Cleveland Pneumatic Tool Co., Cleveland, Ohio. Known as the Cleco 41, the new tool is only 9¾ in. in overall length and weighs but 3½ lb. It will handle dural rivets up to and including ⅛ in.—AVIATION, *May, 1940*

In response to a wide demand for improved rapid action clamping tools for aircraft production work, two new clamping tools have been perfected by the Detroit Stamping Co., Detroit, Mich. Both clamps are of rapid action type and of rugged construction. The De-Sta-Co Toggle Clamp No. 220, "Aviation" model, delivers a pressure ratio of 33 to 1 to the clamping arm. De-Sta-Co Toggle Pliers No. 460 allows adjustment of the clamping head for a spacing of 0 in. to 11/16 in. Closing of the handles exerts a pressure ratio of 75 to 1.—AVIATION, *May, 1940*.



Ajax furnace

Application of a new principle to large nitrate baths for heat treatment of aluminum alloys results in automatic circulation of the bath by means of electromagnetic forces generated at the heating electrodes. Various heat-treat furnaces of the salt bath type and using the Ajax-Hultgren principle are now available to the aircraft industry from the Ajax Electric Company, Inc., of Philadelphia, Pa.—AVIATION, *May, 1940*

Certain features of arc welding are winning new converts for this method of fabricating aircraft steel tube structures. Special equipment manufactured by the Lincoln Electric Company, Cleveland, Ohio, is being widely used by Boeing Aircraft Company and other representative plants in the manufacture of some of our latest types of aircraft.—AVIATION, *May, 1940*

(*See page 113 for Window Shopping*)

De-Sta-Co Toggle Clamps.



Arc welding in construction of Boeing aircraft

THE AVIATION NEWS
REVIEW COMMENT, FORECAST
MAY 1940

BLAINE STUBBLEFIELD, Washington
C. F. McReynolds, Pacific Coast
Jay P. AuWerter, New York
E. R. Lucken, New York

FDR Orders CAA Back to "Commerce"

(See Story and "Spot Checking" on page 68)

Aviation helps to make war worse; and, whether you like it or not war helps to make aviation better. Everybody hopes, though, that war will be grounded for good some day and that airplanes will fly for peace only. Above you see a brand new war maneuver by air. German troops are flown to Denmark and Norway in Junkers-52 planes. The Germans say thousands of soldiers thus have passed high over British mines and guns on the water. Below is shown the jigs and tail structure of the Douglas 70-ton bombardment plane being built for the Army. The useful load will be about 28 tons; wing spread 210 feet; speed over 200 mph; range more than 6000 miles; 16-feet three-bladed propellers; engines four, tricycle landing gear. Sleeping quarters, radio compartment and navigators' space have been soundproofed for efficiency. This is the Army's effort to build a plane for a specific purpose—long-range bombing. This ship will not be said to the Allies, they have no such distances as we have to deal with. In addition, Douglas is building powerful, fast new twin-engined bombers expected to outspeed anything of their type.



NATIONAL AVIATION

CAA Reorganization Fight

President Roosevelt's proposal to Congress for reorganization of the Civil Aeronautics Authority fell like a bomb in the back yards of everybody, including high officials in the Authority. Cries of anguish went up. CAA officials protested to friends, but held formal statements for hearings. Within two hours Senator Pat McCarran, father of the law, wrote a blistering attack on the move, and introduced a resolution to reject the President's plan.

Briefly, the plan would change the name of CAA to "Civil Aeronautics Board" and put it under the Department of Commerce, where the old Bureau of Air Commerce was. It would abolish the Air Safety Board and incorporate its functions within the new CAB. The Administrator's office would be continued, but he would report to the Secretary of Commerce. The five-member CAB would perform its rule-making, adjudicative, and investigative functions independent of the Commerce Department.

Critics replied immediately that the Board would not actually be independent, since its bookkeeping and its funds would be under the control of the Secretary of Commerce, and they predicted that the whole setup would quickly go political, as it was under the old Bureau.

Whatever might have inspired the President to upset the present satisfactory situation and seek reorganization of CAA when it has played so large a part in the successful aviation year just ended, puzzled all articulate observers.

Whatever the cause, the mischief is a-foot. The government reorganization law says that proposals submitted by the President will become effective unless both houses of Congress reject them within a sixty-day legislative period.

The President also proposed that the Weather Bureau be transferred from the Department of Agriculture to Commerce.

Airports Pushed

The airport expansion program is now before the Senate in revised form in a new bill introduced by Senator McCarran which would simply authorize a national system of landing fields, but require additional Congressional action to finance the project.

This latest version follows NAA suggestions by providing that CAA apportion whatever funds are made available—$125,000,000 is mentioned—among the states according to a formula based on population, geographical area and percentage of civil airway mileage. Local administration would be carried out by special state agencies legally designated to foster airport development.



AVIATION'S PART OF ARMY DAY was celebrated in New York by floats illustrating the ins and out of the Air Corps. The floats were contributed by the various aeronautical companies and were paraded up Fifth Avenue between two packed rows of spectators.

Air Races, 1940

For a long time people have been reading about automobile races and saying "I wonder why they keep on doing that." Air racing after so few years, is drawing the same comment. But they may keep on doing it. Those who said the Cleveland race last summer would be the last, didn't really believe it. Chances are that the 1940 version of the races will be at Newark. All it needs is some run-way fixing, and a grandstand. Earl Ortman, the premier pylon duster, says a good 10-mile course can be laid over the Jersey salt grass, with only a few high tension wires in the way. The New York metropolis can furnish perhaps 100,000 ticks of the turnstile per day. Lots of people love air races, and surely some city will be willing to take their money for years to come.

Instructor Courses

CAA believes its methods of instructing student pilots has proved so safe and successful that the system should be extended to all civil flight training. The Authority has made arrangements to enable 600 commercial pilots to take "refresher instructor" courses so they can qualify for instructors' ratings. Pilots who want to be re-rated under the standardization program are also eligible. Courses provide from seven to ten hours of instruction.

YOU MAY HAVE SEEN the charming Lee Ya Ching and her Beechcraft at your airport as she has been flying throughout the country raising funds for the Chinese Relief movement. A skilled pilot, she will soon fly to South America to continue her work.

Spot Checking

Congress must reject FDR's reorganization order by June 11 (60 days) or it will go into effect. If Congress adjourns before that date, a new 60-day period will start with the 1941 session.

A search for political villains who might have influenced the President revealed several suspects, in and out of the Authority. Observers blame them for the sweeping changes that have been proposed. Hearings will start fireworks.

Taking advantage of real war the Army urged the Senate to reinstate the Alaska "cold weather" air base and 496 replacement airplanes, disallowed by the House in passing the 1941 Supply Bill.

Its aeronautics library was given by National Aeronautics Association to the Institute of Aeronautical Sciences which already had its own and the Burden library.

Allies placed orders at last for about 1,500 of the 5,000 American planes they proposed to buy for $1,000,000,000.

An air traffic survey of the U. S. domestic system is completed and a report is issued by CAA. It shows point-to-point flow of traffic in August, 1939.

Ames Aeronautical Laboratories is the name given to Moffett Field, Sunnyvale, California, by NACA, with FDR's approval. Dr Joseph S. Ames retired as chairman of NACA in October, 1939. The committee celebrated its twenty-fifth anniversary at a luncheon for present and former members, April 18.

The Bennett Plan for flying training under "scholarships" financed by the Government was proposed to Congress. Two coupons worth $50 each would be issued to applicants passing physical exams.

Western Electric 32A receiver has been adopted by Aeronautical Radio, Inc., acting in behalf of all air lines, to use CAA's ultra-high-frequency for airport traffic control and to serve as part of the plane equipment for instrument landing, which will be in experimental operation in a year or so.

$15,000 Shell Aviation Scholarships and awards competition will be participated in by student pilots from most of the 435 colleges in the CAA program.

Coming Events

- Apr. 28. Annual Air Manouvres. Atlanta, Ga.
- May 1-3. Spring Meeting, American Society of Mechanical Engineers, Worcester, Mass.
- May 11-12. Aero Club of Kentucky's Annual Aircraft Exhibit, Bowman Field, Louisville.
- May 18. Pacific Coast Inter Collegiate Air Meet, Gardena Valley Airport, California.
- May 27-28. National Aviation Forum, Washington, D. C.
- June 1-2. Air Carnival, Birmingham, Ala.
- June 9. Missouri State Model Airplane Contest, sponsored by Missouri State Jr. Chamber of Commerce, Municipal Airport, Columbia.
- June 9. Annual Air Classic, Port Columbus, Columbus, Ohio.
- June 9-14. SAE Summer Meeting, The Greenbrier, White Sulphur Springs, W. Va.
- June 9-23. Annual Southwestern Soaring Contest, Wichita Falls, Tex.
- June 17-21. American Society of Mechanical Engineers, Semi-annual meeting, Milwaukee, Wis.
- June 25-30. Michigan Air Tour.
- July 4-6. Air Show, Denver, Col.
- July 7. Third Annual Air Races and Air Show, Kalamazoo, Mich.
- July 7-8. National Air Congress and NAA Convention, Brown Palace Hotel, Denver, Col.
- July 21. Fifth Annual Air Show, Fort Wayne, Ind.
- August 18-19. Air Show sponsored by Sheldon NAA, Turner Field, Sheldon, Iowa.
- Sept. 5-6. American Society of Mechanical Engineers, Fall Meeting, Spokane, Wash.

Intercollegiate Conference

The Sixth National Intercollegiate Flying Conference was held at the Wardman Park Hotel, Washington, April 8 and 9. A banquet at the Shoreham Hotel climaxed two days of speeches and business. Representatives of the Army Air Corps, Navy Bureau of Aeronautics, Civil Aeronautics Authority, and other leaders took part. Grover Loening presented the Loening Trophy to the Purdue Flying Club for all-around excellence in aviation activity. Five hundred dollars was divided in first, second, and third prizes to Florence Kernick of Canaan, Conn., Arthur L. Newman of New York, and George McMillan of Clemson, S. C. in the Robert H. Hinckley Essay Contest on "The Cultural Value of Flying."

Advanced CPT Plan

Next year's plans for CAA advanced flight instruction were announced by Grove Webster at the New York Safety Council Meeting on April 17. An additional 50 hours of flying will be given to 1,000 students who complete an advanced ground course of 140 hours and who have added 15 hours of flying time to the first 35 hours given by CAA. Ground instruction will be carried on next winter, and flying will not start until June 15, 1941.

The number of non-college students for primary training will be increased to 1500 next year, and about 8,500 college students will be trained. CAA hopes to increase the number of training centers to 750.

Southwest Conference

Southwest Aviation Conference began three days of highly successful meetings on April 25. Aviation leaders from all parts of the country journeyed to Tulsa, Okla., for the third annual affair. The program, under the direction of Moss Patterson, president of the conference, was based on recommendations made by some 3,000 persons interested in aviation.

W. G. Skelly, president of the Skelly Oil Co., was chairman of the speaker's committee and convinced a notable list of aviation people to come to Tulsa. Over 40 speakers were on the program during the three days of meetings.

EXECUTIVE COMMITTEE, Southwest Aviation Conference. Front row, l. to r., W. H. Green, Mrs. Wm. B. Perry, Mrs. W. M. Wyatt, Mrs. Dorothy McBirney, Gerald Wrathy. Standing, l. to r., Wade Whiteside, Russell Cantwell, H. C. Duncan, H. M. Cosgrove, Mather Eakes, Ted Law, Stanley J. Ehlinger, H. L. Smith, Fred Q. Casler.

THE WASHINGTON WINDSOCK

by BLAINE STUBBLEFIELD

$1200 Worth of Conversation

700 Years of flying by one person is the equivalent of the airline's year of safe operation, says W. A. Patterson of United Air Lines. When we pointed this out to our general secretary, who is twenty and has brown curls, she said "That's fine, but I don't want to fly 700 years; I just want to go for a trip in an airplane." Jane doesn't go because she can't afford to. There's another problem for you and the boys, Mr. Patterson.

Increased cost of military airplanes seems to have been legislated into effect to some extent by Congress itself. General H. H. Arnold, Chief of the Air Corps, testified at 1941 appropriation hearings that costs have increased (instead of going down with greater production) because of greater performance demands, guarantee of delivery dates, fear of labor trouble, splitting of awards, etc. He said too, that for years the airplane industry has been earning about four per cent profit. Then along comes the Vinson-Trammell Act, putting on a 12% profit limit. The implication was that this increased the price of planes.

Wall Street never heard of such strenuous back-stage doings as the Administration's pull-and-haul with the Allies over release of latest model airplanes for export at high prices. England bawled like a stuck pig about financing our plants, and balked when Morganthau told the purchasing mission to pay for development of new designs for the U. S.—or else. The mission then went straight to the President. That gentleman doesn't talk, but everybody knows he will help England and France all Congress will stand for. Isolationists say if the situation was reversed the Allies would soak us. Anglophiles say we're Shylocking again, we'd better help now—or fight the Allies' war later.

A delicate situation confronts CAA, which is urged by the Private Flyers Association to relax a rule against flying by pregnant women. Gynecologists, obstetricians and general medical opinion, sought by the CAA medical examiner, solidly uphold the rule. They say that prospective mothers are subject to syncope (fainting), nausea, vertigo, and even hemorrhage. The association, however, produced some medical opinion favoring its case. It is admitted that the rule is harsh on the women, because required months on the ground loses them their flying status.

Now private flying will try its hand at a demonstration of safe flying. The CAA-college schools have already made an auspicious beginning. But demonstrated safety will attract more people, and more people will buy more airplanes, but they will make trouble. Automobiles kill folks by the thousands, partly because it's an important industry, and the pressure on government to let nit-wits drive is irresistible. That same kind of pressure may some day come on private aviation.

A high-priced hall roast was put on for American Export and Pan American in their tiff over the Atlantic run—and the public took the check. The hearing record covered 3,018 pages. An airplane manufacturer asked for a copy and the stenographic company that took it down quoted him 30 cents a page or $1,200, with one third off for the job lot. Some lawyers in charge of this remarkable gab fest privately admitted it was unnecessary, but both sides wanted to talk, a sacred right in a democracy. Insiders knew the question was a matter of national policy and would be so decided.

1940 Forum

Washington (AVIATION BUREAU)—Thomas H Beck, the livest live-wire in aviation, announces that the object of the National Aeronautic Forum and Conference (Washington, May 27–28–29–30), is to sell the people of the Americas on flying and air defense. And he means *both* Americas. The Latin countries are being told about it by shortwave and air mail

There will be exhibits of all branches of aviation, under a Government Committee headed by Robert Hinckley, who was appointed by the President Most exhibits will be at Bolling Field and Anacostia, served by frequent bus, and some light aircraft will be down on the Mall by the Lincoln Memorial Several airlines and manufacturers have agreed to exhibit

Forum meetings will be in the Department of Commerce auditorium, across the street from the Willard Hotel, new headquarters of NAA

NAA Meets in July

Plans have been completed to hold the national convention of the NAA at Denver, July 7–10 James Webb of Sperry Gyroscope is head of a committee working up the agenda, and William F Redding, NAA treasurer, of the Denver Chamber of Commerce, is general manager of arrangements

Aviation Conference Held

The 1940 Western Aviation Planning Conference was held at Fresno, Calif, on March 30 Speakers included the Governor of California, Culbert L Olson, Robert H Hinckley, chairman of the CAA, Brigadier-General F D Lackland, commander first wing GHQ, Commander H M Mullinix, U S Naval Air Station, San Diego, John Hunter, Airport Section, CAA, William Slee, American Road Builders Association, Major A B McMullen, Chief, Airport Section, CAA, Elwood Cole, State Coordinator, CAA, Dudley M Steele, president, United Airports of California, T G McMahon, executive secretary, Douglas Aircraft Company, Frank Fuller, Fuller Paint Co president, and well-known sportsman pilot

Dress Rehearsal

It's quite a complicated job to get a legal bag of tricks ready and go to court with your lessons prepared Even the lawyers can't always stack up their stuff in the right order So the Civil Aeronautics Authority has announced it will hold "pre-hearings" in all airline economic cases coming before it It's a kind of dress rehearsal The Authority is following a pre-trial procedure adopted by the Supreme Court. It must be all right.

Calling Names

Harold Brahman Pinehurst N C pilot, finds that blowing low ship stream over peach orchards prevents frost formation.

Dr E H Johann Schuette co-founder of Germany's Schuette-Lanz co works, died in Dresden April 1 He was colleague of Count Zeppelin

Lieut. James Warren Phelps Jr Berwyn, Pa died April 3 when his ship crashed into Lake Erie near Cleveland during routine war practice

Ruth Haviland whom Admiral Byrd taught to fly in 1928 is United's new woman's promotion director

Lee Swigart TWA's traffic manager at Kansas City is advanced to district manager at New York City

T T Hildebrandt, Washington becomes U S Air Compressor's governmental representative

Dick Stoddard wireless operator on Howard Hughes' globe shrinking 1938 flight is vice president of the Los Angeles Hollywood chapter Veteran Wireless Operators Association

Yale D Hills becomes assistant general manager of Timken Roller Bearing's service-sales division at Canton Ohio.

Hugh C Robbins resigns as secretary treasurer and director, and A E Kungas as auditor upon sale of Continental Aeronautic Corp. of Burbank and Glendale to Lockheed Aircraft.

Floyd E Evans, Lansing, Michigan's aviation director has released Wings Over Michigan 16 mm colored movie

David C Jones, V P and Gen. Mgr The Funkenkeimer Company Cincinnati died March 11 following a brief illness.

John W Kenny has resigned as vice president of Spencer Larsen Aircraft Corp.

The CAA was officially "absolved" of any bias in approving LaGuardia Field as New York base instead of Newark March 19 by a Senate commerce subcommittee which denied a resolution to investigate.

William Stanley Rust CAA inspector died March 13 in an airplane accident near Hicksville, New York

Bakelite Corp held last of three technical meetings March 12 at The Franklin Institute, Philadelphia

Carl A Swanstrom, president, Elastic Stop Nut Corp., died March 12 after an extended illness

Gill Robb Wilson NAA president is named to national board of judges of $15 000 Shell Oil Company's Aviation Awards Competition The fund provides intercollegiate aviation scholarships for student pilots It is administered by Institute of the Aeronautical Sciences

Jackie Cochran claims another speed record on a 2,000 kilometer course at 224 m p h. elapsed time was 1 hours, 44 minutes 47 seconds.

Edith Olmsie Dance made a 5-minute flight with the late Wilbur Wright in April 4 she made her second flight at LaGuardia Field as a guest of American Airlines.

Eastern Airlines flew 4,000 pounds of office equipment Boeing Air Transport did it 13 years ago

Northwest Airlines new publicity agent, Joseph A Ferris released his first yarn—on himself

TWA appoints I S Randall eastern region manager as assistant to board chairman T B Wilson with headquarters in New York.

EAL appoints Frank J Macklin to newly created post of Sales Manager. Walter Sternberg northwestern d t m at Chicago Daniel L. Sinkler as d.t.m at New York James P Ferrell as traffic agent at Newark and Gregory Flynn, formerly Gotham d t.m. as director of conventions and sporting events sales Robert J Smith, V P at Dallas and Hal C. Thurman Oklahoma City attorney are new Braniff directors

DEFENSE

'41 Money for Defense

After unusually prolonged hearings due largely to changes in aircraft release policy, the House finally received and passed the War Department military appropriation bill carrying funds for one year's expenses beginning next July 1

Outside of operating costs, the major part of the money will buy antiaircraft, artillery and ordnance material, with only $0,143,855 earmarked for new airplanes The Army had asked for 496 planes to replace anticipated losses during 1942 But without following the priority suggested by the Department, the House approved 14 amphibians 6 transports, and 37 advanced training planes, explaining that "if we are to forego for the present 2200 planes (under the new release policy), the Committee felt that procurement of practically all of the 486 might be deferred also just as well"

Money has previously been provided to procure aircraft up to the 5,500 authorized strength, all but 186 already under contract The Air Corps now expects to have on hand by July 1, 1941, a total of 5091 operating aircraft, exclusive of 409 National Guard planes Deliveries will begin to swing into high speed during the summer, with 772 planes coming through in 1940 and 2555 in 1941, according to present official estimates.

The appropriation bill also includes funds for continued expansion of military air bases but omitted a $12,731,060 low temperature experimental air base project at Anchorage Alaska Continuing economy pretenses—which the Senate is consistently knocking down—the House also cut heavily into the educational orders program

Meanwhile, the House Naval Affairs Committee concluded plans for reorganizing the Navy Department, abolishing the currently vacant post of Assistant Secretary for Aeronautics, consolidating ship construction bureaus, and effecting other rather minor changes Republican members, however, threaten a far wider readjustment if they come into power next year.

The turn of events abroad was immediately reflected in attitude as to appropriations for the Navy. The Senate Appropriations Committee, reporting the House-approved bill just after the Scandinavian invasion, increased contract authority for aircraft procurement from $10,000,000 to $25,000,000 The extra $15,000,000 was ear-marked one-third for replacement planes and two-thirds for planes to complement the new aircraft carrier, Hornet Also, $2,000,000 set down by the House for experimentation was diverted to buy Hornet planes

The Senate Committee, however, reduced the direct appropriation for airplanes, parts and accessories $5,000 000 below the House figure to $41,083,400

But even before Congress had time finally to enact this appropriation bill, members were already discussing the probability that additional sums would be necessary to speed up Naval expansion in view of the new crisis overseas

The Skyrocket

It may be sort of funny looking but Grumman's new Navy fighter is supposed to be the hottest thing on wings. The single-place two-engine Skyrocket is claimed to pack more hp per pound than anything yet built and to be faster even than Lockheed's P-38. Observers say that in test dogfights it flew rings around everything it came up against, and practically hung on its props in the climbs

Grumman also claims its new baby can throw a greater volume of heavy gunfire than any comparable ship; rate of fire of its nose cannon is not restricted by having to fire through the propellor An unusually large gas capacity gives it a range that permits bomber escort duty, the ship has racks near the wing tips for light bombs

Intended to operate from aircraft carriers, the Skyrocket has square-tipped wings with a bow designed to prevent wing-tip stall at low landing speeds Power, in unspecified amounts, is furnished by air-cooled radial, Grumman thinks these are less vulnerable to gunfire than liquid cooled jobs

The NEW GRUMMAN SKY ROCKET which has reports of being the fastest pursuit ship in the world. Also it appears to have been released for foreign purchasers. (See story).

Wide World

FLYING BLIND from Mitchell to Langley Field where he made an instrument landing, and then back to Mitchell Field where he made a second blind landing with a Flying Fortress Major Carl McDaniel brought new honors to the Air Corps on April 6 Here the crew is being greeted at Langley. L to r Col Jacob Wuest Major General Delos Emmons, Major Harold George, Navigator Lieut W P Ragsdale, Co-pilot Capt W A Methany, and Major McDaniel.

Midget Special

The Curtiss-Wright P-40D you're reading about is a new name for the P-46 This is the ship the existence of which was presented as justification for export release of the P-40, back in the days when secrets were secrets Now the P-40D has been released, but you still have to buy one to find out what it's like

Reportedly it's much like the P-40 except that the engine has been jazzed up (with a new supercharger?) and the fuselage has been narrowed down a bit and the whole ship gone over so that any extra bumps have been cleaned off

New Air Corps Trainer

Latest in a long line of rugged North American trainers, the basic trainer, Model BT-14, is now under delivery to the Army Air Corps at Randolph Field The BT-14 is a two-place tandem low wing monoplane with enclosed cockpits It has stressed skin wing built in three sections, with integral fuel tanks Fuselage is of steel tube structure to the rear cockpit, metal covered, and of metal monocoque structure aft of the rear cockpit. Landing gear is of fixed type Power is supplied by a Pratt & Whitney engine carrying a two-bladed Hamilton Standard propeller

First Trip, Hood Down

The first all-instrument cross country flight, all under the hood, was made by Maj Carl B McDaniel, Air Corps officer on a 300 mile course from Mitchell Field New York to Langley Field, Va on Army Day, April 6 Major McDaniel is a specialist in instrument and dead reckoning air navigation and has built up a distinguished record as a flyer

His flight was made in a Boeing B-17 four-engined 'flying fortress' bomber, powered with 2 Wright 1,000-hp Cyclones With him were two other officers and four enlisted men who were not under the hood, but they gave him no assistance whatever The usual radio aid procedure was followed, using the directional beam, approach markers, and the glide and direction beams from portable blind landing equipment

AVIATION ABROAD

British Overseas Gets Start

British Overseas Airways Corp officially took over all activities of both Imperial Airways and British Airways on April 1. On the Board of Governors, as announced by the Secretary of State for Air, are Mr. Clive Pearson, Chairman, Mr. Irvine Geddes, Deputy Chairman, Mr. Harold Brown, Mr. Gerard d'Erlanger; and Mr. W. L. Runciman, chief executive member and Director-General.

The new organization has eight departments, administration, finance, public relations, traffic, operations, service engineering, accounts, and technical development. In this country the Manager is Paul E. Newsheo, with offices at 620 Fifth Ave., N. Y. C.

Trans-Atlantic mail service from England to La Guardia Field, via Newfoundland and Canada, is expected to start about the end of May. The flying boats Cabot and Caribou, which were in this service last summer, will again be used.

The Airways Corporation is at present functioning on a special war time basis but it is to be hoped that passenger service across the Atlantic will be commenced some time this year, using 36-ton flying boats.

Under an arrangement with the British Government, the Airways Corporation at present operates National Air Communications for the Air Ministry. In addition, it provides two services weekly from the United Kingdom to Australia, four services weekly to India, once weekly to South Africa, twice weekly to Central Africa, once weekly to Hong Kong, once weekly to West Africa.

On some of the services American Lockheeds are used and quite recently extensive purchases have been made in the U. S. A. of Wright Cyclone engines which are to be fitted in some of the 40-seater airliners on various routes.

International

THREE ARMSTRONG WHITWORTH WHITLEY heavy bombers, which Britain has been using continuously in recent weeks. Powered with two liquid-cooled 980 HP. Rolls-Royce engines these ships will do 245 m.p.h. Close-up of tail turret is shown below. Tail guns have proven to be extremely effective.

British Press Combine

TAIL GUNNER in an A. W. Whitley. To operate four guns, apparently of .30 caliber, gunner grips two handles. As he twists right or left, entire turret and gunner move from side to side. Turning handles up and down quickly changes altitude of guns. Power is hydraulic. Belt cartridges show on left. Used shells slide down chute.

Acme

SHIP IN THE AIR is a scale model with a 50 foot wingspan which type English plan to build in the future as giant flying boat for Atlantic passenger service.

Scandinavian Air Traffic

Before the recent outburst the only possible way to go from Scandinavia abroad by a regular means of communication has, for nearly two months, been to go by air. The boat connections to Denmark, Germany, Finland and Baltikum have been suspended, as well as the steamers going from Bergen to Newcastle.

Traffic on the air lines has been very considerable. From Stockholm to the isle of Gotland ABA has been flying up to 4 trips every day. Generally flying on this route is done only in the summer for bathing guests. Traffic on the newly re-opened air service to Helsingfors is very heavy. Up to four services every day are flown from Stockholm to Helsingfors in addition to two services to Abo. More than 200 passengers are generally transported every day between Sweden and Finland.

On April 1st Swedish ABA-Douglas DC 3 planes will again come to England. They will start in the morning from the Stockholm-Bromme airport and fly in one day to Shoreham. They are painted orange. Up to now the Swedish planes have stopped at Amsterdam.

On April 1st one of the two regular lines Stockholm-Abo-Helsingfors, flown by ABA and Finnish Aero, will also be extended to Tallinn in Estonia.



A NEW FOURTEEN-CYLINDER, TWIN ROW RADIAL ENGINE that produces 1,000 hp has been announced by Industrie Aeronautica Romena, of Brasov, Roumania. The engine is being used on the IAR-39 and IAR-80 airplanes, and is said to be in quantity production.

AVIATION PEOPLE

ROBERT E DOHERTY, president of The Carnegie Institute of Technology, has been appointed a member of the National Advisory Committee for Aeronautics by President Roosevelt, to fill the vacancy left by the resignation of Brig. Gen. Walter G. Kilner, who was named a director of P.A.A.

A FORMER ARMY FLIER is Director of the newly organized Military Contracts Division of Republic Aviation Corporation. He is C. Hart Millar, with Republic since 1935 as Engineering Assistant to the President. Assistant Director of the new division is Mundy I. Peale, formerly with Sikorsky Aircraft.

ROBERT J. SMITH has been appointed a Vice-President of Braniff Airways, to succeed O. M. Mosier, now Vice-President of American Airlines. Smith who was general traffic manager of American Airways from 1929 to 1932, will coordinate Braniff's flight, operations and maintenance departments.

VETERAN TEST PILOT Paul E. Havgard has joined Glenn L. Martin Company as chief research engineer, under W. K. Ebel. An engineer, Havgard designed the Dole Derby winner; tested ships for Keystone, Curtiss, Grumman and Loening; latterly was research engineer for Curtiss Wright in Buffalo.

THREE MEN WHO CAME TO DINNER: Ten years ago Elmer A. Sperry, Jr., of Sperry Products Co. and Sir Hubert Wilkins, arctic explorer, were passengers aboard the first passenger plane dispatched from the old North Beach Airport. The plane, a Ford tri-motor Eastern Air Transport ship, was piloted by Captain Brian H. Parker. When Eastern Air Lines inaugurated its La Guardia Field service on April 1, they commemorated the event by dining at the airport with Captain E. V. Rickenbacker, Eastern's president just before takeoff of the Mexico Flyer "Silversleeper." The "Silversleeper" leaves each evening at 7:15, arrives at Brownsville, Tex., at 9 a.m., transfers its passengers to a Pan American plane which brings them to Mexico City in time for lunch. A snack bar is available throughout the trip, with full meals served at meal times. L. to r., Captain Parker, Mr. Sperry, Sir Hubert, Captain Rickenbacker.

A UNIQUE SERVICE, that of analyzing and testing material used in airport construction, has been inaugurated by Haller Engineering Associates. Director of the Airport Consulting Division is Emil K. Harvey, long an airport consultant, and who for seven years taught airport design at the Guggenheim School

AVIATION MANUFACTURING

Real War Brings Orders

Washington (AVIATION BUREAU) Outbreak of active fighting in the Scandinavian theatre has thrown the dawdling export situation wide open. The allied purchasing commission, not having any use for airplanes at the moment and knowing that the longer it waited the better ships it would be able to buy, had not been pushing very hard on the necessary detailed negotiations with the War Department that followed announcement of the new liberal policy on release of high-test ships Then, a day or two before Germans marched into Denmark, when it was becoming clear that something would break, the heat was really turned on, the negotiators got down to business, and the planes were released It was then possible to talk turkey to the manufacturers on actual orders.

The "new" policy was not so much new as newly made public Weeks before manufacturers had had the tip-off that they could safely negotiate sales of the still un-released models And administration sources made it their business to prepare public sentiment by talking up the strength of the Germans and the needs of the Allies One highly authoritative source let slip, "off the record," that Germany would soon be building 6,000 planes a month, while Britain could only make 1,200 and France 400 (An equally good authority, incidentally, thinks the Nazis will be doing mighty well if they turn out 2,000 a month)

Further proof of the legislators' approval of this policy came in the virtual elimination of aircraft purchases from the Navy supply bill and in the defeat, 10-7, by the Senate Naval Affairs Committee of Senator Lodge's amendment requiring the Navy to spend all its airplane money within the coming fiscal year.

Prospects that the Allies will get fairly quick deliveries on their new orders are good Production lines now rolling out planes for the U S can be switched over to export orders The backlog of unfilled military export orders amounts to about 3,350 units, which won't take long to run off at present production rates Of the 1,400 or so ships now being produced each month, about 300 are flivvers, another 100 larger civil types, perhaps 200 are for our own armed forces (this will decrease in future), and the remaining 800 are for military export Production is rising fast and is scheduled to reach about 2,500 a month by year end

Don't Let Mars Fool You

Hazards of the aircraft industry, from the investor's point of view, have not been removed by recent increases in aircraft backlogs, according to a report sent stockholders of Douglas Aircraft Company by Donald W Douglas, president. Pointing out that rigid profit limitations are fixed by law on all planes sold to the United States Government, that increases in production costs have been brought about by recent rapid expansion, and that possible losses may occur through cancellation of foreign contracts, Douglas emphasized the effort of the Douglas Company to improve its future position through devoting engineering research to development of the commercial market. Douglas currently has a backlog of approximately $97,000,000, of which about $20,000,000 represents commercial business

Hans Groenhoff

LUSCOMBE "SILVAIRE", newest of Luscombe's metal ships, has several improvements over earlier models This is the deluxe job with much fancy fittings and a 75 h p Continental

SPERRY GYROSCOPE COMPANY'S NEW LOCKHEED—first twin-engine ship built exclusively for flight research purposes. Sperry engineers wrote specifications for many parts of the airplane. It will be used for instrument tests and developments, study of special navigational aids and vibration research

Nix on Freight Rates

Still worrying the engine people is the petition independently presented to the Interstate Commerce Commission by the New York, New Haven & Hartford Ry Specifically aimed at Pratt & Whitney, this requests either a 70 per cent rate increase or reduction of liability between Hartford and Weehawken, N J embarkation point for shipments to Europe The application is momentarily quiescent, and the shippers hope that in view of the action of the other lines, N Y, N H & H will quietly let it drop—but are keeping their powder dry for an ICC fight

Lockheed Business

While talk of huge military orders continues to dominate aviation gossip, the Lockheed Aircraft Corporation has announced receipt of approximately $615,000 in new commercial business during March Included in this business were three new Lockheed 18s for Continental Airlines, two 18s for Air Afrique, one model 18 to a private customer and one model 12 to the U S Navy To accommodate increasing business the Lockheed Corp is rushing completion on two new assembly buildings at the Burbank plant, one costing $55,000 and the other $40,000.

Recent Awards

Navy Department

United Aircraft Corp, East Hartford Conn $52,110 for blades and hubs for airplanes

Wright Aeronautical Corp Paterson, N J $25,412 for aircraft engines.

United Aircraft Corp, East Hartford Conn $246,580 for aircraft engines

Worthington Pump & Machinery Corp, Washington, D C. $24,785 for air compressors

United Aircraft Corp, East Hartford Conn., $685,881 for aircraft engines

War Department

The E A Kinsey Co, Cincinnati Ohio, $5,670 for universal horizontal shapers.

Bausch & Lomb Optical Co, Rochester N Y $11[illegible] for aerial navigation instruments

Westinghouse Electric & Manufacturing Co, Dayton Ohio $[illegible] for power and control equipment

Bendix Aviation Corp Bendix, N J, $32,028 for starter assemblies, switches and solenoids

United Aircraft Corp, Hamilton Standard Propellers Div East Hartford Conn $[illegible] for propeller and control assemblies

General Electric Co Schenectady N Y, $[illegible] for maintenance parts for superchargers

Curtiss-Wright Corp Clifton, N J $[illegible] for propeller and blade assemblies and controls.

Wright Aeronautical Corp, Paterson N J, $[illegible] for maintenance parts for Wright Aeronautical engines.

Ingersoll-Rand Co Cincinnati Ohio, $[illegible] for air compressors

Taller & Cooper, Jersey City N J, $[illegible] for six component balance for wind tunnel

Douglas Aircraft Co Inc Santa Monica Calif $[illegible] for aircraft equipment.

E. J. Parker Joins Howard Aircraft

Directors of Howard Aircraft Corporation of Chicago announced the election of E J Parker as president and treasurer of the corporation, to fill the vacancies left by Ben O Howard and Damon Howard both of whom recently resigned Mr Parker was formerly an executive with one of the Fisher Body units in Detroit

AUTOMOBILE INJURIES resulted in the death on April 9th of our contemporary, Robert J. Pritchard, for 14 years editor of Western Flying Originally a newspaper man, Bob Pritchard switched to aviation in 1926, when he and V. L. Ehrenclou founded the Occidental Publishing Co Except for a brief period in 1939, he had been editor of the magazine and editorial director of the five trade magazines published by his company

Switlik's New Factory

A formal inspection of the new Switlik Parachute & Equipment Company Building was held in Trenton, N. J on Friday, April 12 The new building which was purchased by the company, makes available for immediate use over 50,000 square feet of floor space, with present production facilities for over 200 parachutes a week. It is now one of the largest parachute factories in the world, where 75% of both the United States Army and Navy parachutes are made, in addition to supplying a number of foreign governments

Belt-line production—Piper's cub factory brought "Fordism" a step farther into commercial aircraft production when it introduced a monorail assembly system patterned after the auto factories, speeding up production 15 per cent in the process. After final welding the bare fuselage is hung on the monorail and moves over 3,000 ft of trackage equipped with switches, sidings and crossovers

Sub-contracts—Keeping busy on a $400,000 backlog of sub contracts while it carries on flying windmill development for the Army, Kellett Autogiro has leased 16,000 sq ft of a four-story building near its Philadelphia Airport plant, provision is included for getting more space as needed

INTERESTED SPECTATORS at the testing of Culver Aircraft Corporation's plastic bonded ship,—the Dart Model E Bottom row Kenneth Aldrich, CAA Inspector, George Stephens, CAA Engineer, M P. Crewe, Chief Midwest Branch, K. K. Culver, Jr., President. Top row C. M. Jamieson, Assistant Engineer; M. Jakasky, CAA Engineer; Al W Mooney Chief Engineer, H. G Fitzgerald, Secretary, K K. Culver, Sr, Treasurer.

Flying Wings Report

From the Guggenheim School of Aeronautics at New York University, as the result of testing a model submitted by the Burnelli Aircraft Company, come some very interesting results on the lift characteristics of fuselage sections built in the shape of airfoils. A nine foot model was tested, with wing panels on each side of the airfoil fuselage, at a critical Reynolds number of 580,000 and a speed of 59.4 m.p.h. to obtain the results (part of which are shown on the accompanying graph). This model was to 1/24 scale while on the full scale ship the lifting section of the fuselage would be 24 ft. long with a chord of 30 ft. The fuselage was a basic profile of the NACA 0012 type modified to a maximum thickness ratio at 32% of the fuselage chord.

One of the outstanding results was the percentage of lift carried by the fuselage as compared to that carried by the wing. At low angles of attack practically all of the lift was taken by the fuselage (see graph). At 9 degrees angle of attack the curves crossed and at higher angles of attack two thirds of the lift is carried by the wing. Also of interest was that tests with varying the angle between the outer wing panels and the fuselage showed that the most efficient combination was that at which the two were at zero angle to each other.

Tunnel Tests Augmented

Following the practice he initiated in early tests with the Northrop "flying wing" which served as a flying test model of the famous Northrop Alpha, Beta, Gamma, Delta series, John K. Northrop is now planning man-carrying scale models of larger planes in order that free flight testing may be conducted before starting production on full-sized planes. Northrop now has under development a "family" of planes reported to incorporate a radical new basic design. No hint as to the nature of this design has been given, other than that it will apply to a series of planes ranging from small single engine fighters to large multi-engine craft. Now in first stages of production in the Northrop factory are 24 conventional type monoplanes recently ordered by Norway. Meanwhile workmen are rushing to completion the first of Northrop's flying models, to be test flown within 60 days according to announcement. This is said to be one third size and is a scale model of a twin-engined military plane.



THE LIFTING FUSELAGE of the Burnelli Aircraft Co. showed remarkable characteristics in the wind tunnel results.



HERE'S ONE hot off the old flivver. The Rudy Arnold "trap door" on the exhaust line is part of a new exhaust silencer that is attached along the bottom of the plane. Besides operating automatically in case of back fire, it can be controlled by the pilot to be used as a "cut-out"—how's that for the racy set.

Research Conference Off

The National Advisory Committee for Aeronautics is too busy researching to talk about it, especially with the new labs at Langley and Moffett fields. Hence, the annual aircraft engineering research conference has been postponed a year to May, 1941.

Altitude Fuel System

At certain conditions at high altitudes, high test gasoline vaporizes and replaces liquid fuel in feed lines to the engines. It's not hard to see that these "vapor locks", as they are called, play havoc with efficient operation of the engine. For this reason Military planes had trouble in consistantly operating with the same degree of efficiency above 20,000 feet.

The Pump Engineering Service Corporation in Cleveland, in cooperation with the Army has developed a new fuel system that is aimed at eliminating these "vapor locks". The new system changes the placement of the fuel pump to a point remote from the engine and at a level more equal to that of the gas tank. The Result—although not officially released, military ships have been able to fly well above 20,000 feet with much improved operation.

Standardizing In West

Dedicated to the establishment of standards of shape, size, weight, color, and composition of aircraft parts, accessories, and materials, the Western Aircraft Standards Committee has been organized to represent the standards engineers of all Pacific Coast aircraft plants. Edward J. Kasmicka, Lockheed standards engineer, is chairman of the committee. Hundred-degree countersunk head rivets are one of the standardizations effected by the committee to date. Heretofore plane companies have been using rivets varying from 80 to 120 deg. The committee also has standardized de-icer manifolds into four types and the engineers are now concentrating on such items as ventilating ducts, universal joints, screws, steel tubing sections, etc. An effort is also being made to arrange an identification code for colors on cable wrappings, and to get stainless steel for aircraft use in sheets of standard shape, size, and composition. Kasmicka will shortly make a trip to the East coast for a conference with standards engineers there.

Automatic Warning Lights

An "electric eye" has been devised to control the familiar red warning lights at the New York Municipal Airport. When darkness or fog or haze thick enough to make flying dangerous is present the photoelectric cell automatically lights four red lights on a tower two miles from the field. In the morning or when the gloom passes, it will automatically turn the lights off.

A recording voltmeter will be connected in the relay circuit to record the on and off time of the lights. The relay makes use of one phototube and three standard metal vacuum radio-type tubes. Relays of this type have had their test run in street and highway lighting proving their reliability. The General Electric Company's lighting engineers were the ones who developed the idea which looks like a good one for relieving some of the responsibility of the already too busy man in the control tower.

TRANSPORT AVIATION

Airline Discount Battle

Washington (AVIATION BUREAU)—It will be a long time before you hear the last of the airline fare discount question on which the Civil Aeronautics Authority held hearings for several weeks. The two main points under discussion are the discount card, which is issued to business firms and to individuals who will place a deposit of about $400 with the airline that writes the card, and the 15 per cent discount allowed to federal employees.

The Authority has to decide whether these cuts are discriminatory against the ordinary air traveler. History in brief: In 1935, when there was no passenger rate control, American Airlines issued discount cards in large numbers as a smart competitive move. Other lines were forced to follow suit, because the cards actually constituted a rate cut to the main body of air travelers. United Air Lines for a while tried the credit contract plan but later decided to abandon it.

The result is not entirely satisfactory to anybody but American. Many customers think they have to deal with the line that issued the card, and a few of them think they can use the card only on the line that issued it. So AA has the advantage. The system makes a lot of confused bookkeeping for *all* the lines. It makes trouble, too, for companies holding them, such as employees taking unauthorized rides.

The Authority can do one of several things. It might allow the airlines voluntarily to discontinue issuing cards, and let them be issued for all by the Air Transport Association, with modifications which would remedy minor troubles. It might possibly order the discount cards stopped entirely, on the ground it is discriminatory against the citizen who cannot afford to make the deposit. But the chances are it will recognize the discount for volume business as legitimate, following precedent in many other lines of selling.

Discount to the Government is a different problem. It isn't getting much business for the airlines. Federal travelers are afraid to take the air, because if they don't prove that per diem and salaried time were saved as a result of the air trip the Comptroller General disallows the extra airline cost, and it's not recoverable. When the new civil air law opened the way for government travel, the lines excitedly prepared for a sell-out, but President Roosevelt immediately ordered federal agency heads to scrutinize every trip, with the result that the smoking-cars, and not the skies, are darkened by bureaucrats.

If CAA regards G-travelers as individuals, then the discount to them is discrimination. But if they are regarded as employees of an organization, then they are entitled to it as a concession to volume.

PROMOTION comes to Edward Sullivan heretofore chief of stations for Pennsylvania-Central Airlines, who has been appointed the line's General Traffic Manager by Vice-President J. J. O'Donovan. With the company since 1935, he has been District Traffic Manager in Washington, Cleveland, and Pittsburgh.

WORLD'S FAIR visitors will soon come flocking in to the seaplane terminal at La Guardia Field where Pan American Clippers sail in and out. By the end of May it is expected that British mail planes will also be using these facilities.

MOVING UP from Eastern Manager for TWA to assistant to the chairman of the Board, J. S. (Stick) Randall will now enlarge his activities to cover the entire country. His office will continue to be NYC.

Safety Council Meeting

Ways in which private flying can be made safer occupied most of the first session of the Safety Council's aeronautical section at the New York meeting on April 17. Gill Robb Wilson was chairman and Grove Webster the lead-off speaker. Earl Ward and Fred Smith also represented CAA. In a discussion about airport controls for private flyers, David Little, Bill Lear, Roger Wolfe Kahn, Laurence Sharples, Jim Guthrie, Douglas Longstaff and Charles L. Morris were speakers.

At the afternoon session dealing with transport problems, T. P. Wright gave an illustrated talk, "Aviation Today and Tomorrow" and S. Paul Johnston gave an interesting presentation of recent developments in research that have increased safety in flight.

Route Rejections Tough

CAA has a lot of route applications pending and on the few of averages that's going to mean a lot of rejections. That each one is going to empty vials of wrath over the authority is indicated in the repercussions from the examiners rejection of the Great Falls, Mont., to Lethbridge route into Canada.

No satisfactory proof was presented, found the examiner, that there would be enough traffic to justify the line. Say local proponents, "So what." It's the only connection to Canada in 1,600 miles, and if the applicants failed to prove there would be traffic or that national defense is involved, the CAA should have hunted around and proved it for them.

Meanwhile plenty of local heat is being turned on the authority to reverse its examiner.

Pick-up Bids Called

All American Aviation's application for a CAA certificate of convenience and necessity was filed December 21, 1939, but because the Authority has not acted on it, and says it cannot act in the near future, the Post Office was compelled to call for bids on the system, to be opened May 10.

The Post Office call for bids requires bidders to have a suitable and safe pick-up-and-drop

AIR TRANSPORT INDICATOR

April 1, 1940

164.25

Which is the ratio of passenger miles reported by the Air Transport Association for all domestic lines for March 1940 to the figure for March 1939. Total for the Indicator has decreased slightly over the last month but still remains far ahead of last year. For the first three months of 1940 traffic stood at 181,564,287 revenue passenger miles—up 64.2 per cent.

See Finance page for individual companies' traffic figures.

gadget. Several such are said to exist, beside the one developed by Dr. Lyle S. Adams and now in use by Du Pont. But any bidder must face the fact that if successful his contract would be cancelled by the PO when CAA awards a certificate. No one but Du Pont has applied to CAA for it. Odds would be heavy against any new-comer applicant.

Pan American's Plans

PAA is still waiting to start its San Francisco-Los Angeles-New Zealand run. CAA has not yet decided whether to OK the Los Angeles jump-off. The company wants it badly as a good source of traffic to Honolulu, which would be a way point. Daily runs to Hawaii would be an early possibility. High speed high-altitude four-engined planes will be used. Long ago PAA agreed to share possible daily service through joint ownership with the Matson steamship line, but that matter is up to CAA now.

PAA has gone back to its summer route: direct to Lisbon via the Azores. One of the big Boeings has been put on the Bermuda run, with 60 seats to handle spring business.

The company has filed applications for two more routes southward: one from New Orleans direct across the Gulf of Mexico to Guatemala via Merida, Mexico; and one from Los Angeles to Mexico City.

Orders soon will be issued to Douglas for the first three of a fleet of DC-4s for Pan American-Grace Airways' South American west-coast-and-trans-Andean line to Buenos Aires, which will be within 48 hours of the United States when things get going.

Nix—Freight Rate Rise

Representing a significant step in airline rate history, United Air Lines on April 10, inaugurated a 25 per cent reduction in Los Angeles-San Francisco fares over their Coast route. The move was made following authorization by the CAA and covers schedules served with the older Boeing 247 type transports which make a number of stops en route. Regular schedules are flown non stop with Douglas DC-3 equipment. The new low fare averages 2¢ cents per mile and will be tried for a period of six months. It is thought that travel to the 1940 San Francisco Exposition will be stimulated materially over this route as a result of this fare concession.

Airline Doings

American Airlines awaits CAA action on its application to operate from Dallas-Fort Worth and El Paso to Mexico City. Eastern section of proposed route would be via Eagle Pass, Texas, and Monterrey, Mexico. Monterrey would have air service for the first time, if route is approved. Ordered four Douglas DC-3s, two 14-passenger DC-3 skysleepers, and 15 forty-passenger DC-4's for delivery early in 1941.

TWA, Inc., seeks a route from Amarillo, Tex., to Dallas, Fort Worth and Houston, via Lubbock, Abilene, and into Austin. Jack Frye, president, says if application is approved, TWA will schedule direct service from Texas to Pacific Coast. TWA also seeks a direct route between San Francisco and Los Angeles, another between Pittsburgh and Boston, and between Kansas City and Denver. To serve Washington for first time directly from San Francisco, Amarillo, Tex., and the Grand Canyon, TWA proposes another new air route. Stops en route would be at Evansville, Ind., Louisville, Ky., Cincinnati, and Parkersburg.

Braniff's growing pains also include a Washington service. The line would establish a route from Kansas City to the capitol city, via Jefferson City, St. Louis, Evansville, Louisville, Lexington. Service on the route for which CAA blessing is sought would be operated entirely with Douglas DC-3's. Company also seeks the proposed Denver-Laredo, Tex. route, via Colorado Springs, Pueblo, Amarillo, Lubbock, Big Spring, San Angelo and San Antonio, with a correlated route from Lubbock to Abilene, Austin and Houston.

AVIATION FINANCE

Spotlight in aviation financial circles is held by the proposed Curtiss-Wright-Atlas Corp merger as stockholders prepare to vote on the plan. Airline companies enjoy record first quarter traffic and earnings while aircraft manufacturers rush production on business scheduled for delivery this year, and garner large orders for 1941 shipment.

Curtiss-Wright-Atlas Corp. proposed merger, will come to a decision late this spring when stockholders vote on the plan. It has been strongly intimated that Curtiss-Wright directors would give consideration to common dividend payments upon approval of the merger.

Domestic airlines handled a record volume of traffic in March, exceeding that of last October, the best previous month. Eastern Air Lines was principally responsible for the new high record. Traffic over the EAL system is usually at a seasonal peak in March.

Braniff and a number of other airlines—but none of the transcontinental units—enjoyed record March travel. Profitwise, the March gains enabled the air transports as a whole to break about even in the first quarter. At the end of February the domestic airlines had a two months' deficit of around $500,000, as compared with a loss of $780,000 last year. In 1939 the industry was not in the black until April.

Douglas Aircraft completed delivery of its first French war order in February. Shipments that month were around $5 000,000, may rise to a monthly peak of $7,000,000 this summer. Large scale commercial and military deliveries from orders now on the books will extend well into 1941.

Aluminum Company of America plans to double the capacity of its Los Angeles plant at a cost of $2,000,000. This expansion is a direct result of increased demand from aircraft industry.

Lockheed produced 358 planes in 1939, compared with 93 the previous year. Output in the first quarter this year averaged 25 planes monthly, somewhat under the best rate reached last year. With unfilled orders at record levels, production will be speeded up as fast as engines are available.

Registration of 230,200 shares of Solar Aircraft Company $1 par value stock for trading on the Los Angeles Stock Exchange became effective April 13. Concurrently, Edmund T. Price, president, issued a statement calling attention to the growth of Solar from gross sales of $158,462 for 1938, to $533,847 for the fiscal year ended April 30, 1939, and to $461,148 for the six months ending Nov. 11, 1939. Backlog is currently about $1,250,000 and current deliveries are at the rate of more than $100,000 per month.

Beech Aircraft delivered sales were $332,000 for the six months ended March 31, 1940, up from $281,000 a year ago. Beech is doubling present plant capacity to 30 planes monthly.

Piper Aircraft unfilled orders were above 900 planes in April. Installation of an overhead line slowed up output in the first four months this year.

Bendix Aviation sales increased approximately 6% in the first quarter of 1940. At the same time new orders approximated shipments and unfilled orders currently stand about $37,000,000, a gain of $25,000,000 in the past nine months. A dividend of 50¢ has been declared payable June 1.

Sales of **Interstate Aircraft and Engineering Corp.** for the first ten months of the current fiscal year were $245,373, up 117% from a year ago, according to Don P. Smith, president. Backlog April 1 stood at $230,000, an increase of 234% from the previous year while net profits were $24,694, as against a $31,345 net loss.

Micromatic Hone Co. earnings for the first quarter amounted to around 48¢ a share, as against 12¢ a year ago. Application will be made shortly to list the stock on the N. Y. Curb Exchange. Some 35% of current sales is for aircraft precision products and incoming orders are in excess of shipments.

Northrop Aircraft with a backlog already above $2,250,000 as a result of a parts order from Consolidated, and an order for 24 monoplane seaplane bombers from Norway, expects to have about 1200 employees by June.

Braniff's recent stock issue was oversubscribed the first day of offering . . . Vultee Aircraft unfilled orders were $14,860,000 on March 1, as compared with $915,000 a year ago . . . Trans-Canada Air Lines reported a deficit of $411,656 for 1939, expects a profit this year . . . Eastern Air Lines set an all-time passenger record March 21, by carrying 1,218 passengers that day . . . Eaton Mfg. Co. is increasing productive capacity of the aircraft engine valve plant at Battle Creek, Michigan . . . Curtiss-Wright had $35,431,000 in advances on sales contracts on January 1, and United Aircraft had similar advances of $26,481,000. Most of these cash balances related to foreign war orders . . . Ryan Aeronautical unfilled orders recently totaled approximately $1,880,000 . . . Dow Chemical is increasing output at the Midland, Michigan plant 50% through construction of a $500,000 rolling mill to produce Dowmetal . . . Fairchild Engine & Airplane has plant expansion under consideration . . . Lockheed received $615,000 in new commercial business in March . . . Martin first quarter sales estimated at around $9,000,000 . . . Solar Aircraft has received the second largest order in its history ($150,000) from the Martin Co. for military plane parts.

Current Earnings Reports

Company	Period	Net Income— 1939	Net Income— 1938	Common share earnings 1939	Common share earnings 1938	Sales 1939	Sales 1938	Back-log 1940	Back-log 1939
Aviation Corp	Yr. Nov 30	d 2 238 000	187 960	d	0 07	8 301 000	6 373 000	4 464 000	418 000
Bendix	Dec 31	4 452 000	156 048	2 14	0 07	41 726 000	20 893 000	37 000 000	
Boeing	" "	d 3 284 000	d 554 300			21 896 100	3 000 000	23 102 000	14 894 000
Braniff Airways	" "	45 824	25 756	0 56	0 38	1 749 299	1 395 144		
Breeze Corp	" "	177 128	135 367	0 76	0 43				
Brewster	" "	9 076	233 879	0 02	0 66			27 850 000	2 002 000
Bellanca	" "	286 000	d 22 171	1 04		3 565 746	2 985 411	5 421 000	628 000
Curtiss-Wright	" "	5 212 255	2 498 738	0 59	0 17	48 654 142	33 102 962	144 030 000	31 540 000
Douglas Aircraft	" Nov 30	2 884 066	2 147 392	4 81	3 75	27 866 000	28 347 000	97 287 000	22 500 000
Fairchild Av	" Dec 31	422 740	322 473	1 25	0 98	2 903 116	2 105 815	2 101 000	1 070 000
Fairchild Eng	" "	187 894	d 185 229	0 18		1 343 013	702 247	1 875 000	290 000
Grumman	" "	892 063	617 074	1 85	1 30	4 478 889	4 904 846	6 000 000	3 800 000
Lockheed	" "	3 132 018	442 111	4 04	0 87	35 308 000	10 274 800	57 330 000	33 390 000
G L Martin	" "	4 110 865	2 349 355	3 75	2 15	24 189 000	12 417 000	48 241 000	13 903 000
No Amer Aviation	" "	7 068 066	1 904 700	2 06	0 56	27 608 000	10 062 000	51 589 000	10 014 300
Penn Central	" "	83 318	d 20 868	20		1 857 493	1 480 894		
Sperry	" " 31	5 462 000	4 019 900	2 71	2 46				
United Air Lines	" "	322 121	987 221	0 21		12 287 000	9 925 000		

d — deficit

With the Airlines

Company	Revenue Passenger Miles* March 1940	March 1939	% Gain	9 Months 1940	9 Months 1939	% Gain	Revenue Passengers March 1940	March 1939	% Gain	3 Months 1940	3 Months 1939	% Gain
American	21 257	12 337	72	54 147	31 010	61	54 840	30 208	81	138 518	76 121	83
Braniff	2 831	1 432	95	6 390	3 748	78	8 718	4 720	85	20 245	11 917	66
Chicago & Southern	907	577	50	2 159	1 442	50	2 266	1 397	62	5 395	3 564	54
Eastern	15 000	10 419	59	41 000	26 324	56	28 000	18 308	45	71 000	47 425	81
Northwest	2 814	1 438	96	7 501	3 802	[illegible]						
Penn Central	2 438	1 480	68	5 839	3 428	65	13 233	7 922	67	21 000	18 206	61
T W A	9 200	6 007	53	22 330	12 763	62				a 27 024		
United	13 300	8 689	53	32 423	20 443	59				a 38 184		
Western Air	1 072	580	84	1 443						a 5 377		

* (000-omitted) a — 2 months — current figures subject to final adjustment

PROFIT & LOSS

Trusts Buy Aviation Stocks

By Raymond Headley

Mr. Headley will be very glad to answer your questions regarding the financial outlook of listed aircraft companies

Aviation stocks are coming into pronounced favor with the investment trusts as well as with the average investor. This is borne out by the eleventh annual survey of stocks held by 78 investment trusts made by the brokerage firm of Frazier Jelke & Co. According to the survey these concerns greatly increased their share holdings in the aviation field in 1939 along with heavier purchases in the steel, automobile and chemical industries. These gains were made at the expense of the building, rubber and amusement industries as holdings in those groups declined. As a result of phenomenal growth and attractive current outlook, aviation since 1936 has come up from nineteenth to thirteenth position among the industries in which investment groups place their funds. The number of Douglas Aircraft shares held by these trusts increased 172 per cent last year, Martin 75 per cent, Lockheed 63 per cent and United Aircraft 28 per cent. Of special significance is the increasing preference on the part of these institutional investors for air transport stocks. American Air Lines and Eastern Air Lines appeared in the survey for the first time in 1939 while heavier commitments were made in Pan American Airways and United Air Lines.

In this investment "popularity contest" United Aircraft Corp. led all other aviation stocks by a rather wide margin, appearing in the portfolios of 35 trusts. In fact, United tied Bethlehem Steel at the 1939 year-end for sixteenth place among the most favored of all industrial stocks. (Kennecott Copper, found in 56 investment lists, was the all-industry favorite.) The Martin Company was the second most popular aviation issue, having representation in the investment folders of nineteen trusts. Closely following in popularity were Douglas, Pan American Airways, United Air Lines, Eastern Air Lines, Curtiss-Wright A stock, Lockheed, American Airlines, Consolidated Aircraft, North American Aviation, National Aviation, TWA and Boeing.

As the largest aviation financial deal that has been proposed since 1929, the Curtiss-Wright-Atlas Co. merger is a main topic of conversation in Wall Street. Interest centers around the $36,500,000 cash "kitty" that Curtiss-Wright would receive from Atlas on consummation of the plan. There has been gossip that C W plans to buy up some accessory and machine tool companies—become the Henry Ford of aviation. It appears more likely that the money would be used to retire new preferred stock that would be exchanged under the proposal for present Atlas preferred and Curtiss-Wright class A stock. This would achieve in a roundabout way the capital set-up—only common stock outstanding—that Curtiss directors have sought for years. It would give Curtiss-Wright a capital structure more in keeping with that of other aircraft companies and more suitable for an industry which has consistently shunned the pyramiding of large issues of senior stocks and funded debt ahead of the common stock.

First quarter earnings of the aircraft companies were only a preview of the higher profits expected later this year. Shipments in some cases like Lockheed and Martin were lower than in late 1939 although well above a year ago. Recent difficulties in securing engines will be eased shortly when the impetus of the engine companies' expansion programs begins to be felt. Meanwhile accessory companies like Bendix and Thompson Products are likely to report the largest relative lift in first quarter earning power due to gains in both their aviation and automotive divisions.

AVIATION OPERATORS CORNER

10,000 Cash Customers

This summer there will be 10,000 new pilots looking for a place to fly. Most of them will have money to rent airplanes. Operators who want their share of this new business should spend the month of May getting ready for it.

Approximately 5,000 of the pilots trained by CAA live in the same general vicinity where they learned to fly, and presumably they will continue their flying with the same operator. Needless to say, any operator who has had a group of CAA students should do everything he can to hold on to his boys. And don't let anyone fool you that these youngsters won't keep on flying! About 70 per cent of last spring's class kept up their flying.

The other 5,000 college boys have been attending school away from home. Many of them may live in your community and when they come home in June they are going to start looking for a place to fly. In "Don't Give Up the Ship," in this issue we have urged the new pilots to keep up their flying. It is up to you to let them know you are ready for business and that you want their trade.

They have had 35 hours or more of excellent instruction and you can trust them with your ships. But they are used to flying in clean airplanes that are well maintained. So wash off the mud, and make sure your ships are kept tuned up.

The boys are all going to want to try their wings at cross-country flying. They can pay for it, but they can't pay too much. Don't kill the goose that lays the golden eggs by charging too much.

You usually have to spend money to make money. Last month we suggested an advertising service by Norman Warren that costs $5 a month for four advertisements. Whether you use his ads, or your own, it may pay you to do some advertising to attract your share of the new business this summer.

Southwest Airmotive Company is the new name of the former Booth-Henning organization at Love Field, Dallas. The firm will no longer handle airplane sales, but will concentrate on service and repair. It holds every class of CAA rating for repairing ships.

Mal Nuss tells us that the Reading, Pa., airport is being groomed for big things this spring. The town hopes that TWA will soon be using the airport regularly. Lighting equipment is being installed and runways are being lengthened.

Chicagoland Glider Council was active throughout the winter and has extensive plans for its spring program. Over 10,000 spectators came out to see the soaring show at Elmhurst Airport in February. About 30 pilots flew the seven sailplanes.

Fort Wayne, Ind., Aero Club announces its Fifth Annual Air Show for Sunday, July 21. Last year over 35,000 persons saw the show. Now that Cleveland has given up the Races, Fort Wayne plans the biggest attraction of the Mid-West. Bob Schatt will direct. The Club has a membership of 185.

Toronto, Canada, is proud of its new airport which was recently finished. The city converted a barren waste of sand on Toronto Bay into a splendid 178 acre field. The airport has two 3,000-ft. runways that are hard-surfaced and an additional 3,000-ft. grass runway plus several taxi strips.

A 160x120 hangar and a splendid administration building have just been finished. A completely equipped seaplane base is also new. Pilots using the Field can get to the business section of the city within ten to fifteen minutes by using a cable ferry installed for airport use.

Bowlus Sailplanes continues to make news, this time with its attractive folder describing the ABC of Soaring and a pictorial presentation of how its sailplane is put together from the Bowlus kit.

Operators looking for additional college business—and the profits from college-boy flying will definitely increase in the next few years—might study the success of the University of Southern California Flying Team which competes in one or two tournaments each month. College flying clubs, in which ships will be bought or rented from local operators, is a worth-while feature for all operators near college towns.

Timm Aircraft Corp. has sold its repair division, located on Grand Central Air Terminal, Glendale, to W. D. Timm, who has resigned as secretary treasurer of the corporation to devote all of his time to the rapidly expanding repair business.

Originally established by W. D. and Otto W. Timm some six years ago, this repair business was the nucleus around which the present Timm Aircraft Corp. was formed. K. W. Moore, comptroller and formerly assistant secretary of Timm Aircraft Corp., succeeds to the position vacated by W. D. Timm.

Michigan airparks are getting ready for the light plane tour that will travel up through the state the last week in June. Col. Floyd Evans, State Director of Aviation, expects at least 200 airplanes from Southern and Eastern states. Traverse City will be northern terminal. There will be no alligators, but you can count on some of the best fishing the country offers.

Birmingham Air Carnival will be held June 1 and 2. This is the tenth affair and Steadham Acker insists it will be the best. Throwing modesty to the winds, Birmingham says its carnival is the largest air show in the world, and they may be right at that.

TRAINING
Of Air School

Spartan School of Tulsa is booming these days, with nearly 400 students in the various departments. About 160 Flying Cadets and some 75 Air Corps mechanics are at the school, with new Cadets arriving every six weeks.

New equipment at the school includes a Weidenhoff Electrical Testing Unit, a new brick building for class purposes, and additional equipment for the engine, instrument and metal shops. One building is set aside for the study of fuels, oils and carburetion. The school is directed by Capt. Maxwell W. Balfour.

Prof. Wm. A. Wheatley has been appointed United Air Lines' Director of School and College Relations. With many years behind him of experience in public school and educational work, Professor Wheatley will build good will for United with the schools and colleges of the country. His office will be in Chicago but he will spend much time traveling up and down the lines.

More schools should follow the example of Herbert Hartley of the American School of Aircraft Instruments of Glendale, Cal. Not being content to get the real facts about what the industry wanted in instrument repairmen from just his own neighborhood, Mr. Hartley has taken a swing around the entire country, calling on airlines, overhaul bases and factories. His training course will be closely geared to what industry is looking for.

Delgado Trades School in New Orleans was given nineteen airplane engines and considerable other equipment for its aviation course by the Army recently. The aviation course covers three years and has about 400 students enrolled.

Rising Sun School of Aeronautics in Philadelphia placed 38 graduates last month. New school equipment includes a 1,050 hp.



New Hangar at Toronto

Wasp, two Lycoming 65s, and two Continentals. Four Taylorcraft fuselages were brought in for rigging and welding work.

Omaha, Neb., has such a successful ground school run by the Junior Chamber of Commerce that a second and more advanced course has been organized. The first course ran once a week for six weeks and attracted 1,500 persons.

Students out of the Ryan School in San Diego got a lot of fun out of watching the new Ryan Dragonfly that was described in our last issue. One flying cadet at the school expressed his bewilderment this way:

"I was coming in for a landing and the first thing I knew I passed under some shade that shouldn't have been there. I looked up and saw the Dragonfly about a thousand feet above me but I knew he couldn't get into the field from as high as he was, so I came on in and landed. When I looked back after landing, there was the Dragonfly sitting on the ground about 200 yards behind me, and, by the time I had taxied back to the line the "Dragonfly" was floating around again at 1,000 feet."

Boeing School of Aeronautics placed 250 students with 58 different firms. The school will expand its facilities this summer when it will take over space vacated by United Air Lines, which is moving from Oakland to San Francisco. Several Boeing students have recently gone to Cheyenne to begin work at the main U.A.L. base under the new apprentice plan.

Due to increased somber of students, both space and equipment have been increased at the Lucombe School of Aeronautics at West Trenton, N. J. Several new engines have been installed including a Continental with fuel injection. New propeller and shop equipment has also been added.

When an aviation school runs an airline—that's news. And yet the advanced students of Parks Air College have been doing it every spring for six years. Round trip scheduled flights carrying "passengers, mail and express" are made from the home airport at East St. Louis to Chicago, Indianapolis, Memphis and Kansas City.

All procedures closely follow regular airline practice and provide excellent experience for students who will later go into airline work.

The latest addition to the equipment used by the Alabama Institute of Aeronautics to instruct the advanced C.A.A. students from the University of Alabama is the new Meyers biplane. The Meyers with a 125-hp. Warner engine is a two-placed biplane with metal covered fuselage and fabric covered wings. The advanced course consists of from 35-50 hours of flight instruction in the Meyers and 144 hours of ground school work. The students taking the advanced course have to have first secured their license from the basic C.A.A. course. The prime purpose of the Meyers is to instruct the students in acrobatics and advanced instrument flying.

Although aircraft factories of Los Angeles County are already employing more than 25,000 workers, and are adding to this total steadily, they have acted to stem the tide of hopeful youths who have rushed to Southern California from all parts of the country only to be stranded without jobs in all too many cases. Frequently these young men have come to California in response to sales solicitation by "mushroom" aviation schools, of which dozens have sprung up during the recent boom. To meet this situation the personnel managers of Southern California aircraft plants recently cautioned boys against these mushroom schools.

Meyers Trainer Used at Alabama

JERRY SAYS

By JEROME LEDERER

Fire extinguisher Ordinarily the one quart Fire Extinguisher in most conventional airplanes is held in its bracket by side and end clamps. Care should be taken that the extinguisher is properly placed in the bracket and the clamp secure. If the extinguisher should become loosened by the seat, by clothes, shoes, by the parachute or just by climbing in and out of the airplane it will usually fall upon the floor and may jam the controls. If this happens when making a landing or takeoff or in violent maneuvers, it may result in a crackup. A new type of fastener has a band around the extinguisher with a quick opening device which appears to be very good and should be used.

Hot air at LaGuardia airport The seven hangars at LaGuardia Field encompass 33,000,000 cubic feet. Each hangar could accommodate a full sized football field with plenty of room for spectators. From floor to bottom of trusses is 42 feet. Doors 160 feet long and 40 feet high open to the full sweep of cold winds from the bay.

Despite the tremendous problem of heating this hangar space, a temperature of 55° F is maintained in the hangar, 65° F in adjacent shops and 70° F in the offices. When hangar doors are opened and then closed at an outside temperature of 30° F, the hangar can be heated to the desired temperature in 10 minutes. Warm air discharged at the floor line and returned to the heater room also at the floor line, gives a minimum difference of temperature between floor and ceiling. Actual readings show a temperature difference of only 5° between floor and ceiling.

Thirty 3,150,000 BTU per hour hot air units furnish the heat. The air being heated is always under positive pressure while the gases in the combustion chamber are always under a slight negative pressure. This means that the products of combustion can never pollute the air stream.

More landing fields Among the good by-products of the Civil Aeronautics Authority's Pilot Training Program is the establishment of more landing areas (not airports). The students must fly over a triangular 50 mile course landing at approved fields. In many sections of the country these fields were non-existent until recently when the program forced them through. We already have 2,300 landing areas or airports. Few people realize that the addition of only about 1,200 inexpensive landing fields would enable a pilot to be within ten minutes of a safe place to get down at any time assuming a cruising speed of only 80 miles per hour. Florida, Michigan and Nebraska have landing field programs under way. Lets hope other states will follow. More landing fields make the pilot less dependent on weather, gives him more places to go, increases the utility of airplanes.

Rear locks With airplanes being parked out in the open on a larger scale than ever before, it is important to have good doors and door locks to prevent pilferage of valuable equipment. One point to watch in these door locks is that water cannot get into them and soak the inside of the door especially if there is sound proofing or trim material in it. This increases the weight of the ship and is likely to cause corrosion. It is recommended that drain holes be placed at the bottom of the doors to let the water run out. On transport ships, most of the water enters through the door locks. On private ships it may enter through the windows.

"I wasn't play, too" "In connection with candidates not physically qualified for flight training, the Base at Philadelphia reports an unusual instance. One candidate appeared for physical examination and his eyesight was such that if he looked anywhere but ahead he *saw double*. The commanding officer commented that the student could not be accepted. However, he would be in position to fly formation with himself in the Link Trainer."

WHAT I SAY....

A well-known private pilot presents the views of his fellow flyers.

We took delivery recently of a new Stinson '105' The weather had been bad for several days and they were still test-hopping the ship when we arrived After a rigging check flight, the pilot made a series of careful approaches and landings and then taxied in with a note for the mechanics. Upon inquiry we learned he was making "landing tests"

That was a new one to us What did one test for on landings? It turned out that accurate observations were made of the necessary back-stick movement to make a three point landing under the most nose heavy condition With that known, an elevator stop is riveted in place, and henceforth the ship can never be brought up to a full stall from approach or climbing speed It's an old trick, but it is refreshing to see the factory doing it on all airplanes—and definitely, as the ladies say.

We understand the restricted elevator and the built-in slots are considered to contribute about equally to the '105's' excellent stall resistant characteristics This brings us right to the old problem of cause and effect. The C A A favors stall resistant airplanes They also require spins for license qualification The problem is theirs. Which is it to be? Must the '105' owner hire another, and less safe airplane than he wishes to fly in, just to prove far license test that he can get out of a maneuver he will never get in?

We were sitting in the back end of a DC-3 as it came into a small but thriving city in the middle south About the time the wing came up to completely obliterate our view ahead, the pilot suddenly steamed off and went around for another approach and a lovely landing During the brief loading stop we asked the pilot what had happened "Oh", he growled, "a blankety blank Cub was just off the runway and pointed away from me I didn't know whether he was going to take off or not"

That was certainly good judgment, but just to draw the pilot out, we observed mildly, "Yeah, I suppose you airlines will soon have to build your own right of way like the railroads, and make your own airports all down through here" If we had hit him with a ball bat he could not have been more astonished With plenty of beat, he came right back, "This is a municipal airport. The city seems to want us here badly. If those blame private ships don't get out of our way, they'll have to run *them* off to other fields"

We looked around There were six of them moving around on the ground or within sight in the air and knowing that there were only four airline schedules in and out of the airport each day, we wondered if a downright vote wouldn't show the citizens preponderately in favor of devoting their airport to private flying That would be a ridiculous situation, so instead we lead with another thought.

"We don't see that your problem is with the private fliers They are in the same boat you are when it comes to traffic, and they want to keep out of your way fully as much as you want them to. Seems to us that if the airport manager just took the trouble to drive out and wave red and green flags a few minutes before you are due in, that everyone would be happier and safer. Looks to us as if your quarrel was with the manager and you ought to get him to do something about it"

That great big pilot—representative of the best elements we have in flying today—looked just as astonished as he had a few minutes before. "Gosh", he said thoughtfully, "I never thought of that!"

There are many enterprising airlines and airports down through Central America, but best of them all are the splendid facilities of Pan American Airways We presume a private pilot wandering down through there is nothing but an annoyance to them, but you'd never know it On a recent trip to South America through the land airports of the Central American republics and back by way of the sea bases of the West Indies—we were flying an amphibian—we were the most grateful guest of the finest flying outfit in the world From the time George Kraigher took us in hand in Brownsville until we taxied up the ramp at Dinner Key, we were made to feel at home and our way was marvelously smoothed for us

Pan American charges are not low—quite the opposite—but the service is incomparable Without our thinking of it, our plane was supplied with a box of regulation Panair chewing gum and drinking cups At San Jose we stepped off the hotel elevator at six on a Sunday morning. A Panair station manager was already there to tell us that our tail wheel tire had gone flat over night and should they replace it for us while we were at breakfast? Without exception every detail to make our trip pleasant was anticipated and provided for It was private flying at its best

A friend of ours, landing his Beech at a large terminal airport, stopped to watch a DC-3, just fresh from a complete overhaul, taxi out for its first subsequent check-hop. The tired chief mechanic, an ex-Army sergeant, who had worked overtime many nights to complete the job on schedule, leaned wearily against the hangar door and lit a cigarette

The great ship wheeled into position Inside, the pilot locked the tail-wheel and requested the assistant, riding for the test-hop as co-pilot, to release the landing gear safety-latch Being new to that job, he not only released the latch, but also tripped the landing gear raise lever Slowly the big ship lurched to the right first crumpling that wing while the prop went to work on the concrete, then settling to the left creating equal havoc on that side. The noise stopped. The dust settled The ex-Army sergeant disgustedly spat on the apron, and ejaculated with all the vehemence of a curse, "Scuttled, by God"

For a hundred dollars you can buy a marvelous little black box for your ship It has a minimum of knobs and gadgets, and you can talk through it as far as you need to when flying You have to take a test for license to operate it. One of the questions asked is what you should do if you suspect it isn't operating satisfactorily The right answer, and the only one they will accept is, "Turn it off and get a radio technician to look at it".

If that precept is known and understood, it seems to us that all the folderol about licensing you and licensing it—at least for the itinerant aircraft frequencies—is entirely unnecessary Right now, the Federal Communications Commission looks on your little black box just as they do on WGY and KDKA, or the transmission of the Arlington Time Signals You even have to file the complete corporation details of your company to get the right to use it.

AT THE CHICAGO SPORTSMAN SHOW this attractive Taylorcraft was exhibited Equipped with a 65 HP Lycoming and given a special hand-rubbed finish, the ship caused much favorable comment It was furnished by the Fox Valley Flying Service of Aurora, Ill.

Take to The Water

(Continued from page 34)

built and the operator has a crowd of from 5,000 to 10,000 people to draw from. At Austin, Texas, Harry Hamil, Beechcraft distributor, is busy these days from his seaplane base operation. At Hot Springs, Ark., Paul Miller flies Cubs from the river. In New Orleans the Chapman Air Service flies Aeroncas on floats.

The East Coast has dozens of seaplane operators, only a few of whom can be mentioned. One of the oldest is the Winnepesaukee Air Service of New Hampshire, founded by Bob Fogg, who is now the Seaplane Facilities Expert of CAA and who is the man to ask for help or advice concerning seaplane bases. The seaplane service he founded is now in its nineteenth year, and has flown some 60,000 passengers without an accident of any kind. Jack MacManus also has a well established base on Lake Winnepesaukee. Guy Ham has had a charter service for five years at West Falmouth, Mass. In Boston, Robert Love has a school and charter service and demonstrates Stinsons, Aeroncas and Fleets. Another successful Boston operator is E. H. Wiggens, who puts some of his ships on floats in the summer and takes them to Naples, Me.

Another operator who shifts his base twice a year is H. L. Redfield of Syracuse. In summers he goes up to the Thousand Islands and in the winter he takes a Waco to Winter Haven, Fla. Thanks largely to CAA, Florida has over 30 new seaplane floats and another dozen will probably be built. Florida is a "natural" for water flying. In Miami, Embry Riddle is [illegible]. He has a class of CAA college students from the University of Miami that is learning seaplane flying.

One of the Atlantic states' best known operators is Glenn T. Clark of Charleston, W. Va. You would hardly expect to find a successful seaplane base in the heart of the Blue Ridge Mountains but there it is. Clark used to fly from the airport 10 miles out of town but decided to move in where the people were. So he bought an old barge and built a hangar on one end at a cost of $700. Since 1932 he has expanded several times. Being on the water front, he gets lots of visitors so he built a restaurant for them, also put in an out-board motor boat business and other attractions which pay him well.

Under State Director "Les" Morris, Connecticut is putting on an active seaplane base program. By July ten bases will have been built. The state pays the $150 for lumber and material and NYA boys do the work. Later, if the individual towns show the right spirit and responsibility, the state will turn over the bases to them but at present the state maintains and operates them.

The area around New York City, with its miles of rivers, bays and inlets is attracting more seaplane pilots every year. In the past two years, four operators have established successful seaplane bases in one area in Ridgefield Park, N. J., a few miles west of the 125th Street Hudson River ferry. Although all are within 3,000 ft. of each other, no one complains about competition.

Bill Mellor and John Howard, both commercial pilots with instructor's ratings, operate the A.F.A. Seaplane Base on Overpeck Creek. They have a J-3 Cub and a Waco three-place open ship, and have a new Cub 65 on order. In the past year they took 650 passengers for rides and gave about 250 hours of dual instruction. They soloed 47 students and have about 68 active students now. They expect to solo at least 125 students this year.

Tony Barone, W. Gatto and R. P. Hahn operate the North American Flying Service at Little Ferry, N. J. From their base on the Hackensack River they operate two Aeroncas. Last year they soloed 39 students and took 470 passengers for rides. They now have about 60 active students. They are building a new hangar and have plans to buy two new ships.

The Modern School of Aviation, also on the Hackensack River, operated by Garofalo, Kohn, Zoeller and

(Turn to page 97)

Cyak Air Service ramp, Cordova, Alaska

The Milwaukee Seadrome has a landing field in front of the hangar and a seaplane base behind it, and thus both land and water pilots are satisfied.

(*Continued from page 94*)

Emery, flies in Taylorcrafts. Last year 43 students soloed and their charter business was excellent. A new Taylorcraft and a Luscombe are on order and the partners expect a big summer.

A fourth operator, Harold Lenz, with a base at Sky Harbor, lost his barge and two seaplanes in a fire recently, but he is getting new airplanes and expects to be back in the running this summer, probably from a base at Seacaucus. The success of these four bases is typical of what can be developed when operators capitalize on the natural desire of people to be near the water.

Another rapidly growing seaplane base near New York is on the Hudson River at Dobbs Ferry. The Westchester Private Flyers used to fly land planes from the Valhalla airport. Last spring the club moved to Dobbs Ferry, constructed a float, a ramp with a marine railway and a small hangar. Starting in carefully, they bought one Cub on Edo floats, but members were so pleased with off-the-water flying that a second Cub, with a 65-hp. engine, is now being delivered. The club has over 60 members, headed by George Helwig who is president, and Ross Weaver, treasurer. Lee Lord is instructor.

Nelson Miles, who operates out of the Gulf Seaplane Base at Fort Washington, Long Island, has run a successful seaplane business for a number of years. He does a lot of charter work, operating Bellancas, Stinsons and other such planes. The Gulf hangar services some 40 seaplanes. The McKinley Pneumatic Float Corp. has a base at Babylon, Long Island, and teaches a CAA college group seaplane flying, and hangars a number of private planes.

The story of the Wall Street ramp in New York is fairly well known. Every year sees more business men commuting by seaplane. This successful development is typical of what every large city on a water front will have in a few years.

In the Los Angeles area, the chief exponent of seaplane flying is Kenneth Baetz, who is now in his third summer at Cabrillo Beach. He has done two things particularly well: provided practical and attractive facilities, and he has done a good job of advertising. Facilities consist of a float, ramp, dolly and a hangar, plus a ticket booth, wind sock, and a nice set of signs that advertise his business. Baetz built an efficient dolly, and also constructed his float, the latter at a cost of less than $100.

A Grumman amphibian arriving at New York City's Wall St. seaplane ramp.

A Beechcraft biplane on floats with an Edo towing dolly.

A Waco about to take off.

Baetz's dolly is home-made, but it is very efficient. A pair of auto wheels is mounted on an underslung axle, with a long tongue extending forward for handling purposes. Main wheels are just back of mounted plane's CG and a pair of auxiliary wheels is set in front.

Business is about equally divided between pilots taking instruction or renting the plane for local flights, and the general public buying $1 joy hops or longer scenic rides over the Los Angeles harbor. Baetz is the only commercial seaplane operator in this vicinity. He uses a Cub-40 on Edo floats. Wes Carroll and Clyde Schlieper, also flying a Cub, have done some seaplane work out of Newport Harbor.

Advantages in Teaching

Seaplane fans claim that one of the greatest advantages comes in teaching. A student learning to fly tries to get in as many take-offs and landings as possible. But at a busy airport a student has to circle the field after every take-off, and he may have to go around twice. In seaplane instruction a student can take off and land in a straight line. Al Hummers, who flies at Ridgefield Park, reports he got in twenty take-offs and twenty landings in a half-hour period of instruction. There is also a reduced mental hazard for the beginner because there are no trees, telephone posts or other obstructions in the way.

Safety is also a factor. A seaplane that stalls or spins in usually lands in such a way that a wing-tip and a float hit the water first. This provides a cushioning effect. Planes have been completely demolished on falling into the water but pilots are seldom seriously injured.

What does it cost?

The problem of first cost stops some operators from buying seaplanes. Floats for a light ship cost $600. Corrosion proofing costs $100 and the factories charge about $60 to install the floats. This adds a list increase of $760 to the cost of a land plane. Many operators figure they save a good share of this in reduced hangar and airport expenses. Seaplanes can be winterized and left out on the water all summer. Around salt water extra care is necessary to stop corrosion. But the additional cost of a seaplane over a landplane can usually be made up by the increased business during the summer months. If the operator also flies from an airport he can remove the floats in the fall, put on wheels and still get his winter business. Through the South, floats are good the year around.

Ask Captain Fogg

Operators who want to get full information about any phase of seaplane operation should get in touch with Captain Robert Fogg, Airport Development Section, CAA in Washington. He knows the situation from coast to coast. He will provide literature describing seaplane operation and has many plans and specifications for bases, ramps, marine railways and dollys. He has been flying seaplanes for over twenty years and is a real enthusiast. In addition to the technical details, he is a master showman at knowing how to draw in the crowds for seaplane openings and ceremonies.

"Take to the water" is good advice for many operators because the public is fast becoming convinced that they can get plenty of fun on floats.

Vultee Production

(*Continued from page 41*)

and built in our shops This machine is powered with a high frequency electric motor which drives it at speeds up to 10,000 rpm, as compared with a maximum of 2500 rpm on conventional metalworking mills A considerable number of operations are performed on this mill, two more of which are being installed to give us a battery of three of these high speed machines An example of the time reduction through use of this fast cutting tool is given by the time of one hour and fifty five minutes recently established for a milling job which had previously required about thirty hours

In addition to such machines as we have developed ourselves, we have been able to purchase and install many different types of equipment representing the last word in aircraft production technique One such machine is the Erco automatic riveter which we use in the bench assembly department. With this machine one man can do the work of several by former methods The Erco punches the hole inserts and heads the rivet, all in the twinkling of an eye. Vultee is the first plant to place this new machine in operation although other factories now have them on order In our steel tube structure assembly department we have adopted electric arc welding almost entirely Through use of special jigs and arc welding we can assemble steel tube frames without any appreciable distortion Perhaps the most elaborate and efficient steel tube welding jig yet developed is now at work in our fuselage department This jig is mounted on a large cantilever frame which carries a master jig set-up in the center, and two side plate jigs on rollers These side jigs start at the end of the large master jig, where they permit workers and welders full accessibility for simultaneous assembly of the two fuselage side frames. As these frames are completed the frame jigs are rolled into position on the master mount in the center, and cross members are tack welded in place The side frame jigs are then rolled back to their original positions and new frames started while final welding work is done on the main fuselage unit, now held in position by end jigs at the center of the master jig frame

Rotating jigs eliminate awkward working positions and last time in shifting work to a more accessible position. A quick flip at jig makes work available.

Throughout the various departments where jigs are used for assembly it is standard practise to make them rotating so that the work may be made fully accessible to the worker Certain precision jigs, such as for the monocoque after-portion of the fuselage, are built on rigid cantilever bases which prevent distortion yet permit ready access to the work from every direction

Location of the paint shop in the center of the factory instead of at one side or entirely outside the main building, as has been common practice, has already proved itself a major point in smoothing out the flow of material along the various sub-assembly lines leading into the final assembly line. Of course the paint shop is fully fireproof and is protected by water curtains, automatic sprinklers, and fire doors

The aircraft production problems of tomorrow are to a great extent unpredictable With aircraft manufacturing technique developing as it is, our ideal factory of today can become outmoded by tomorrow unless we keep everlastingly at the job of keeping it up to date through study and improvement—and that is exactly what we intend to do

Engineers spent much time and thought over designs of Vultee final assembly jigs. They are of rigid cantilever construction and provide for great accuracy.

To pilots who have never had the opportunity of flying a Beechcraft and gaining first hand knowledge of their superior features, we offer the following reasons for making an early check-up.

1 STABILITY AT ALL SPEEDS Beechcrafts feel "solid" at all speeds from the stalling speed on up They answer the controls instantly and faithfully at any speed and require a minimum of attention during cross-country flights, even in rough air

2 FREEDOM FROM TENDENCY TO SPIN They practically have to be forced into a spin, and recover with a minimum loss of altitude when the controls are released. The biplanes can be turned completely around in a normal way in 15 to 20 seconds when fully stalled

3 HIGH PERFORMANCE Beechcrafts have *proved* their superior speed in *every* major free-for-all cross-country race since 1936 Their unique performance at high altitude has made them the choice of those whose business is carried on at high altitude, the mapping photographers.

4 LOW LANDING SPEEDS They have the lowest landing speeds of any airplanes in their weight classes. This is achieved by use of very low wing loadings and not by means of oversize flaps, which would tend to require precision landing technique Beechcrafts are easy to land in small areas by day or by night

5 WEIGHT CARRYING EFFICIENCY Beechcrafts are economical of fuel because of their high speed at low percentage of rated power As a result they carry more load over long non stop distances

6 SUPERIOR FLIGHT VISIBILITY Increased student activity has put a premium on flight visibility around busy airports The unique Beechcraft curved safety glass windshield permits the pilot a clear view toward the inside of any turn, *over the upper wing*

7 COMFORT Beechcraft occupants enjoy ample ventilation at controlled temperature, soundproofing, foam rubber seat cushions, and well-appointed cabin interiors Retractable landing gear and flap mechanisms are electrically operated and require no exertion

Any Beechcraft dealer will be glad to prove the superiority of Beechcrafts. A careful comparison will be convincing

BEECH AIRCRAFT CORPORATION

6411 EAST CENTRAL AVENUE WICHITA KANSAS U S A.

BEECHCRAFT

Snow Cruiser's Pickaback Plane

. . . controlled with American Tiger Brand Aircraft Strand and Cords



(Above) *Beechcraft, similar to the DiTA Model which is specially equipped and mounted on skis for use by the Byrd Antarctic Expedition All controls are rigged entirely with American Tiger Brand Aircraft Strand and Cords.*

MOORED on the roof of Admiral Byrd's famous Snow Cruiser, now in exploratory duty in Little America, is an interesting five-passenger Beechcraft biplane, mounted on skis. This ship, equipped as a laboratory, carries special aerial cameras for use in photographing and mapping the polar continent, Antarctica, from the air.

It is only natural that an airplane designed for service over the frozen wastes surrounding the South Pole, thousands of miles from the nearest airport, should be constructed of the most dependable products available. That's why all controls are rigged entirely with American Tiger Brand Aircraft Strand and Cords

These cables are a standard specification of successful aircraft designers and builders, for use in the control systems of commercial, private, and service craft Composed of uniformly cold-worked wire, precision-drawn to high tensile strength, these cables offer superior strength, excellent fatigue resistance, and minimum stretch They meet all requirements of the latest U. S Army and Navy specifications

THREE CONSTRUCTIONS

American Tiger Brand Aircraft Strand and Cords are available in either tinned, galvanized or U S S Stainless Steel in the following constructions

19 wire Strand	semi rigid
7 x 7 Cord	flexible
7 x 19 Cord	extra flexible

AMERICAN STEEL & WIRE COMPANY

Cleveland, Chicago and New York

Columbia Steel Company San Francisco, *Pacific Coast Distributors* United States Steel Export Company, New York

UNITED STATES STEEL

How Luscombe Builds Metal Planes

(*Continued from page 45*)

treated member, and the gears have been sent out for this processing. Luscombe has since installed its own heat treating equipment.

Because of its semi-cantilever construction, the Luscombe gear requires only a .125 stainless steel strap to complete the triangle from the axle to the extreme inside of the upper leg. Because of the absence of an external oleo strut and shock cord, the Luscombe gear gives a slender appearance and is more easily streamlined.

After installation of landing gear, wheels and tailskid, the fuselage receives the stabilizer and vertical fin. Both are stressed skin structures, consisting of Dural channel section frameworks which are jig assembled. Because of the narrow nature of these structures special bucking dollies have been built to reach into tight spots. Riveting the covering skins to the stabilizer frame requires considerable care to avoid the possibility of allowing them to get out of tension in spots, which will cause "oil canning."

Elevators, ailerons and rudder use corrugated Alclad covering skins. These skins are cut to shape on the Niagara shear and on a bench shear, and fed into a corrugating die on the Lynch press brake which automatically maintains the same distance between corrugations. This corrugating process was formerly done entirely by hand. Ailerons are mounted to the wing on ball bearings.

The visitor to the Luscombe plant frequently wants to know what all the "rails" are for. The I-beam extrusions, which are wing spars in the rough, are neatly stacked in one section of the sub-assembly division and at first look something like shiny railroad rails. Templates with hardened drill dies are clamped to the spars which are quickly drilled for fittings, reinforcement plates, etc. All fittings are riveted to spars by jaw riveting machines in a few minutes. The spars are then placed on the wing racks, ribs are placed into position and riveted on with Chicago squeeze riveters. Ribs are made up well in advance. The curved top cap strips are still formed by hand in a mold. The vertical rib stiffeners are wide channel sections of light Alclad. Nose ribs are simple stampings, several of which have fairleads riveted into them for aileron cable guides. Leading edge is .020 Dural riveted to ribs and spars.

Though the Luscombe wing is a very simple and light structure it has withstood a load of 8G. This is significant when it is considered that most military airplanes are built to take loads of 9G. Aside from being the only light plane with a metal wing structure, the Luscombe also possesses another unique advantage. In most cases of wing damage the tip is usually the most damaged part. With this in mind, Luscombe engineers conceived the idea of splicing to the end of each spar a lighter 3½ foot channel section which would give way quickly in a crash involving wing damage. This idea has saved many owners the expense and time involved in rebuilding an entire wing. Replacing the tip section is a simple operation and can be performed by the average mechanic with ordinary tools in a couple of hours. Another advantage of the metal wing is that spars can be straightened with ease in event of severe damage.

When the wing structure has been completed it is routed into the paint shop where it is treated to a bath of P27 primer before covering. Ready-made wing covers are then sewn on and doping proceeds in the conventional manner. Six coats are used, and all wings are finished with aluminum dope unless a special paint job is ordered. Wings are then routed to special racks in the final assembly division awaiting the airplanes to which they have been assigned.

Meanwhile fuselages are coming through the assembly line in rapid succession, and after tail surfaces are installed, motors are placed in their welded steel tubing mounts.

Luscombe models now in production use Continental 50, 65 and 75 hp. engines, as well as the Lycoming 65 hp. engine. An oval-shaped gas tank with a capacity of 14 gallons is then hung in the rear of the cabin by cables carried through the top rear fuselage skin.

The nose cowling is an Alclad stamping made by Teicher Manufacturing Corporation and finished and fitted within the Luscombe plant. Entire cowling from firewall forward is one unit after riveting together in a special jig. Final fitting is by hand.

Simultaneously with the cowling fitting the control system is installed just after the fuselage is lined with soundproofing material when called for. The control system is a steel tubing structure made within the Luscombe plant. All cables are cut and spliced up in standard lengths well in advance.

Finished fuselages are rolled into the final assembly division where streamlined V wing struts, jig welded within the plant, are fitted and wings installed. Pyralin windshields are riveted together, doors and upholstery are installed and instruments placed into position and connected to their respective engine connections. Landing gear fairing is put on and all special paint jobs, striping, etc., are also done in this stage. The airplane is then completely inspected again, a propeller fitted, and the ship is test flown, licensed and delivered to the customer.

Recent new machinery which has enabled such rapid assembly includes a DeWalt circular saw for steel tubing, all sorts of extrusions, square or round. Two scroll shears enable workmen to cut curved surfaces accurately. A Bliss press with a capacity of 35 tons punches out instrument panels, seat bottoms, etc. Sanders, grinders, portable arc welders, Kempsmith milling machine table, lathes, a Doall metal band saw, numerous Chicago air drills and riveters all help cut down labor time and improve the efficiency of the rapid assembly. By making its own dies Luscombe has further reduced the cost of outside labor.

At such a time when production reaches a much greater rate, there is the possibility of further keeping costs low by installing gang punch presses, riveters and drill presses. The present rate of production is leading towards the installation of such specially manufactured shop equipment, which will maintain low cost in large quantity production.

In order to insure accurate workmanship in every stage of production, and eventual satisfaction to every customer, Luscombe has inaugurated a highly specialized method of inspection. Every rivet is carefully inspected by men who have had considerable experience in this type of construction. Contrary to the common conception, there is no student labor in the Luscombe plant. Luscombe school graduates make up most of the employees as they are especially trained in metal construction for at least one year. A visual control system has been inaugurated for an accurate check on the progress of each plane through the plant.

Lenape "Brave"

(Continued from page 61)

threads, which anchor into the aluminum "Y" alloy cylinder head. The top portion, which protrudes from the cylinder head proper, is ½ in. in diameter with standard S.A.E. threads.

Many features of the valve assembly are worthy of notice, such as a double row of S.K.F. ball bearings in the rocker arms, Thompson siterome valves for both intakes and exhaust, provision for full force feed lubrication of rocker arms and double valve springs, one within the other which makes it possible for the engine to operate in the event of a broken valve spring. A small steel circlet is added for safety to all valve stems. Bronze valve seat inserts of unique design prolong the life of the engine by permitting renewal in the event of wear and valve guides are fabricated from a special bronze alloy. In the event of lubrication failure these guides will give unusual emergency service without undue damage to the valves themselves.

A great factor in the saving of weight on this engine is the use of a magnesium alloy crankcase, which is lighter than aluminum and weighs less than 22 lb., with all studs screwed in place. The case itself is split on the center line of the cylinders and through-bolts used to fasten both halves together. Provision is made in the crankcase design for the oil to preheat the incoming gases from the carburetor, and a special manifold which acts as an external oil sump is connected between the carburetor and crankcase. All the cam mechanisms and cam followers are inclosed in the front half of the crankcase and are insured of adequate lubrication through oil passages. From the maintenance standpoint this is an interesting feature because all wearing parts are replaceable.

The crankshaft is designed with four main bearings from S.A.E. No. 3140 steel forgings. There are two sets of ball bearings on the front half of the crankshaft, one of which is a deep grooved double thrust bearing which takes the thrust from either direction and thus makes it possible to use the motor as a pusher as well as a tractor without any change. The rear half has a ball bearing adjacent to the crank throw, and a plain bearing on the extreme rear which acts as a constant oil feeder as well as a steady bearing for the overhanging shaft which drives the accessories.



Rear view of Lenape "Brave"



Crankshaft and rocker arm

Crankshaft, rod and counterweight assembly

Rear half of crankcase accessory case removed

Phosphor bronze counterweights are so designed that a boss of one goes completely through a hole in the crankshaft cheek and through a hole in the opposite counterweight. This boss absorbs all the loads resulting from centrifugal forces and the bolts used to tie the weights to the crankshaft are not forced to carry this centrifugal stress.

The master rod and the link rods are of tubular construction, machined from solid forgings of S.A.E. # 3140 steel. The master rod has a lead-bronze diamond-bored crankshaft bearing, which is very large, and is free to rotate, thus giving a double bearing surface, one on the interior of the master rod the other on the exterior of the crankshaft throw.

The magnesium alloy accessory drive case bolts to the rear half of the crankcase. A simple bevel gear on the end of the crankshaft drives four other bevel gears. Two of these drive the horizontally mounted magnetos, independently, thus providing true dual ignition. A third bevel gear at the bottom of the case drives the oil pump and the fuel pump of the Romec or Pesco vane type. The fourth bevel gear at the top of the case powers the tachometer and the generator drive and also a fitting for an a.c. fuel pump if such should be desired. The unique lower fuel pump drive from the oil pump shaft incorporates a design which insures positive lubrication for the fuel pump packing gland at all times. The alternate fuel pump drive at the top of the engine is designed with a cam which is part of the vertical shaft of the generator and tachometer drive, which makes provision for the less expensive diaphragm pump of automotive type.

A vibration absorbing mounting ring, constructed of steel and rubber, serves to reduce shock and prevents undue wracking of the airplane structure. Another instance of weight saving is the magnesium alloy propeller hub. The steel hub originally used by Lenape was approximately 50 per cent heavier than the magnesium hub.

Lenape Engine Specifications

Rated horsepower	95
Weight (Dry)	192 lb.
Bore	4¼ in.
Stroke	4 in.
Piston displacement	275 cu. in.
Compression ratio	5.1:1
Rated engine speed (r.p.m.)	2200
Overall diameter	36 in.
Overall length	24 in.
Fuel consumption gal. per hr. cruising	6.48

Don't Give Up the Ship

(*Continued from page 37*)

should come from cross-country flying. A pilot who has served his apprenticeship flying close to the airport under the CPT plan has had sufficient basic instruction to fly cross country. Two pilots who fly together not only add to the pleasure of the trip but can split the cost.

There are undoubtedly all sorts of interesting places in your vicinity to which you can fly. Fishing and hunting spots, air meets, vacation resorts, class mates' homes . . . the list could be extended indefinitely. Private pilots have always enjoyed flying cross country in loose formation. Perhaps you could get two or three ships to make a tour together.

A number of operators have agreed to rent ships, such as Cub Coupes and Luscombes, with two-way radio for $8 per hour, with a minimum guarantee. You could rent a ship Saturday morning, fly to some cross-country point, and return on Sunday. Yet you would pay only for the time you were in the air plus a small additional service charge.

Perhaps you live near a seaplane base, or will be spending part of the summer near a lake or river, or along the shore, where you can get the new thrill of seaplane flying. The seaplane pictures in this issue should appeal to everyone who enjoys being around the water. After you have had a few instruction trips and have been checked out on floats, you will be delighted with flying over the water and with the freedom you can get from being able to put your ship down anywhere on the 'water airports.' You really have something to look forward to if you have never done any seaplane flying.

Piloting, like many other skills, needs to be kept up if efficiency is to be maintained. In aviation circles there is considerable talk of corrosion. It attacks pilots as well as airplanes. With pilots, it gets in its work most easily during vacations from flying when the pilot's techniques and skills become rusty from lack of use. To keep in good flying form, try to get out to the airport every week.

Many students who have had the first 35 hours or more under the Civilian Pilot Training program will return to college in the fall and will want to apply for advanced, second-year instruction. Although CAA has not announced details of the advanced instruction, some off-the-record advice can be given about how to qualify. There are sure to be many more students applying for second-year instruction than can be accepted. It seems logical that CAA will want to accept students who have two qualifications: an excellent record during primary training, and an intention to keep on flying. If you want further CAA training, you can definitely help yourself to qualify by building up some additional flying time this summer. But keep your record clean!

Another advantage to flying this summer, in addition to all those we have mentioned, is that it will help you to get an aviation job after leaving college, if that is what you want. Many of you are attracted to aviation and are wondering how you can make it pay as a vocation. There are many jobs in which the chief requisite is being a skilled pilot. Every private-airplane company in America is looking for top-notch salesmen. There are lots of salesmen, and lots of pilots, but a combination of the two is not easy to find. Many college students have been studying economics, merchandising, advertising and selling in preparation for a business career. If

(*Turn to page 110*)



Find an airport near your home. There are also many other places to rent ships in addition to these 508 CPT operators.

(*Continued from page 107*)

they have the nack of selling, and learn to be safe, steady pilots, they can look forward to a profitable future selling airplanes Airplane selling today is about where automobile selling was in 1915 and the tide is surging upward and is sure to bring profits to smart salesmen

There are also many other aviation jobs where piloting is necessary The oil companies aviation schools fixed base operators, and many companies using airplanes in their business will need an increasing number of skilled pilots each year Airlines are searching for men who meet their standards Both the Army and Navy have attractive offers for college men.

But 35 or 40 hours of flying won't get you a job That is just a beginning. A pilot has to build up considerable more flying time before he can convince a business firm that he is a safe, dependable flyer If you are a sophomore or junior this year and can get in a full summer of flying and continue to fly until you graduate you should have enough flying time to find a job when you graduate.

Follow the Rules

Every college pilot should read Tom Hardin's article in this issue about accident prevention CPT instruction has been excellent and pilots who have built up 35 or 40 hours know the rules for safe flying While you have been under the eye of your instructors your flying has been 1 100 per cent safer than private flying in general That is a remarkable record

But everyone in the aviation industry wonders if you can keep it up. What is going to happen now that you are on your own? Are you going to proceed to break loose and tear things apart just to show that you have come of flying age? We hope not You were chosen for your intelligence as well as for your potential flying skill —and the smart flyer is one who follows the rules Your prestige as a pilot depends on your flying record this summer And remember that if you wash out a plane through your own fault you put a millstone around your instructor's neck Rightly or wrongly, he carries some of your burden—so remember he is keeping an eye on you even though you are many miles away Don't let him down

Bon voyage for a swell summer!

(EDITOR'S NOTE: If you can not find an airport near your home on the map printed on page 107, write us for the name of an operator in your neighborhood.)

Follow the Rules

(*Continued from page 43*)

I realize that it would be physically impossible to make this widespread change immediately, but there is no reason why it should not be accomplished in the near future We have proof that the spin and dangerous stall can be eliminated The spin is an absolutely useless maneuver in civilian flying, and insofar as I am concerned, both the spin and the dangerous stall are unfortunate carryovers from the limited knowledge of yesterday's aeronautical engineers For the present, however, pilots must learn to stay within the safety limitations of currently available aircraft

The common objective today among all interested in private flying should be the improvement of the safety record. The Air Safety Board will cooperate by doing everything in its power toward attaining this objective, and I sincerely hope that through cooperation we can achieve a better record for private flying in the immediate future

Basic Combat Fighter

(*Continued from page 53*)

the leading edge and the hinges are four ball bearing type The removable rudder tip contains a balance weight.

The main landing gear consists of two 27 inch smooth contour tires and 27 inch streamline wheels mounted on cantilever shock absorber struts of the oleo-pneumatic type. The struts are attached to the wing center section on fore and aft trunnion bearings, about which the gear swings inwardly for complete retraction The wheel is connected to the shock absorber piston by means of a single legged fork of aluminum alloy box section construction

The gear, actuated hydraulically by means of a power system or emergency hand pump, is automatically locked in the down position and locked "up" by means of an eyebolt on the axle automatically engaging a spring loaded hook A warning horn blows when the throttle is closed unless the landing gear is extended and locked

The tail unit of the landing gear, which is also retractable, consists of a full swiveling, steerable tail wheel employing a 10 inch smooth contour tire and pneumatic shock strut.

Recent Books

Long distance flying technique

AN OLD CAPTIVITY *by Nevil Shute*, William Morrow & Co., New York, N. Y., $2.50.

For those who like their tales of sub-Arctic expeditions combined with romance, Nevil Shute's "An Old Captivity" makes diverting reading. Shute author of 'Ordeal", demonstrated in that book his practical knowledge of aircraft, and in his new book deals even more painstakingly with aeronautical details. His patient recording of maintenance and of flying technique involved in long-distance flights is realistic, and should prove an eye-opener to that public which still thinks of such flights in terms of adventure, sans skill forethought and manual labor. His new story lacks the impact and excitement of "Ordeal", but it is a good one, with its thread of mysticism neatly balancing the fatigue and nervous tension accompanying an account of an aerial survey. Mr. Shute is an experienced writer and an experienced airman, so that his book will appeal to both the general reader and the aviation reader.

Lessons from the last war

UP AND AT 'EM *by Harold Hartney*, Stackpole Pub. Co., Harrisburg, Pa., $2.50.

The new book is by Harold Hartney, who commanded the First Pursuit Group in France during the first World War. This book has the distinction of being the only one about aviation in the last big war which has been written since the present war began. Col. Hartney points to many lessons learned at great sacrifice during 1914–18 and emphasizes what can be done to prevent mistakes occurring 'the next time". "Up and At 'Em" is an engaging aviation story that will please many readers.

Aviation through the years

THE STORY OF FLYING, *by Archibald Black*. Whittlesey House, McGraw-Hill Book Co., New York. 267 pp., $2.50.

With the coming of age of the aviation industry, the public is finding its history and background an engrossing subject. Latest account is "The Story of Flying" by Archibald Black. A very good account, too, Mr. Black has set down, in a style both interesting and concise. His story concerns not only the early efforts, first flights and record flights, but the equally important record of World War aviation; the post-war boom; air mail; engines and propellers; gliders; rockets and airships; airports, airways and radio; photography, skywriting and mapping; accessories; modern air transport; and a forecast of future developments. All this, encompassed in 267 pages with a very complete index and well illustrated, makes a fine reference work, and should be on the book shelves of the industry at large. It is also something to think about when graduation gifts rear their heads. Archibald Black has been in aviation since 1915, as consulting engineer with the Navy, Curtiss-Wright, and as a free lance. He is the author of "Transport Aviation" and "Civil Airports and Airways".

Aviation Directory

"AVIATION DIRECTORY AND REFERENCE GUIDE," *by Harold E. Boughman*, published by Aero Publishers, Inc., Glendale, Calif. $6.50.

With 598 pages, 7,000 listings, and 170 illustrations, the book represents a complete and accurate compilation of aviation terms and data, cross-indexed for ready reference. Contents include complete aeronautical nomenclature, and a comprehensive directory of aircraft plants, parts, equipment, accessories, repair stations, schools and personnel.

Window Shopping

(Continued from page 66)

The following catalogs or trade literature may be obtained by writing direct to the manufacturers listed.

Air Associates Catalog No. 16—A complete listing of aviation materials and products in 196 pages with more than 1,350 illustrations. Air Associates, Inc., Roosevelt Field, Garden City, N. Y.

Aero-Thread—Bulletin T-1—A 16-pg. bulletin presenting engineering standards and technical information covering the recently developed Aero-Thread system for bolts and studs. Aircraft Screw Products Company, Inc., 2512 41st Avenue, Long Island City, New York, N. Y.

Chambersburg Pneumatic Forging Hammer—Bulletin No. 1275—A 14-pg. presentation of the motor driven Chambersburg forging hammer, a tool primarily suited for forging alloy steels. Chambersburg Engineering Company, Chambersburg, Penna.

A B C of Spray Painting Equipment—A hand book covering the entire field of spray painting equipment. The DeVilbiss Company, Toledo, Ohio.

DoAll Precision Saws—DoAll Precision Film Bands—Folders finding the complete line of saws and film bands for the special DoAll machine. DoAll also offers to engrave writing for at a special steel hole blank suitable for finishing into a high class hunting knife. Continental Machines, Inc., 1201 Washington Avenue, South Minneapolis, Minn.

Ex-Cell-O Tool Tips—Regular publication of the Ex-Cell-O Corp., 1230 Oakmen Blvd., Detroit, Mich.

Gisholt Balancing Machines—A handsome 30 page catalog of Gisholt balancing machines. Gisholt Machine Company, Madison, Wisc.

Johnson Bronze General Catalog—No. 400—The most comprehensive book of the type ever produced. Over 800 sizes of plain bearings and 350 sizes of bronze bars listed. Johnson Bronze Company, New Castle, Penna.

Kennemetal Catalog No. 3—A 32 page guide for the earn end and use of carbide tipped tools. McKenna Metals Company, Latrobe, Pa.

Kollsman Pointers—A periodical publication devoted to information on aircraft instruments. Kollsman Instrument Co., 8000 Forty-Fifth Ave., Elmhurst, N. Y.

New Materials Handling Catalog—A 56 page catalog of floor trucks, jack lifts, skid platforms and other materials handling equipment. Lewis-Shepard Sales Corp., 293 Walnut St., Watertown, Mass.

Sheet Metal Welding Fundamentals—A 16 pg. booklet covering such subjects as design factors, control of expansion and contraction, use of gas welding procedure etc. The Linde Air Products Company, 30 East 42nd St., New York, N. Y.

Metmeltzing—An 8 pg. pamphlet discussing metal spray protection of steel, a process now finding commercial application in aviation. Metallizing Engineering Company, Inc., 21-07 41st Ave., Long Island City, N. Y.

For Better Gears—A 52 pg. booklet devoted to gear machining and gear forming machinery. Michigan Tool Company, 7171 E. McNichols Road, Detroit, Mich.

The Neoprene Notebook—Up-to-the-minute facts about a modern material. The Rubber Chemicals Division of E. I. DuPont De Nemours & Co. (Inc.), Wilmington, Delaware.

Oxy-Acetylene Tips—A monthly publication devoted to gas welding and cutting. The Linde Air Products Company, 30 E. 42nd St., New York, N. Y.

Pyhumin—An 8-pg. pamphlet describing a process for protecting aluminum. Pyroxan Manufacturing Company, 560 Eminent Ave., Newark, N. J.

Simplex Airplane Jacks—Bulletin Aero 40—Pamphlet describes a line of jacks designed especially for jacking up aircraft. Templeton, Kenly & Co., 1020 South Central Ave., Chicago, Ill.

U. S. Hose Hints—A 34-pg. booklet dealing with selection of rubber and cloth hose for industrial use. Mechanical Goods Division, United States Rubber Co., 1790 Broadway, New York, N. Y.

Victor Welding Equipment—Devoted to gas welding accessories and supplies. Victor Equipment, 3821 Santa Fe Ave., Los Angeles, Calif.

Aeronautical Fabrics—A comprehensive paper on this subject prepared by Howard M. Bingham, Wellington Sears Company, Inc., 65 Worth St., New York, N. Y.

Electric heating equipment—Catalog 36 000—A 38 pg. catalog of electric immersion heaters and heating elements. Heating Division, Westinghouse Electric & Manufacturing Company, Mansfield, Ohio.

Ingenious arrangement for recording test data. At regular intervals during test flights, this array of instrument dials and manometer tubes was photographed.

Into the Sub-Stratosphere

(*Continued from page 49*)

tion is NACA 0018 and tip section is NACA 0010.

Front and rear spar chords are 24ST square tubes with tapered wall section. Terminals are steel, heat treated to 150,000 lbs. per square inch. Diagonals and verticals are aluminum alloy square, rectangular and barrel section tubes. Compression ribs and intermediate ribs consist of hat channel section chords tubular diagonals and verticals, and sheet gussets of aluminum alloy. The covering is 24ST Alclad, over 24ST Alclad corrugations. Leading edges are flush riveted.

All fuel tanks are carried in the wings in padded cradles. Between the two nacelle locations of each wing is a 425-gallon main tank and a 212.5-gallon auxiliary tank, while a second 212.5 gallon auxiliary tank is located in each wing between the inboard nacelle and the body. The total tankage is thus 1700 gallons.

Engine nacelles are of semi-monocoque construction, providing a roomy structure for mounting of equipment and access to this equipment. The nacelles have "J" section frames and bulb angle stiffeners, with partial longerons to back up engine mount bolts. The engine mounts proper are of welded steel tubing. The landing gear, which is of the single oleo type, retracts by electrically-driven screw operation into the inboard engine nacelles.

Two different types of wing flaps are used on the Stratoliners. The Model 307's of Pan American Airways have split trailing edge type flaps while the Model 307-B's of Transcontinental & Western Air, Inc., have slotted, trailing edge flaps. In each case, the flaps extend the complete distance from body to ailerons. Leading edge slots near the wing tips have been incorporated for maximum control at the stall.

Other differences between the Model 307 and 307-B, aside from interior furnishings, are concentrated mainly in the power plants. The 307 has Wright GR-1820-G102 Cyclones (1100 horsepower each for take-off and 900 horsepower normal rating), while the 307-B has GR-1820-G105A Cyclones of the same take-off and normal rating but with two speed supercharging for high altitude performance. Propellers are the Hamilton Standard Hydromatic full-feathering type, three-bladed, with a diameter of 11½ feet. Cooling systems vary in the two models, the PAA version having fixed ring cowls while the TWA airplanes are equipped with cowl flaps. The cantilever tail surfaces of the Stratoliner include a single vertical fin which extends forward into a low vane along the back of the body. This forward vane provides exceptional stability for high angles of yaw. The fin and stabilizers are all-metal, and the elevators and rudder are of metal structure with fabric covering. Hydraulic boost controls are used on rudder and elevators, providing ease of control under all conditions of operation. Both elevators and rudder are provided with powerful trim tabs, with which the airplane may be trimmed through a wide range of speeds, and with one or more engines inoperative. The elevators are provided with control tabs which make landings easily possible even without the use of the hydraulic boost control.

Supercharging Equipment

The Stratoliner's cabin supercharging heating and ventilating system is sufficiently interesting to be described in considerable detail. The plane can be operated either with or without cabin supercharging at any altitude. At comparatively low altitudes, below 8,000 feet, there is little advantage to pressure-cabin operation. Moreover, hot weather conditions frequently prevail at low altitudes so that a comparatively large flow of cool air into the cabin is desirable. For these reasons, a separate cold air system is installed in addition to the supercharging system. A blast of fresh air is rammed into a scoop at the top of the nose of the cabin, then passes through a centrifugal rain separator and then into a central duct in the cabin's ceiling where it is distributed through grills. An auxiliary ventilation outlet of large capacity in the bottom of the accessory compartment below deck permits the large quantity of cool ventilation air at low flight levels to sweep through the passenger compartment and to be subsequently discharged to the outside atmosphere. This is adjustable to suit weather conditions.

At 8,000 feet the overhead auxiliary air scoop and the auxiliary outlet are closed, and all ventilation is carried on through the supercharging system, with automatic pressure control and automatic temperature regulation. From 8,000 feet to 14,700 feet, there is no change in the atmospheric pressure within the cabin. The cabin is still at an "apparent altitude" of 8,000 feet when the 14,700 foot level is reached. In operation above 14,700 feet, a differential of 2½ pounds per

(*Turn to page 119*)

(Continued from page 116)

square inch pressure between outside and inside atmosphere is maintained so that the "apparent altitude" in the cabin gradually increases. At an actual altitude of 16,000 feet, the "apparent altitude" in the cabin is approximately 9,0000 feet. At 18,000 the "apparent altitude" is about 10,600 feet and at 20 000 feet, it is approximately 12 300 feet.

The routing of supercharged ventilating air through either one of the two duplicate supercharging systems may be described in general as follows: Fresh air is taken in through an opening in the lower leading edge of the wing between the inboard engine nacelle and the body. It then passes through a centrifugal water separator to the supercharger "blower" unit mounted behind the engine in the inboard nacelle and mechanically driven by the engine. In this "blower" the air is increased in density. It is subsequently warmed by steam radiators and then flows through a duct to the automatic flow control valve in the control unit located in the accessory compartment below deck, which maintains a constant weight flow of air through all ranges of operation. From this point it is routed to ventilation grills at the sides of the cabin at the floor level, and, if desired, to the individual adjustable ventilator outlets. The air, after circulation, escapes through mushroom-shaped outlets in the floor to the accessory compartment below deck where it passes through the automatic pressure control valve and escapes to the outside atmosphere. The pressure control outlet valve and the inflow control valve, mentioned above, are combined into a mechanical unit known as the cabin supercharging control unit. There are two of these units, each serving identical functions for the duplicate supercharging system.

If, for any reason, the air inlets in the leading edge of the wing should become plugged, a secondary inlet valve opens automatically to furnish air for the supercharger blower. This auxiliary valve is inward-opening and is located within the protected landing gear well of the inboard nacelle, in the side of the duct leading to the supercharger. The suction of the blower causes the valve to open and there is no reduction in the cabin air supply rate as a consequence.

The cabin supercharger is a centrifugal compressor having an integral speed-increasing gear box. It is mounted on the rear of the fire wall of the nacelle and is driven by a flexible shaft from the generator drive of the engine. The supercharger impeller shaft is geared at 11 625 times the engine speed. Tests have shown that with only one of the two blowers in operation, the 2½ pounds per square inch internal cabin pressure can be maintained at altitudes considerably above 20,000 feet.

A blower relief or surge valve is located in the duct leading from the blower to the cabin. This opens automatically by means of the pressure built up in the duct in case the flow of air into the cabin is throttled down by the valve in the control unit, thus bypassing the air output from the supercharger and preventing surging or overheating of the blower. During low altitude operation in warm weather, the entire air output of the superchargers may be bypassed through these relief valves to the outside atmosphere by shutting the control unit airflow valve and using ventilation from the auxiliary cold air system. Normally, however, the flow of supercharged air into the cabin is maintained even in non-supercharged operation, in which case the blowers serve merely as ventilation fans.

The air is warmed as it leaves the cabin supercharger by means of a simple steam-heating system located in the engine nacelle. Steam is generated in a boiler consisting of a finned cylinder which extracts heat from the engine exhaust. The steam from this boiler passes into banks of condenser tubes and the cabin air supply is heated as it flows past these tubes. Water for the boiler is contained in a conical-shaped sump located below it and so designed that if any of the water should freeze when the engine is stopped it will immediately thaw upon starting the engines. A feedwater pump, driven by oil from the airplane's hydraulic system, circulates the water from the sump to the boiler. Heat output is regulated by the speed of this feedwater pump, which is automatically controlled by a thermostat located in the central part of the airplane cabin. The setting on the thermostat can be varied at will by the airplane hostess or steward.

Distributing the Air

After the supercharged air supply passes through the flow control valves in the accessory compartment below deck, it continues to a set of distribution valves, where it is directed into one of several alternate flow courses which may be selected according to weather conditions. During hot weather, it is preferable to divert the air into the auxiliary ventilation duct in the cabin ceiling, whence it is distributed through the overhead grills and individual ventilators for the most cooling effect. The second optional flow course consists of a series of ventilation grills in the side of the cabin near the floor, providing superior hot air ventilation during cold weather. It is also possible to direct part of the air into the overhead system and part into the floor duct system. The choice between these various alternatives is made by the hostess or steward who operates selector valve controls located in the forward end of the cabin. The major portion of the pressure air may also be diverted into nozzles extending along the lower edge of the pilots' compartment windshield for windshield defrosting.

The supercharging control unit located in the accessory compartment is a compact apparatus, representing many months of development work, which automatically regulates the atmospheric pressure level in the cabin. It contains both the air inflow valves and the spent air discharge valves. The pipe through which the spent air is discharged to the outside atmosphere passes directly through the duct for incoming warm air, which prevents frosting of the air outlet. The cabin-pressure regulation is accomplished by variations in the degree of opening in the outlet valve, which is governed by pressure-sensitive mechanisms that are responsive to absolute pressure and to differential pressure.

The cabin supercharging, heating, ventilating and pressure-regulating apparatus has been described in the singular for the sake of simplicity. All units of the system, including superchargers, steam-heating apparatus, automatic control unit, etc., are installed in duplicate in identical form and the system may be operated by either or both sets of apparatus.

Operation of the System

The operation of the supercharging system is vested in the Flight Engineer, although he has little to do in this connection other than to turn controls on or off, and observe the pressure instruments mounted on his instrument board in the rear right portion of the control room. He has three master levers. Two of them control the right and left supercharged air inlet valves, respectively. These two levers are normally left in one position, which provides automatic regulation of the supercharged air inflow by the automatic control unit. In the opposite position, the levers cut off the supercharged air inflow, and in intermediate position, they provide

(Turn to page 120)

(*Continued from page 119*)

manual regulation of the air inflow. The third master lever has three positions. One is for unsupercharged, cold air ventilation (auxiliary cold air intake valve open and auxiliary outlet valve open), the second is for unsupercharged, warm air ventilation (cold air intake valve closed and auxiliary valve open), the third position is for supercharged operation (cold air valve closed and auxiliary outlet valve closed and supercharging under automatic control).

The Flight Engineer's instrument board has a compact group of pressure-cabin instruments, in a central location separated from surrounding instruments by a green border. Within the border are the following instruments: An indicator showing rate of pressure change within the cabin, a "cabin altimeter" showing the pressure altitude within the cabin instead of the airplane altitude, a supercharger discharge pressure gauge with a 2-way selector switch for connecting it to right or left supercharger, a suction gauge with a 3-way selector switch to show cabin pressure as referred to outside pressure or to show flow pressure in the right or left air supply ducts. At the top of the panel is an outlet valve selector switch with 3 positions. With this switch in vertical position, the cabin supercharging is controlled by both of the automatic valve control units, in the left hand position, the system operates through the left outlet control valve only, and in the right position, the right outlet unit only.

Ease of Maintenance

A feature of the Stratoliner is the accessibility of controls and equipment, and the ease of maintenance. All accessories such as batteries, control boxes, compressors, autosyn dynamotors, propeller de-icer fluid pumps and tanks, etc., are installed in the accessory compartment bewteen spars in the bottom of the fuselage. All of this equipment, as well as the supercharging control equipment, is readily accessible for servicing from an outside door, and the compartment is also accessible during flight. Control cables and lines under the control room floor are accessible by way of a door in the forward cargo compartment, which can also be reached during flight. A round door in the nose of the plane permits access to the back side of the main instrument panels. Accessibility to all control lines etc., beneath the floor of the passenger cabin is provided through the lower cargo hatches. The tail cone of the airplane is readily removable for access to the tail section which can also be reached from within through the hatch in the rear pressure bulkhead.

The semi-monocoque engine nacelles make power plant equipment readily accessible. All engine mounts and power plants complete with all equipment except for exhaust collector rings, generators and hydraulic pumps, are interchangeable within each airplane and may be installed on any nacelle of any other Stratoliner. The engine mounts are quickly detachable.

Landing gear and tail gear retracting mechanisms and wing flaps are operated in the Stratoliner by individual directly-connected electric drives, which insure positive control of the units through all positions. Individual hand cranks are also provided for emergency operation. Wheel brakes, fuel dump valves propeller-feathering, power boost controls, and various other items are operated by the airplane's hydraulic system. There are three sources of hydraulic pressure: two engine-driven hydraulic pumps—either of which is adequate to perform the function—and an electrically driven emergency pump mounted in the accessory compartment and controlled remotely from the cabin.

The interior of the Stratoliner was laid out to take full advantage of the size of the plane. The main passenger cabin is divided on the right side into four travel compartments separated by wood-panelled partitions, while along the left side there are nine individual reclining chairs. Each of the four compartments has deep-cushioned davenport-type seats for six passengers which make up into upper and lower berths for four passengers, with berths running transversely in the cabin. Thus, the plane will carry 33 day passengers or 25 night passengers including the nine reclining chairs.

Control Cabin

The Stratoliner control cabin was designed with special attention to convenience of arrangement and simplicity of operating procedures. Pilot's and Co-pilot's instruments are arranged in a series of compact groups to facilitate reading. Power plant controls and miscellaneous other controls are grouped in a systematic arrangement on a centrally-located stand between the two pilots. Behind the Co-pilot's station on the right side of the room is the Flight Engineer's station, with desk and instrument panel. The Flight Engineer's chair is mounted on a special, movable base which may be swung around into a position immediately behind the main control stand between the two pilots. These three flight officers, plus two cabin attendants, comprise the crew of the TWA Stratoliner. The Pan American version provides for two additional flight crew members—a radio operator, whose position is immediately behind the pilot in the left rear corner of the control cabin, and a navigation officer, for whom a special navigation compartment has been provided just aft of the main control room.

Performance figures for the Model 307 and the Model 307-B Stratoliner vary somewhat, due to the difference in power plants. Following are some approximate performance figures for the 307-B. Maximum speed at 17,300 feet is 246 miles per hour, and cruising speed at 15,500 feet is 222 miles per hour. Takeoff distance at sea level in still air with maximum gross weight (45,000 lbs.) is 930 feet. Service ceiling at maximum gross weight with 4 engines is 26,200 feet; with two engines, 21,300 feet. With two engines, 6800 feet. The maximum range at 50% power is 2390 miles.

Financial Trends

(*Continued from page 51*)

company may also obtain a higher rate of mail pay, although not as favorable as originally anticipated.

Transcontinental & Western Air should, according to its estimates, fly about 147,785,000 revenue passenger miles for 1940, an increase of over 47% over 1939. This would increase passenger income to over $7,500,000 or an increase of about $2,300,000 over 1939. TWA will gain a competitive advantage over the other transcontinental lines this summer when it places its four-motored Boeing's in operation. Delivery of the first of these 5 ships is expected within the next few months.

Eastern Air Lines with a net profit of $386,486 for the first two months of this year and with record passenger traffic for March, bids fair to surpass by a wide margin its profit of $294,120 for the first quarter of 1939. Eastern, however, has no real competition and can not but help reap the bonanza of traffic it is experiencing.

Pennsylvania Central Airlines, benefitting from new DC 3 equipment installed, estimates an increase of 30% in revenue passenger miles this year. This would place its passenger rev-

(*Turn to page 124*)

SEALED WITH YOUR FINGERS AT A TON PRESSURE!*

After you inflate each tire, the Tire Valve Cap should always be firmly applied with your fingers. The final twist you give a Schrader Valve Cap, sets up a pressure equivalent to 2,000 lbs. per square inch at the contact area between the cap washer and the valve mouth.

This pressure not only seals the valve, but it anchors the cap securely in place. No amount of vibration can loosen it and allow it to work off.

Schrader Valve Caps are a safe-guard against your ever having a tire valve "slow leak". Dirt and muck cannot get in to harm the valve mechanism and air cannot get out.

For complete safety for take-offs and landings see that an air-tight cap is firmly applied to every tire valve.

1. *Valve Cap body or shell.*
2. *Brass Swivel Plate of loose Cap Shell to turn independently of rubber washer on Cap is applied. This assures proper seating of washer and prevents distortion.*
3. *Brass Dome Shaped Plate provides an INDESTRUCTIBLE chamber for safe clearance of valve core pin.*
4. *Molded Rubber Washer seals valve mouth when Cap is screwed on firmly by hand, while rubber between brass plates 2 and 3 provides spring action to MAINTAIN positive seal.*

All standard Schrader Valve Caps stocked by Tire Branches, Jobbers and Dealers, contain washers with the unique construction illustrated above and are guaranteed air tight up to 250 lbs. pressure.

Schrader

TIRE VALVE CAPS

*When a SCHRADER Valve Cap is tightened with full finger strength, a downward force of about 50 pounds is exerted against the top of the valve mouth. The actual effective contact surface between cap washer and valve mouth is about 1/40 of a square inch. By multiplying the 50 pounds by 40 we get the equivalent per square-inch pressure, which is 2,000 pounds.

A. SCHRADER'S SON — **BROOKLYN, N. Y.**

Division of Scovill Manufacturing Company, Incorporated

PISTONS for Aircraft

Top-quality alloys, precise heat-treating, and accurate machining, together with our thorough understanding of aircraft requirements, enable us to produce for you either castings or finished pistons exactly suited to your needs.

RAY DAY PISTON CORPORATION

All types of Aluminum Alloy Castings of Aircraft Quality made to Government specifications.

West Warren at Walton • Detroit, Michigan

If it's Ray Day it's Grade A

McGRAW-HILL

DIRECT MAIL LISTS

As business paper publishers for over fifty years, McGraw-Hill is uniquely equipped to offer complete authoritative direct mail coverage of industry's major markets. Extreme accuracy is maintained (guaranteed to 98%) and through careful analysis of markets, complete classification of companies and personnel aim the widest possible selections are available. Send for handy reference folder "Hundreds of Thousands of Reasons Why" which describes how McGraw-Hill Lists are built and maintained.

• What Fields Do You Want to Reach? •

Aviation
Bus & Electric Railways
Civil Engineering and Construction
Coal Mining
Electrical Construction
Electrical Industry
Food Industries
Metal Mining
Metal Working Industries
Process Industries
Textile Industries
Administrative Executives
Electrical Dealers & Wholesalers
Mill Supply Houses
Power Services
Product Engineering & Design
Production and Maintenance
Radio Dealers & Wholesalers
Radio Engineering & Design

For further details, selections from above basic classifications, counts, prices, etc., or estimates on special lists ... ask any representative or write to

DIRECT MAIL DIVISION ...
McGRAW-HILL PUBLISHING CO.
330 W. 42nd STREET — NEW YORK, N. Y.

Complete lists covering industry's major markets

TRADE MARK

NOC-OUT

THE HOSE CLAMP WITH THE THUMB SCREW

The Noc-Out contribution to an outstanding achievement by our commercial airlines—1 year of passenger traffic without a single fatality—is the safer hose clamp that provides a perfect all around seal with a wide margin of strength for safety.

Because aircraft equipment is proof-tested and specified for the extra safety factor, Noc-Outs have been a U.S. Government Specification for many years and are the standard hose clamp of commercial airlines and the aircraft industry. There are Noc-Out Hose Clamps for all types of hose connections ... ask your jobber.

NOC-OUT Stainless Steel

Type "F.B." is a solid band stainless steel clamp, welded for greater strength, especially designed for aircraft. Type "GT" made in stainless steel and in Cadmium plated Cold Rolled Steel. Type "A" Adjustable will fit many hose sizes. Type "B" general utility band clamp.

Write for Catalog Sheets

TYPE "A"
TYPE "F.B."
TYPE "GT"
TYPE "B"

WITTEK MFG. CO. 4305 W. 24TH Pl., CHICAGO

If your Life depended on SOCKETS

... you'd check on the *steel* in those sockets ... on the way they were broached, shaped, hardened. Lives *do* depend on sockets ... on the way nuts are turned, tightened and adjusted. So for *safety's* sake, for the greater service speed, skill and earning power good sockets can bring you ... make sure *your* sockets are the best you can buy.

Snap-on sockets are famed for fine steel ... electric furnace toughened for the greatest tensile strength without brittleness, hardened *all the way through*, hot broached for clean-edged, non-slip grip, precision machined for fit and finish.

Snap-on *originated* sockets ... today makes a wide range of styles and sizes for aviation needs. See your Snap-on Salesman, or write

SNAP-ON TOOLS CORPORATION
Dept. Av 5
Kenosha, Wisconsin

Snap-on
Finer Tools for Flying Service

B★A★30

B★A★30 airplane wing cloth, famous for its uniformity, is lighter, stronger and more closely woven than other airfoil fabrics. Inquiries from dealers and manufacturers will receive prompt attention.

WELLINGTON SEARS COMPANY 65 Worth St., New York City

U. S. Distributors
AIR SUPPLY CO.
5959 W. 3rd St., Los Angeles, Calif.

BREDOUW AEROMOTIVE CORP.
Municipal Airport, Kansas City, Missouri

Canadian Distributors
FLEET AIRCRAFT, LTD.
Fort Erie, Ontario, Canada

$1 DOWN buys this New *Sensational* 4 in 1 WRIST WATCH

1. Accurate TIME PIECE
2. Distance TELEMETER
3. Split-Second STOP WATCH
4. M.P.H. TACHOMETER

Just the thing for AVIATION

Here's the most MODERN wrist watch in the world—and it's yours for only $3.00 a month! ONE DOLLAR down buys it—think of the practical advantages and convenience of having—on your own wrist FOUR WATCHES IN ONE!

SIMPLE TO OPERATE

The smart, compact MONROE 4 in 1 Wrist Watch has TWO tiny levers to control ALL extra features. Each dial is accurate and clear—readable at a glance! With your Watch you get complete instructions in the many uses of the 4 in 1. It tells time of day like any other high grade wrist watch. Press lever and it's a precision STOP WATCH with "TIME-OUT" feature. Press lever and it's a TACHOMETER to tell miles per hour. Press lever again and it's a TELEMETER to tell distance from source of light and sound!

ONE YEAR Written Guarantee

This protects you against any mechanical defect. It's proof the makers of your MONROE Watch stand back of their product. In addition, you get your money back guaranteed if not satisfied, return the Watch in 10 days and your money will be refunded.

10-Day Trial Offer!

Fill out and mail this part at once. Pay only $1.00 down on delivery of your MONROE Wrist Watch.

Only $1 ON DELIVERY — Send NO Money

LOWEST CASH PRICE— NO INTEREST OR CARRYING CHARGES

UNEEDA
375 LIVINGSTON ST., BROOKLYN, N. Y.

UNEEDA Dept. A5
375 Livingston St., Brooklyn, N. Y.
Send MONROE 4 in 1 Wrist Watch at $21.95. I will pay $1 on delivery and $3 a month.

Name ____ Age ____
Address ____
City ____ State ____
Employed by ____ How Long? ____
Address ____

(Continued from page 120)

enues in excess of $1,800,000 for 1940 compared with $1 270,000 last year

Northwest Airlines, with an estimated 50% increase in revenue passenger miles this year, may bring its 1940 passenger income to $2,000,000 compared with $1,324,728 for 1939 Northwest is also hopeful that it may be successful in establishing a fourth transcontinental system by extending its present route to New York via Toronto or Windsor

Favorable earnings by the industry may bring in its wake a number of offsetting factors Increased operating costs along with higher rentals for use of airport facilities may be experienced The airlines may further be faced with the burden of assuming a greater share of the costs of maintaining weather aid facilities now borne by the Federal Government

The air transport industry has definitely come into its own, but by relative standards it is still picayune Any number of individual companies in other industries dwarf the entire air transport industry from the standpoint of total assets, gross revenues and earnings. For example, Inland Steel Company last reported total assets in excess of $166 800 000 and for 1939 had net sales of more than $115,000,000 with net earnings of almost $11,000,000

The present prosperity experienced by the air lines afforded an opportune time for public financing of a number of companies whose securities had heretofore been privately held In recent months the public was permitted to share in the ownership of Northwest, Mid Continent and Braniff All three issues, in investment parlance, "went out of the window", and quickly sold at a premium over their offering prices It is noteworthy that all of the Northwest offering, (100,040 shares at $14 per share) and one third (50,000 shares at $10 per share) of the Braniff sale, represented distribution by the original ownership interests, who were thus able to realize on their pioneering in the industry

Continental Air Lines, less bold, issued 3,636 shares at $27.50 per share to company officials and employees for a total of $99,990 As proceeds were less than $100,000 and no public sale intended, the company avoided the filing of a registration statement with the SEC

Gradually disappearing are the companies whose ownership will continue to be privately held With Boston Maine Airways owned by the Boston Maine Railway and Marquette Airlines, subject to CAA approval, to be absorbed by TWA, only two of the smaller domestic companies remain under closely controlled ownership

Several new companies, however, have been organized in the past year and have filed application for routes Included in this group are Dixie Airlines Missouri Central Airlines, Trans Southern Airlines and Kansas City Southern Transport, Inc The last named Company is a subsidiary of Kansas City Southern Railway

With over $600 000,000 in purchases of aircraft, metals machinery and chemicals, placed by England and France since the start of the war, that widely heralded one billion dollar order for additional aircraft was finally reported on its way after "clarification of details"

The Allies had been reported as insisting on ships of the latest and most advanced types Inasmuch as deliveries could not be made before early 1941, previous models ordered it was felt, would be obsolete by the time they were placed in service

Furthermore, Congressional fear was expressed that the American national defense programs may be retarded by foreign demand

After certain committee hearings and issuance of authoritative statements, the murky atmosphere surrounding the Administration's policy on aircraft exports was cleared It was indicated that sales to the Allies of late models would be permitted so long as they did not incorporate secret devices. Moreover, the Army was reported as willing to release certain of its orders, now in production, to the Allies This would expedite deliveries to the Allies and give our government the benefit of advanced aircraft developments in addition to improving and increasing our productive facilities

Following considerable negotiations, the Anglo-French Purchasing Mission agreed "without reservation or complaint" to this government's conditions for the release of the latest types of craft It is reliably believed that among other things, the Allies consented to defray certain engineering expenditures that may be made in the future by the companies involved in the production of more advanced types of aircraft for the United States

The list of advanced types of aircraft released for export thus far is a very good indication where the orders will ultimately be placed Late models produced by Martin, Douglas, Curtiss, Lockheed and Bell have been made available and presumably will be ordered in quantities by the Allies

When awarded, this billion dollar order may not be the last from the Allies A member of the Anglo-French purchasing Board stated that the rate of expenditure can be expected to rise with the continuation of the war, which will be 'long and hard"

It is important to point out that the total of $600,000,000 war supplies purchased during the first seven months of the war does not include contracts for aircraft and other materials placed by the French and British last summer

Enjoying the benefits of its increased productive facilities, the industry should be in a position to handle a substantial increase in orders An output level of $50 000 000 a month is reported as having been reached by April against the $30 000,000 average which prevailed during the first two months of this year A substantial amount of subcontracting has been done by the industry which should further increase its capacity

The realization that big airplane orders were almost in hand finally perked up the aircraft stocks in recent market sessions These securities however, continue to sell at a relative low earnings ratio This of course, is recognition of the fact that the industry's prosperity may be short lived

It is also becoming increasingly apparent that the domestic services are determined not to pay any substantial profits to the aircraft builders The 12% profit limitation on all sales to the Army and Navy is one check in this direction Almost unnoticed however, was the recent allotment of $30,000 made by the War Department to the National Academy of Sciences to conduct a thoroughgoing study of aircraft production in the United States Among other things, this study proposes to ". . . . determine existing factors which affect increased output of airplanes, engines, and accessories and the unit cost of same for the air forces of the United States Government." This study may provide the Army with facts to reduce the costs of its planes

The Glenn L. Martin Company recorded the largest profit in its history when results for 1939 showed net earnings of $4,110 605 of $3.75 per share on 1,094,532 shares outstanding Although the company has been rapidly exhausting the $49,241,516 backlog reported as of January 1, 1940, little difficulty is anticipated in maintaining capacity operations throughout the year With sales for the first half estimated at about $20 000,000, net profit for this period may equal earn-

(Turn to page 126)

(*Continued from page 124*)

ings reported for all of 1939 Martin is believed to be one of the major beneficiaries of that $1,000,000,000 Allied order Moreover, after completing an extensive expansion program, Martin holds out the possibility that still further expansion may be required This time however, the inference is advanced that such added facilities will be paid for by someone else other than the company

Boeing Airplane Company was awarded a War Department contract for $8,000,000 worth of Flying Fortresses, believed to total about 50 ships. Backlog on April 1, was estimated at about $20,000,000. The company may also augment its operations by obtaining subcontracting work from Douglas to the extent of $15,000,000 to $20,000,000 of the new Allied military purchases. Decided reorganization changes have taken place at Boeing since the return of Phil Johnson to the presidency of that company A substantial loss, $3,284,074, was reported for 1939. The bulk of this loss was attributed to heavy development costs occasioned in the manufacture of 4 engine clippers and "stratoliners" With its balance sheet cleared of huge deferred charges, Boeing is now in a position to record its first profit since 1937

Carrying 25% of its sales through to net, North American Aviation showed the best profit margin among the major builders during 1939 The Company earned $7,088,092 or $2.06 a share in 1939, compared to only $1,904,086 or $0.55 a share for 1938. With a backlog of about $50,000,000 along with a favorable outlook for additional business, and possessing one of the industry's highest productive capacities, North American may again establish a new high in both sales and earnings when results for 1940 are recorded

Aviation Corporation was one of the few companies in the industry to have operated at a loss last year For the fiscal year ended November 30, 1939, the company showed a net deficit of $2,238,049 after all write-offs Aviation Corporation in its present form represents a different company than it was a number of years ago. Its principal manufacturing subsidiary, Aviation Manufacturing Corporation has greatly simplified its operations and recently completed a new plant in Nashville, Tennessee. Vultee, albeit still controlled, is no longer a wholly-owned subsidiary. Aviation Corporation has maintained its investment in $2,422,112 50 of American Airlines convertible debentures and also owns 183 478 shares of Pan American Airways. Both of these investments aside from representing a substantial unrealized profit to Aviation Corporation gives the company control of about 9.5% of the capital stock of Pan American Airways and a potential ownership of 35% of American Airlines capital stock to be outstanding

Control of Aviation Corporation reposes in Aviation & Transportation Corporation which owns 1,129,428 or 28.9% of the former's capital stock outstanding Recently, new interests entered the picture, when General American Transportation Corporation acquired 160,895 shares or 7.2% of Aviation & Transportation's common stock General American also owns 84% of the common stock of Berkley Grow Aircraft It is believed that General American Transportation, primarily a railroad car builder and lessor, is entering the aviation industry so that it may supplement its basic function and be represented in all phases of transportation

Evidently Howard Hughes means to own an airline. In addition to the consistent market purchases of TWA stock, the Hughes Tool Company, controlled by Howard Hughes, has agreed to purchase 119,154 shares of unissued stock of the airline at $14 per share Together with previous purchases, this would give Hughes an interest in 290,454 shares or 30 6% of the total of 950,000 shares of TWA to be outstanding The first Hughes purchase of about 100,000 shares was made a year ago at approximately $10 per share. The bulk of subsequent acquisitions were made at only slightly higher levels

The financial listings of the individual companies are on page 84

Fairchild Trainer

(*Continued from page 54*)

pared by its manufacturer so that a single piece covers the whole top of a wing panel and extends around the leading edge back to the bottom of the front spar This means that there are no joints or seams in the covering in the main part of the upper wing surface.

The tail surfaces are cantilever with fixed surfaces being mahogany plywood-covered units treated in a similar manner to the wings, built up from spruce spars and ribs Movable surfaces are a composite steel and aluminum alloy structure, fabric-covered and are dynamically balanced Cockpit-controlled tabs for longitudinal balance are provided in the elevators. All controls, bellcranks, etc are mounted on ball bearings, and elevators are interchangeable right and left for easier replacement of spares.

The landing gear is of the cantilever type, having vertical motion of 8 inches equipped with 6 50" x 10" low pressure tires, having a tread of 9 feet 4 inches. The tailwheel is steerable through full range of rudder travel and automatically disconnects to become full swiveling for spot turns and hangar handling Hydraulic brakes of the expander tube type are provided and also a parking brake controllable from both cockpits is supplied

Two tanks of 22½ gallons capacity each designed with expansion space are provided, one in each wing, giving the ship four hours' range The fuel system is of the pump feed type, and an auxiliary wobble pump is provided which can be operated from either cockpit.

A Ranger 6-440 C-2 engine is used. It develops 175 hp. and can be run on 65 octane fuel Engine is of conventional Ranger design being 6-cylinder air-cooled inverted inline type, The metal propeller is standard equipment of the McCauley steel type having detachable and adjustable blades and a diameter of 7 feet 2 inches. A direct drive hand turning Eclipse starter is provided with the handle located on the left hand side of the ship just forward of the wing

Open cockpit arrangement is standard equipment with a suitable brace to protect the crew in the event of a turn-over Cockpit enclosures are provided as extra equipment These are of the sliding type, covered with Plexiglas and fully enclosing both cockpits. Each cockpit is equipped with a shock mounted panel offering space for 8 instruments. All instruments are recessed in a rubber crash pad, and fuel gauges are located one in each wing, visible from either cockpit.

Performance Based on 175 hp. (65 octane fuel)

High Speed at sea level	135 mph.	216 kph
Operating speed at sea level (75% power)	120 mph.	192 kph
Cruising range	4 hours	
Service ceiling	16,000 feet	4880 m
Rate of climb sea level	835 ft /min.	250 mpm
Landing speed sea level	48 mph.	77 kph

Specifications

Gross weight	2450 lb	1110 kg
Weight empty	1749 lb	790 kg
Useful load	701 lb	320 kg
Overall span	35' 11⅞"	11 m
Overall length	27' 8⅝"	8.5 m
Height	93"	2.3 m

AVIATION'S MARKET PLACE

CLASSIFIED ADVERTISING

USED PLANES, ENGINES AND PARTS FOR SALE, TRADE OR WANTED
SPECIAL SERVICES OF DISTRIBUTORS, FIXED BASE OPERATORS, ETC.
(Sales and Service—Storage—Repairing—Charter—Aerial Towing or Exhibitions—Special Instruction)

EMPLOYMENT—SELLING—BUSINESS OPPORTUNITIES OFFERED OR WANTED

Address AVIATION Classified, 330 W. 42nd St., New York, N. Y. Phone MEdallion 3-0700—Ext. 556

RATES: UNDISPLAYED, 10 cents a word, minimum $2.00 DISPLAYED $6.00 per inch. Contract rates on request.

USED PLANES FOR SALE

Grouped by Make

For additional planes offered in other ads see Index. Ads appearing in group form are keyed to indicate that they also cover
P — Parts, T — Trades, W — Wanted

Aeronca

AERONCA CHIEF, Cont. 50 HP. Blue and Yellow, 2 doors, pants, brakes, tail wheel, navigation light, battery, compass and other extras, just relicensed, very few hours from factory. Cost $2,290. Will sacrifice. Thomas E. Saliba, Marianna, Florida.

AERONCA K—1937—two doors, fabric. Airplane can hardly be told from new. Total time 283 hours. Gartee Lee Breckenridge, 100 Dibble St., Rochester, N. Y.

AERONCA CHIEF 65 Continental, few hours, extras, dual ignition, tail wheel, brakes, wheel pants, door lock, Pioneer compass, radio, special paint. Cost $2100. Sell $1595. Jim Gillespie, Robertson, Mo.

Bird

BIRD 3 Place. Have on hand 2 sets of upper wings, perfect teelage, leading peer, lower wings, 2 sets of tail surfaces. Kinner K5 just majored by approved station. Make a reasonable offer. Lew Dalte, Hangar 33, Roosevelt Field, New York.

BIRD Airplane parts, wings, Kinner, mount, airwheels. Trade on car, light ship. —Lee Jacobson, 315—12th St., West New York, New Jersey. (T)

Cessna

CESSNA 1936 Eagles just majored, total time 900 hours. Special instruments, sensitive altimeter, rate of climb, turn and bank. Price $3000. Standard Aerial Surveys Inc., 54 Park Place, Newark, N J.

C 38 CESSNA. Perfect condition. $450 extra instruments. $600 two way radio. Complete factory check August. Write for details. Russell P. Hay, 121 Meyran Avenue, Pittsburgh, Pennsylvania.

Cub

CUB E2. Just out of the shop, perfect condition. Everything in it completely majored. Two hours since relicensed. A good buy for someone to build time up without spending any money for repairs, best offer gets it. Lew Dalte, Hangar 33, Roosevelt Field, New York.

38 CUB J 3 Cont. 40—total 150 hours—Perfect condition—tail wheel—spcl. Paint. $725. Dr. P. Kenesky, 1608—A 5 Ave., Moline, Ill.

INDEX

AVIATION "Classified"—May, 1940

Undisplayed ads offering only ONE make of plane are grouped under that make. Others appear under "USED PLANES—General" and are numbered and indexed to enable readers to conveniently locate the make of planes offered, or other items of interest. All other undisplayed and displayed ads—excepting those relating to employment and business opportunities—are numbered or referred to by number and indexed for the reader's convenience in quickly finding ads.

Curtiss Thrush

CURTISS THRUSH 6 place Wright J6 7 E 250 HP. license to May 1941. $1200 will take Cub 50 as part Payment. FS 572, Aviation, 330 West 42nd St., New York, N. Y.

Fairchild

FAIRCHILD 24, Late 37. Warner de luxe, perfect condition. 125 hours total time. Engine just overhauled. Two way radio, generator, blind flying instruments, head $3,950. "2425" Edo floats $600. Western Electric 19 A transmitter $175. William C. Huet, R.D. Box 103, Port Washington, L. I., N. Y. Telephone 2231.

Rearwin

REARWIN 90 1938 brakes, carb. heater, compass, 200 hours, privately owned, always hangared. First $1575.00 takes it. Roy Potter, Wisconsin Rapids, Wisc.

Sikorsky

S 39 C SIKORSKY 400 Pratt & Whitney Junior installed Pratt & Whitney factory September 1938. Total time 342 hours. Ship majored September 1938 by Aero Trades. One spare P. & W. Junior. Electric tachometer, electric gas gauges, bank and turn, rate of climb, one straightaway and one ball compass. Ship's general condition excellent. $7,000.00. Henry J. Topping, Jr., 598 Madison Avenue, New York.

Stinson

1936 STINSON SR8-E Wright 320, two way radio, gyro. Complete set of instruments, etc. 750 hrs. total time, never cracked, privately owned, excellent condition. Asking price $6500, make any offer. Box 237, Leominster, Mass.

Viking

VIKING Flying Boat, 4 Pass. Hull just recovered, complete new bottom. Red Upholstering. New paint job and motor overhauled. Edna Bartlebaugh, McLain, Miss. Gen. Del.

Waco

1937 WACO STANDARD 225 Jacobs, complete with flares, lights, radio, turn and bank, rate of climb. Privately owned, never cracked. Price $3,000. J. M. Bennett, Box 1872, Houston, Texas.

WACO CABIN 1937 Model ZGC powered with Jacobs L 5 Engine. Color Gunmetal. Airplane and engine time approximately 200 hours. Starter, generator, radio receiver, chair type chutes and fully equipped for instrument flying. An excellent opportunity for anyone desiring an exceptionally good airplane to secure it at an attractive price. For further particulars write to Eclipse Aviation Division of Bendix Aviation Corporation, Bendix, N. J.

AVIATION'S MARKET PLACE

Used Planes—General

(See Index on page opposite)
(See also Group Classifications)

Cub Coupes 1939 (new) complete $350 off list price 1938—$1295 1940—complete with muffler etc $200 saving Six 50 HP Cub Trainers 1940 models $895–$995 Kinner New Standard—$695 Other bargains. Financiable Free flying instruction. Bennett Air Service, Hightstown (Cubtown), N. J. No. 1

CIRRUS, Mark III parts. One Wright Gypsy Travelair, Two 2 T1A Great Lakes One Brearwin LeBlond seventy Great Lakes parts Engine overhauls a specialty Cub Sales and Service Racine Flying Service, Inc., Racine Airport, Racine, Wisconsin (P) No. 2

Engines & Parts

See also ads marked (P) in group Classifications

TWO Disassembled Lycoming Engines $350.00 each Warner Engine parts cheap One Operadio Public address system with three speakers, $75.00 Parrish Flying Service, Box 624, Georgetown S. C. No. 3

AMERICAN CIRRUS and Wright Gypsy Parts! Complete Stock of Brand New Cirrus and Gypsy Parts at 50% Discount Write Menasco Manufacturing Company 6917 McKinley Avenue, Los Angeles, California No. 4

Equipment & Products

Aircraft Batteries

AIRCRAFT BATTERY SETS includes new Exide or Willard 6 volt battery and battery box complete $7.00. Battery only $4.50 approved. Send for catalog Aeronautical Trading Co. Floyd Bennett Airport, Brooklyn, N. Y. No. 5

Floats

Floats Edo model 3830 For sale $500.00. Chatham Hunter, Shrine Building, Memphis Tennessee. No. 6

Office Equipment

Typewriter $9.00 Oneliciter $24.95 Adder $37.00 Addresser $19.00. Pruitt 31 Pruitt Bldg. Chicago, Ill. No. 7

Parachutes

Parachutes bought, sold, serviced and rented. New York Distributor for Irvin Air Chute Joe Crane, Roosevelt Field, Mineola, L. I., N. Y. No. 8

Skis

SKIS for Cub Craft Aeronca, Luscombe, all models approved complete, low prices Air Transport Equipment Inc., Garden City, N. Y. No. 9

Services & Instruction

Books

INSTRUMENT RATING—Latest Text covering instrument rating examinations, including Radio Telephone Operator's Permit. $4.00 postpaid or C.O.D. Quiz System, Dept F, 1435 Flower St., Glendale Calif. No. 10

PILOTS EXAMINATIONS fully covered (private and commercial) in 1940 revised "Aeronautical Training" Important new questions with answers. Complete text on Navigation Meteorology C.A.R., Aircraft and Engines $2.00 postpaid or C.O.D. Quiz System, Dept A, 1435 Flower St., Glendale, Calif. No. 11

FLIGHT INSTRUCTOR RATING a quiz text prepares the pilot for Instructor Rating examination Authentic questions with answers $2.00 postpaid or C.O.D. Quiz System Dept. A, 1435 Flower St., Glendale Calif. No. 12

RADIO TELEPHONE OPERATOR Permit a new quiz text covering examination under new regulations Required by Instrument Flyers $2.00 postpaid or C.O.D. Quiz System, Dept A, 1435 Flower St., Glendale Calif. No. 13

Services & Instruction

Instruction

AIR NAVIGATION INSTRUCTION. First Lesson free Practical correspondence course teaches essentials for navigating aircraft Chart work use of sextant, compass and other instruments. Capt E. O Carlson, 48 William St., Orange, N J (Instructor Newark YMCA Navigation School) No. 14

Employment Service

MEN-SALARIED POSITIONS—WOMEN $2,500 to $15,000. Our confidential system promotes you for high salaried positions at small cost. Without obligation write for testimonials and valuable information No. M 37 "Executives" Promotion Service, Washington D. C.

Employment

Positions Vacant

PURCHASING AGENT WANTED by inland aircraft factory with aggressive development program one thoroughly experienced in aviation industry, familiar with suppliers and effective in dealing with them. P 568, Aviation, 520 N. Michigan Ave., Chicago, Ill.

Positions Vacant

CHIEF ENGINEER WANTED, by inland aircraft factory with aggressive development program one who has studied markets and is thoroughly experienced in aeronautical design Address P 569 Aviation 520 N. Michigan Ave., Chicago, Ill

PILOT with new CAA Instructor Rating for year round job Must have following qualifications, bookkeeping education and experience office management experience and preferably stenographic training. Apply P 570 Aviation, 330 West 42nd St., New York, N. Y

Positions Wanted

PHOTOGRAPHER—desires position mfg. concern 15 years experience commercial and portrait—furnish all equipment, also mechanically inclined Atlantic Coast preferred PW 571 Aviation, 330 West 42nd St., New York N. Y.

Wanted

Wanted Fleet Ryan First class condition Give lowest price first. R. W. Brthee, P.O. Box 1190 Chattanooga Tennessee.

Business Opportunities

Parachute Opening Device

For Sale/ Automatic parachute opening device, has many uses Weighs 28 ounces (840 grams), fits any type of chute Outright or royalty. E Lanrlain 420 Dollar Bank Bldg., Youngstown, Ohio

When You Need Quick Action . . .

on Opportunities available or wanted in AVIATION

Use

The "MARKET PLACE" OF AVIATION

Published Each Month

Copy received until May 15 for the June issue.

AVIATION'S MARKET PLACE

THEY USED AVIATION'S "Market Place"

"I sold my aeroplane in four days after the Ad appeared. I could have sold it ten times."

"I received forty replies and Five Cash Offers as the result of my advertisement in Aviation Classified."

"Every Instrument listed (there were 51 listed) sold—the day after the Ad appeared."

"The Advertised Engine was sold to a customer who stated he saw the Ad in Aviation."

Contact!

A word that still means a lot to men who fly! Especially men who own their own planes or are in the market to buy, sell or trade used planes, engines or parts. To these men "Contact" means locating the buyer or seller who wants what they have or has what they want and—That is the "Contact" you can make among over 100,000 readers through advertising in

Aviation's "Market Place"

AVIATION'S MARKET PLACE

WHERE TO BUY

(SUPPLEMENT)

New Equipment — Accessories — Materials — Supplies — Services

PHENIX
AIRPLANE DOPES
CLEAR and PIGMENTED
PHENIX AIRCRAFT PRODUCTS CO
5565 Main St — Williamsville N Y

Fatigue Resistant!
Beryllium Copper Fuse Clip
A better clip for aero-service! Has high corrosion resistance, high tensile strength. Spring qualities equal steel, 4 sizes. Write for test samples.
LITTELFUSE INCORPORATED
4740 Ravenswood Ave. — Chicago, Illinois

American FleeShip

Universal Aircraft Co., Inc., Fort Worth, Texas

SUPPLIES
Complete Line of Aircraft, Engine & Pilot Supplies. Lowest Prices. Write for booklet
Aeronautical Trading Co.
Floyd Bennett Airport, Brooklyn, N.Y.

STANDARD AIRCRAFT FINISHES
Since 1913
TITANINE
TITANINE INC. — UNION, N. J.

COPY for
"MARKET PLACE" Advertisements
in the
June Issue of AVIATION
Required by
MAY 15th

AVIATION SCHOOLS

Aeronautical Engineering — Ground — Mechanics

Flying — Instrument

COMPLETE COURSE in AERIAL SURVEY PILOTING
Good mapping pilots are still in demand!
Instruction by experienced mapping pilots and aerial photographers. Class and air instructions including 4 hours on Link Trainer. Only pilots with commercial and 2S rating eligible. Tuition reasonable.
STANDARD AERIAL SURVEYS, INC.
56 Park Place, Newark, New Jersey

Learn
INSTRUMENT FLYING
where airline pilots fly
Sunderph Aeronautical Corp.
CLEVELAND MUNICIPAL AIRPORT

DANIEL GUGGENHEIM SCHOOL OF AERONAUTICS
Undergraduate and Graduate Courses in Aeronautical Engineering and Air Transport. Write to Dean
COLLEGE OF ENGINEERING
NEW YORK UNIVERSITY
University Heights — New York N Y

Learn
AIRPLANE DESIGNING
Step out of the rut type of job into a position with unlimited future. No previous training necessary. Courses are approved by the industry and written by leading engineers.
Send for free booklet today
WESTWOOD CORRESPONDENCE SCHOOL
415 Village Station, Los Angeles, Calif.

AVIATION

APPRENTICES
MECHANIX UNIVERSAL AVIATION SERVICE CO
Wayne County Airport, Dept. F — Detroit, Mich

AVIATION INSTITUTE of NEW YORK
24-15 N. Bridge Plaza North
Long Island City, New York
C.A.A. Recognized—N. Y. State Licensed Aircraft & Engine Courses
Division of FRANK AMBROSE Inc.
Dealers & Exporters
Airplanes, Engines & Accessories

AEROPLANE MECHANIC COURSES
PRACTICAL FACTORY WORK ONLY
CHAMBERLIN
School of Aeronautics
BENDIX AIRPORT — BENDIX, N. J.

Further evidence of RESULTS!
"Sold my ship to good advantage within 3 days after your magazine appeared."
If you have a used plane, engine or equipment to sell—why not put the proved effectiveness of AVIATION "Classified" to work for you

AVIATION'S MARKET PLACE

AVIATION SCHOOLS

Aeronautical Engineering — Ground — Mechanics

Flying — Instrument

(Continued from opposite page)

AVIATION WANTS *LUSCOMBE* GRADUATES

There is an unprecedented demand for young men who have had practical training in modern airplane construction maintenance and repair.

At Luscombe you will receive your training on a 240 acre Airport where a wide variety of aviation activities are constantly in progress including the manufacture of all metal aircraft maintenance and repair of both airplanes and engines parachute testing CAA flight training general flying flight testing, etc. Add to this environment a complete Master Mechanic's Course under the direction of Government Licensed Instructors with many years of practical experience and you will understand the success of Luscombe Graduates wherever airplanes are built, serviced or repaired.

NEXT CLASS STARTS JULY 8TH

DON'T DELAY—Send today for free copy of "Opportunity in Aviation" and our School Paper "Luscombe Highlight" Address Dept "B"

Over 90% of our Graduates placed! —a job is waiting for YOU.

ONE YEAR GOVERNMENT APPROVED COURSE leading to an A.&E. License or to Specialization in Factory Production of Modern Airplanes

LUSCOMBE
SCHOOL OF AERONAUTICS
(Division of Luscombe Airplane Corp.)
Dept. "B" — WEST TRENTON, N. J.

Prepare for a Well Paid Career in— *Aeronautical Engineering*

57th YEAR

DEGREE IN 2¼ YEARS

Bachelor of Science Degree in 132 weeks.

Write for catalog. Burton Handy, President
510 COLLEGE AVE — ANGOLA, IND.
TRI-STATE COLLEGE

Learn the Mystery OF THESE CROWDED PANELS

. . . Be An *Instrument Technician*

Secure the knowledge and abilities to be the MAN IN DEMAND in Aviation—the instrument technician. American Tech has on file standing requests for trained instrument men—so prepare now for positions with instrument makers, aircraft plants and air lines. Choice of four training plans —one all home study. Send coupon NOW

AMERICAN SCHOOL OF AIRCRAFT INSTRUMENTS
Dept. A-5

Name ______ Age ______
Address ______
City ______ State ______

A-5

Would you like to know **AIRPLANE STRENGTH ANALYSIS**
WESTWOOD CORRESPONDENCE SCHOOL
415 Village Station, Los Angeles, California

For Additional Advertising of
SCHOOLS
See Opposite Page

RISING SUN GRADUATES *Are in Aviation*

Send for New Illustrated Catalog
RISING SUN SCHOOL OF AERONAUTICS
101 WEST ROOSEVELT BLVD., PHILA.
A Government Licensed and Approved School

INDEX TO ADVERTISERS

SCHOOLS

AVIATION'S MARKET PLACE

(CLASSIFIED ADVERTISING)

(CLASSIFIED DISPLAY ADVERTISING)



Air Transport

CLIMBS TO NEW HEIGHTS

THE NEW BOEING 307
"STRATOLINERS" FOR
TWA AND PAN AMERICAN

CONGRATULATIONS—To Boeing, for another outstanding contribution to the progress of commercial air transportation—

And to TWA and Pan American for their selection of the new Boeing 307 "Stratoliners."

Eclipse is justifiably proud of the fact—that once again—a complete line of Eclipse Accessory Equipment has been selected to participate in this latest engineering achievement.

ECLIPSE AVIATION
DIVISION OF BENDIX AVIATION CORPORATION
BENDIX, NEW JERSEY, U. S. A.

Eclipse- EQUIPPED!

ECLIPSE PRODUCTS USED ON BOEING 307 AIRPLANES—Direct Cranking Electric Starters—Solenoid Relays—Battery Booster Coils—Single Voltage DC Generators—Autosyn Alternators and Dynamotors—Landing Gear, Flap and Tail Wheel Retracting Motors—Propeller Anti-Icer Pumps and Rheostats—Air Check Valves—Vacuum Instrument and De-Icer Pumps—De-Icer Distributing and Control Valves—Engine Synchroscopes.